

# County Surveyor's Record, Douglas County, Oregon

1907

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The depression from which a sandstone boulder,  
10 x 8 x 5ft., has been dislodged, bears  
South, 4 1/2 lks. dist., the boulder now  
bears South, 15 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins.  
in the ground, to solid-rock, and in a mound of stone, 5 ft.  
base, to top, with brass cap mkd.

W C  
T 22 S R 9 W  
S 8  
C 38  
1970

from which new bearing objects

A sandstone bluff, 20 ft. long, 20 ft. high, faces  
S., bears N. 51 1/4° W., 6 1/2 lks. dist., mkd. X BO.  
This is same bluff as recorded in original survey.

A sandstone boulder, 6 x 5 x 4 ft. above ground,  
bears S. 21 1/2° E., 8 1/2 lks. dist., mkd. X BO.

From this same point, the true point for the NW. cor. of Donation  
Land Claim No. 38, bears S. 89° 05' W., 37.43 chs. dist. This  
corner is not monumented.

From true point, the witness cor. for the NW. cor. of Donation  
Land Claim No. 38, bears N. 89° 05' E., 8.37 chs. dist.,  
monumented with the remains of the original corner tree, a decayed  
fir stump, 36 ins. diam., no marks visible, from which the remains  
of the original corner accessories:

A maple root crown, bears North, 15 lks. dist.

A sandstone boulder, 30 x 15 x 15 ft. above ground,  
bears South, 25 lks. dist., no marks visible.

Descend 15 ft. over N. slope.

52.55 Bottom of descent, slopes E.; asc. 360 ft. over broken S. slope.

52.85 State Highway No. 38, 30 lks. wide, bears N. 75° E. and S. 75° W.

64.95 Gravelled road, 15 lks. wide, bears N. 55° E. and S. 55° W.

78.87 The cor. of secs. 6 and 7 only, on the W. bdy. of sec. 8,  
determined at record distance from the original bearing trees:

A fir, stump, 20 ins. diam., bears N. 57° E., 66 lks.  
dist., with healed blaze. (Record, N. 59 1/4° E.)

A decayed fir stump, 22 ins. diam., bears  
S. 65° E., 48 lks. dist., with no marks visible.  
(Record, S. 59 1/2° E.)

A fir, 35 ins. diam., bears S. 58° W., 57 lks.  
dist., with a healed blaze and scribe marks CS  
visible on bark blaze. (Record, S. 56° W.)