

**Dependent Resurvey of the East Boundary  
of Donation Land Claim No. 39,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS

From this same point, the crossing closing corner of secs. 4 and 5, bears N. 89° 16' W., 0.040 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 22 S R 9 W  
CCC  
S 5 | S 4  
-----  
C 39  
1985

from which bearing trees mkd. by Robb in 1985

A fir, 14 ins. diam., bears S. 83° E., 26 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 7° W., 19 lks. dist., with healed blaze.

**Dependent Resurvey of a Portion of the North Boundary  
of Donation Land Claim No. 40,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

From the NE. cor. of Donation Land Claim No. 40, perpetuated by person(s) unknown, utilized by Richard J. Hintz, Registered Land Surveyor No. 497, in 1971, recorded in the Douglas County Courthouse file No. M 42-40, this point is harmoniously related to other original corners and is accepted as the best available evidence of the original corner; monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground. No accessories found.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T22S R9W  
S 9  
C 40 |  
1996

from which

A fir, 29 ins. diam., bears S. 58 3/4° W., 32 lks. dist., mkd.  
T22S R9W C40 BT.

No other suitable accessories available.

From this point, the SE. cor. of Donation Land Claim No. 40, bears S. 0° 03' 19" W., 39.332 chs. dist., perpetuated by person(s) unknown, and recorded by Richard J. Hintz, Registered Land Surveyor No. 1305, in 1971, recorded in the Douglas County Courthouse file No. M 42-40, and utilized by Philip R. Ekelund, Registered Land Surveyor No. 1077, in 1989, recorded in the Douglas County Courthouse file No. M 109-59; monumented with an iron pipe, 1 in.