Dependent Resurvey of a Portion of the North Boundary of Donation Land Claim No. 40, T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	diam., firmly set, projecting 8 ins. above ground. Alongside this iron pipe is an iron bolt, ½ in. diam., firmly set, projecting 6 ins. above ground, with a metal cap mkd. LOT CORNER.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 S | R 9 W C 40 | S 16 1996
	from which the remains of the original bearing trees
	A fir snag, size indeterminate, bears S. 40° W., 73 lks. dist., no marks visible. (Record, 67 lks.)
	A fir snag, size indeterminate, bears S. 56° W., 122½ lks. dist., no marks visible. (Record, 120 lks.)
	and a new bearing tree
	A fir, 21 ins. diam., bears North, 50 lks. dist., mkd. T22S R9W C40 BT.
	Deposit a ½ in. iron bolt alongside and a 1 in. iron pipe and a magnet in a white plastic case at the base of the stainless steel post.
	S. 62° 45' 46" W., on the N. bdy. of Donation Land Claim No. 40.
	Descend over broken NW. slope through light timber and dense undergrowth.
18.516	Intersect the line between secs, 8 and 9, point for the crossing closing corner, hereinbefore described.
	From this point, the angle point between secs. 8 and 9 bears S. 1° 07' 54" E., 1.295 chs. dist.
19.796	The SE. cor. of Donation Land Claim No. 39, located on the N. bdy. of Donation Land Claim No. 40, hereinbefore described.

Subdivision of Section 3, T. 22 S., R. 9 W., Willamette Meridian, Oregon

	From the 1/4 sec. cor. of secs. 3 and 10.
	N. 0° 33' 55" E., on the N. and S. centerline of sec. 3.
	Ascend over E. slope through moderate timber and dense undergrowth.
16.30	Spur, slopes S. 60° E.; desc. over NE. slope.
19.95	Ravine, drains S. 40° E.; asc. over SW. slope.