

County Surveyor's Record, Douglas County, Oregon

16410

Dependent Resurvey of a Portion of Boundaries of
Donation Land Claim No. 46,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

| CHAINS | | | | | | |
|------------|---|---|------------|---|--------|------|
| | <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 53° W., 36 lks. dist., mkd. C 46 BT.</p> | | | | | |
| | <p>S. 89° 43' W., on the N. bdy of Claim No. 46.</p> <p>Ascend 20 ft. over NE slope.</p> | | | | | |
| 1.20 | Ridge, bears N. 40° W. and S. 40° E.; desc. 180 ft. over broken SW slope. | | | | | |
| 15.72 | <p>Intersect the N. and S. center line of the SE 1/4 of sec. 15.</p> <p>The crossing closing cor. of the N. and S. center line of the SE 1/4 of sec. 15, with the N. bdy. of Claim No. 46, established and recorded by Donald A. Bentz, Registered Land Surveyor No. 839, in 1979, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which a bearing tree mkd. by Bentz:</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 59 3/4° E., 6 1/2 lks. dist., with scribe marks BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">E</td></tr> <tr><td style="padding: 0 5px;">CCC S 15</td></tr> <tr><td style="padding: 0 5px;">E</td></tr> <tr><td style="padding: 0 5px;">DLC 46</td></tr> <tr><td style="padding: 0 5px;">1979</td></tr> </table> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 10 1/2° W., 135 lks. dist., mkd. T24S R4W S15 CCC BT.</p> <p style="padding-left: 40px;">Reset iron rod alongside iron post.</p> <p>From this point, the SE 1/16 sec. cor. of sec. 15, bears S. 0° 09' E., 7.58 chs. dist., hereinafter described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 43' W., beginning new measurement.</p> <p>Descend 160 ft. over SW slope.</p> | E | CCC S 15 | E | DLC 46 | 1979 |
| E | | | | | | |
| CCC S 15 | | | | | | |
| E | | | | | | |
| DLC 46 | | | | | | |
| 1979 | | | | | | |
| 7.60 | Bottom of descent, slopes S.; asc. 40 ft. over SE slope. | | | | | |
| 15.50 | Spur, slopes S.; desc. 160 ft. over SW slope. | | | | | |
| 19.89 | Intersect the N. and S. center line of sec. 15. | | | | | |
| 25.30 | Creek, 1 lk wide, course S. 40° W.; desc. 35 ft. over broken SW slope. | | | | | |
| 27.55 | Creek, 1 lk. wide, course S.; asc. 130 ft. over SE slope. | | | | | |
| 35.50 | Spur, slopes S.; desc. 20 ft. over SW slope. | | | | | |