

County Surveyor's Record, Douglas County, Oregon

16415

Subdivision of Section 15, T. 24 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears S. 31 1/2° W., 28 1/2 lks. dist. with scribe marks CW 1/16 S15 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16
C ————— C
S 15
1979

Reset iron rod alongside iron post.

S. 89° 26' W., beginning new measurement.

Descend 100 ft. over SW. slope.

5.80 Bottom of descent, slopes S.; asc. 65 ft. over SE. slope.

19.71 The 1/4 sec. cor. of secs. 15 and 16.

From the E 1/16 sec. cor. of secs. 15 and 22.

N. 0° 09' W., on the N. and S. center line of the SE 1/4 of sec. 15.

Ascend 30 ft. over SW. slope, through scattering timber and dense undergrowth.

2.20 Ridge, bears N. 75° W. and S. 75° E.; desc. 40 ft. over NE. slope.

5.65 Ravine, drains W.; asc. 20 ft. over SW. slope.

11.15 Ridge, bears N. 70° E. and S. 70° W.; desc. 5 ft. over NW. slope.

13.90 Creek, 2 lks. wide, course W.; asc. 30 ft. over SW. slope.

17.30 Head of ravine, drains W.; asc. 45 ft. over SW. slope.

19.95 Point for the SE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the SE 1/4 of sec. 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16 S 15
1979

from which

An oak, 8 ins. diam., bears S. 28 3/4° E., 54 1/2 lks. dist., mkd. SE 1/6 S15 BT.

An oak, 12 ins. diam. bears N. 23° W., 64 1/2 lks. dist., mkd. SE 1/16 S15 BT.

Ascend 165 ft. over SW. slope.

27.53 Intersect the N. bdy. of Donation Land Claim No. 46.