

Dependent Resurvey of a Portion of Donation Land Claim No. 41,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A decayed fir stump, size indeterminate, bears S. 70½° E., 57 lks. dist., no marks visible.</p> <p>and the remains of accessories by Boyer</p> <p>A sawed fir stump, 39 ins. diam., bears N. 58° E., 95 lks. dist., no marks visible.</p> <p>A power pole, 12 ins. diam., bears N. 12° W., 153 lks. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R4W C41</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S16 1995</p> </div> <p>from which new bearing trees</p> <p>A madrone, 12 ins. diam., bears S. 35½° W., 14 lks. dist., mkd. S16 BT.</p> <p>A fir, 14 ins. diam., bears N. 35 3/4° W., 10 lks. dist., mkd. C41 BT.</p> <p>Deposit the iron rod inside and a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>N. 89° 40' 21" W., on the S. bdy. of Donation Land Claim No. 41.</p> <p>Ascend over SE. slope, through moderate timber and undergrowth.</p>
1.05	Dirt road, 15 lks. wide, bears N. 10° E. and S. 10° W.
1.30	Ridge, bears N. 10° E. and S. 10° W.; desc. over SW. slope.
6.465	Intersect the line bet. secs. 16 and 17, point for the crossing closing corner hereinbefore described.
	<p>From this point, the S 1/16 sec. cor. of secs. 16 and 17 bears S. 0° 43' 17" W., 9.601 chs. dist., hereinbefore described.</p> <p>Descend over SW. slope.</p>
17.30	Bonanza Mine Road, graveled, 30 lks. wide, bears N. 5° W. and S. 5° E.
17.40	Power transmission line, extends N. 10° W. and S. 10° E.
17.70	Foster Creek, 3 lks. wide, course N. 5° W.; asc. over E. slope.
26.506	Intersect the N. and S. center line of the SE 1/4 of sec. 17, point for the crossing closing corner hereinafter described.
	<p>From this point, the SE 1/16 sec. cor. of secs. 17 bears S. 0° 31' 58" W., 9.272 chs. dist., hereinafter described.</p>