

Dependent Resurvey of a Portion of Donation Land Claim No. 41,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
29.510	<p>Ascend over E. slope.</p> <p>The SW. cor. of Donation Land Claim No. 41, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1939, recorded in the Douglas County Surveyors Office corner renewal file for this Tp., point identifier No. 041050, determined at the center of the remains of the original corner tree, a sawed and decayed fir stump, 19 ins. diam., from which the remains of the original accessories which were remarked by Irving:</p> <p style="padding-left: 40px;">A rock, 2½ x 2½ x 3 ft., bears N. 56¼° E., 14 lks. dist., mkd. CL41 on the S. face and an X on the SW. face. (Record, N. 50° E., 13 lks.)</p> <p style="padding-left: 40px;">A sawed decayed fir stump, 22 ins. diam., bears N. 87 ¾° E., 17 lks. dist., no marks visible on decayed face. (Record, N. 89° E., 16 lks.)</p> <p style="padding-left: 40px;">A sawed fir stump, 37 ins. diam., bears N. 19 ¾° W., 5 lks. dist., with scribe marks S C4 CS B visible on a bark blaze. (Record, N. 30° W., 3 lks.)</p> <p>At the corner point.</p> <p>Drive a rebar, 48 ins. long, ¾ in. diam., 44 ins. in the ground, through the remains of the original corner tree, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T25S R4W</p> <div style="border: 1px solid black; display: inline-block; padding: 2px 10px;">C41</div> <p>S17</p> <p>1995</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 13¼° E., 22 lks. dist., mkd. C41 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 78¼° E., 26½ lks. dist., mkd. S17 BT.</p>
10.722	<p>N. 0° 00' 36" E., on the W. bdy. of Donation Land Claim No. 41.</p> <p>Ascend over E. slope changing to desc. over E. slope, through moderate timber and undergrowth.</p> <p>Intersect the E. and W. center line of sec. 17, point for the crossing closing corner hereinafter described.</p> <p>From this point, the center E 1/16 sec. cor. of sec. 17 bears S. 89° 23' 43" E., 3.102 chs. dist., hereinafter described.</p> <p>Descend over E. slope.</p>
29.90	<p>Spur, slopes N. 65° E.; continue descending over broken NE. slope.</p>
30.792	<p>Intersect the E. and W. center line of the NE 1/4 of sec. 17.</p>