

Dependent Resurvey of a Portion of Donation Land Claim No. 41,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

An oak, 18 ins. diam., bears S. 68° W., 25 lks. dist., with partially healed blaze.

and bearing trees mkd. by Irving

An oak, 13 ins. diam., bears N. 29¼° E., 28½ lks. dist., with healed blaze.

An oak, 14 ins. diam., bears S. 6¼° W., 81 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Byron

An oak snag, 10 ins. diam., bears S. 13½° E., 41 lks. dist., with healed blaze.

Search was made for original evidence of the exterior "L" corner and the NW. cor. of Donation Land Claim No. 41, none of which were recovered.

Subdivision of Section 16,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 16 and 21, determined at recorded distances from the bearing trees mkd. by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, recorded in the Douglas County Surveyors Office corner renewal file for this Tp., point identifier No. 340400; from which the remains of a bearing tree mkd. by Zirpel, Roseberry, and Corbin:

A fir snag, bears S. 48° W., 91 lks. dist., with fallen trunk alongside, 13 ins. diam., with scribe marks 1/4 S21 BT visible on decayed open blaze. (Record, S. 46° W., 92½ lks.)

and the remains of bearing trees mkd. by Tracy

An oak, 10 ins. diam., bears S. 79 3/4° E., 45 lks. dist., with healed double blaze.

A sawed fir stump, 19 ins. diam., bears N. 2 3/4° W., 83 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.

T25S R4W
S16
1/4 ———
S21
1995

from which a new bearing tree

A fir, 6 ins. diam., bears N. 20 3/4° E., 98 lks. dist., mkd. 1/4 S16 BT.