

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

<p>CHAINS 43.530</p>	<p>The cor. of secs. 6 and 7, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Boundaries of Donation Land Claim No. 50, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the survey by Josiah A. Burnett and Elliott N. Bowman, U.S. Deputy Surveyors, in 1855-56)</p> <hr/> <p>From the SW. interior L cor. of Donation Land Claim No. 50, identical with the N.-NW. cor. of Donation Land Claim No. 53, perpetuated by Arthur Boyer, Registered Professional Engineer No. 1581, in 1947, recorded in the Douglas County Surveyors Office map file, M29-9, further perpetuated by Randall W. Smith, Deputy County Surveyor, in 1987, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 265; monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYORS OFFICE T28S R7W S27</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">NNW</td> <td style="border-top: 1px solid black; border-right: 1px solid black; padding: 2px;">DLC 53</td> </tr> </table> <p style="text-align: center;">1987</p> <p>from which a bearing tree marked by Boyer</p> <p style="padding-left: 40px;">An oak, 28 ins. diam., bears S. 40° W., 227 lks. dist., no marks visible on opened blaze.</p> <p>and bearing trees mkd. by Smith</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 72 3/4° E., 75 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 32½° E., 75 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. 50¼° W., 184 lks. dist., with healed double blaze.</p> <p>Found an iron pipe, 1 in. diam., buried alongside the iron post.</p> <p>The corner is located at a fence corner with barbed wire fence extending W. and woven wire fence extending S.</p> <p>N. 89° 54' 00" E., on the S. bdy. of Claim No. 50, a portion of which is identical with the N. bdy. of Claim No. 53.</p> <p>Over nearly level ground, through populated area.</p> <p>9.35 Asphalt road, 35 lks. wide, bears NE. and SW.</p> <p>11.10 Lookingglass Creek, 60 lks. wide, course N. 60° E.; continue over nearly level ground.</p>	NNW	DLC 53
NNW	DLC 53		