

Dependent Resurvey of A Portion of the  
Boundaries of Donation Land Claim No. 50,  
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS									
	<p>from which</p> <p>An ash, 22 ins. diam., bears S. <math>6\frac{1}{2}^{\circ}</math> E., 290 lks. dist., mkd. X BT.</p> <p>A stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 22 ins. in the ground, for a reference monument, bears S. <math>64^{\circ}</math> E., 233.2 lks. dist., with brass cap mkd. RM C50 154 FT TO COR 1993 and an arrow pointing to the corner.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The reference monument is located in a woven wire fence extending N. <math>65^{\circ}</math> E. and S. <math>65^{\circ}</math> W.</p> <p>The NE. abutment of a concrete bridge spanning Lookingglass Creek, bears S. <math>70\frac{3}{4}^{\circ}</math> W., 6.28 chs. dist.</p> <hr/> <p>N. <math>89^{\circ} 54' 00''</math> W., on the N. bdy. of Claim No. 50.</p> <p>Over level ground, through scattered brush and fields.</p>								
8.75	Lookingglass Creek, 1 ch. wide, course N. $25^{\circ}$ W.; continue over rolling ground, through scattered brush and fields.								
30.70	County Road No. 108 (Strickland Canyon Road), asphalt-surfaced, 40 lks. wide, bears N. $65^{\circ}$ E. and S. $65^{\circ}$ W.								
36.50	Graveled road, 20 lks. wide, bears N. $10^{\circ}$ W. and S. $10^{\circ}$ E.								
45.90	Creek, 2 lks. wide, course S. $30^{\circ}$ E.; asc. over gradual broken SE. slope.								
59.75	Creek, 5 lks. wide, course S. $20^{\circ}$ E.; asc. over gradual SE. slope.								
72.190	<p>Point for the NW. cor. of Donation Land Claim No. 50, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 32 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding-right: 10px;">T28S</td> <td style="border-left: 1px solid black; padding-left: 5px;">R7W</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S28</td> </tr> <tr> <td style="padding-right: 10px;">C55</td> <td style="border-left: 1px solid black; padding-left: 5px;">C50</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">1993</td> </tr> </table> </div> <p>from which</p> <p>A pine, 17 ins. diam., bears S. <math>72\frac{1}{2}^{\circ}</math> E., 359 lks. dist., mkd. X BT.</p> <p>A pine, 17 ins. diam., bears S. <math>9\frac{1}{2}^{\circ}</math> E., 287 lks. dist., mkd. C50 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>	T28S	R7W		S28	C55	C50		1993
T28S	R7W								
	S28								
C55	C50								
	1993								