

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 50,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>The corner is located in an open field.</p> <hr/> <p>S. 0° 14' 00" W., on the W. bdy. of Claim No. 50.</p> <p>Over nearly level ground, through scattered brush and fields.</p> <p>24.90 State Highway No. 42, asphalt-surfaced, 55 lks. wide, bears N. 70° E. and S. 70° W.</p> <p>54.910 The SW. cor. of Donation Land Claim No. 50, identical with the most westerly NW. cor. of Donation Land Claim No. 53, and on the E. bdy. of Donation Land Claim No. 51, perpetuated by Arthur Boyer, Registered Professional Engineer No. 1581, in 1947, recorded in the Douglas County Surveyors Office map file, M29-9, further perpetuated by Herbert L. Northcraft, Registered Land Surveyor No. 750, in 1972, recorded in the Douglas County Surveyors Office map file, M44-41; monumented with an iron rod, 5/8 in. diam., firmly set flush with the ground, from which the remains of a bearing tree mkd. by Boyer:</p> <p style="padding-left: 40px;">A fir snag, 18 ins. diam., bears N. 23½° E., 9¼ lks. dist., with scribe marks C 158 visible on open decaying blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T28S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R7W</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 10px;">C50</td> </tr> <tr> <td style="padding: 0 10px;">C51</td> <td style="border-left: 1px solid black; padding: 0 10px;">C53</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1993</td> </tr> </table> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 42° E., 41 lks. dist., mkd. C50 BT.</p> <p style="padding-left: 40px;">A maple, 13 ins. diam., bears S. 26½° E., 49 lks. dist., mkd. C53 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located at a fence corner with woven wire fences extending N., S., and E.</p> <hr/> <p>NOTE: The SE. cor. of Donation Land Claim No. 55, identical with the NE. cor. of Donation Land Claim No. 51, was searched for but not recovered.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of A Portion of the Boundaries of Donation Land Claim No. 53, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p>	T28S	R7W		C50	C51	C53	1993	
T28S	R7W								
	C50								
C51	C53								
1993									