

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 53,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

(Restoring the survey by Josiah A. Burnett and
Elliott N. Bowman, U.S. Deputy Surveyors, in 1862)

From the point for the NE. cor. of Donation Land Claim No. 53, on the S. bdy. of Donation Land Claim No. 50, determined by the compass rule method; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.

T28S	R7W
C50	

C53	S27
1993	

from which

A pine, 8 ins. diam., bears S. 0 3/4° W., 78 lks. dist., mkd. C53 BT.

An oak, 12 ins. diam., bears S. 30 3/4° W., 105 lks. dist., mkd. C53 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located South, 0.25 chs. dist. of a dirt road, 15 lks. wide, bears E. and W.

S. 0° 05' 00" E., on the E. bdy. of Claim No. 53.

Ascend over broken NW. slope, through heavy timber and moderate undergrowth.

31.45 Ridge, bears N. 35° E. and S. 35° W.; desc. over broken SE. slope.

38.685 Intersect the section line between secs. 27 and 34.

Point for the crossing closing cor. of the section line between secs. 27 and 34 with the E. bdy. of Donation Land Claim No. 53, hereinbefore described.

From this point, the 1/4 sec. cor. of secs. 27 and 34 bears N. 86° 18' 00" W., 15.555 chs. dist.

44.970 Point for the SE. cor. of Donation Land Claim No. 53, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T28S	R7W
C53 S34	

1993	

from which