

Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 53,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS							
	Descend over NE. slope, through moderate timber and light undergrowth.						
15.90	Tenmile Creek, 30 lks. wide, course S.; continue over level ground.						
41.80	Tenmile Creek, 30 lks. wide, course NE.; asc. over NW. slope.						
59.670	The SW. interior L cor. of Donation Land Claim No. 53, identical with the SE. cor. of Donation Land Claim No. 51, perpetuated by George J. Wenderoth, Deputy County Surveyor, in 1946, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 102, further perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 162; monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground.						
	At the corner point						
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T28S</td> <td style="padding: 0 10px;">R7W</td> </tr> <tr> <td style="padding: 0 10px;">C51</td> <td style="padding: 0 10px;">C53</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table>	T28S	R7W	C51	C53	1993	
T28S	R7W						
C51	C53						
1993							
	from which new bearing trees						
	An oak, 7 ins. diam., bears N. 36 3/4° E., 94 lks. dist., mkd. C53 BT.						
	An oak, 7 ins. diam., bears S. 85¼° W., 35½ lks. dist., mkd. X BT.						
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.						
	The corner is located South, 0.03 chs. dist. of a woven wire fence extending E. and W., and North, 0.48 chs. dist. of a dirt road, 15 lks. wide, bears N. 60° W. and S. 40° E.						
	<hr/> Subdivision of Section 7, T. 28 S., R. 7 W., Willamette Meridian, Oregon <hr/>						
	From the 1/4 sec. cor. of secs. 7 and 18.						
	N. 1° 47' 00" E., on the N. and S. center line of sec. 7.						
	Ascend over S. slope, through heavy timber and moderate undergrowth.						
7.80	Ridge, bears E. and W.; desc. over N. slope.						
12.70	Creek, 5 lks. wide, course N. 80° W.; asc. over S. slope.						
19.325	Point for the center S 1/16 sec. cor. of sec. 7.						