

County Surveyor's Record, Douglas County, Oregon

John Coats Donation Land Claim, Nos. 38 and 59.
Tps. 28 S., Rs. 7 and 8 W.

66

CHAINS

- 37, 9 lks. N89*29'W. from the SE. cor. thereof.
- 20.00 Set an iron post, 3 ft. long, 1 in. diam., 28ins. in the ground, for SW. cor. No.3 of D.L.C. No. 38, with brass cap marked
- DLC 38
AP3
- 1924
- from which
- A white oak, 8 ins. diam., bears N.26 $\frac{3}{4}$ *E., 72 lks. dist., marked A P 3 D L C 38 B T.
- A fir, 30 ins. diam., bears N.53*E., 70 lks. dist., marked A P 3 D L C 38 B T.
- Thence
- N.89*14'E., along the S. bdy. of claim No. 38.
- 7.37 Intersect E. bdy. of T.28 S., R. 8 W., 10.96 chs. S.0*07'W. from the cor. of secs. 25 and 36, hereafter described.
- 7.50 Intersect the SE. cor. of the John Coats D.L.C. No. 38, which is a conglomerate stone, 10x6x6 ins. above ground, at fence cor. I designate this cor., Cor. No.4 and mark A P 4 on NE. face; from which
- A white oak, 40 ins. diam., bears S.88 $\frac{1}{2}$ *E., 305 lks. dist., marked A P 4 D L C 59 B T.
- A white oak, 12 ins. diam., bears N.50*W., 476 lks. dist., marked A P 4 D L C 38 BT.
- Thence
- S.0*22'W., along the W. bdy. of claim No.59.
- Along fence.
- 20.12 Intersect the SW. cor. of Claim No.59, which is a sandstone, 12x10x6 ins. above ground. I designate this cor., Cor.No. 5, and mark A P 5 on NE. face; from which
- A white oak, 6 ins. diam., bears N.38*E., 177 lks. dist., marked A P 5 D L C 59 B T.
- No other tree available.
- Find no trace of the old original cor.