

County Surveyor's Record, Douglas County, Oregon

17395

Dependent Resurvey, Portion of South Boundary
Donation Land Claim No. 40,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C 40

T 28 S
R 8 W

S 23
1984

from which

An alder, 16 ins. diam., bears N. 22° E., 15 1/2 lks. dist., bark scribed C 40 BT.

An ash, 11 ins. diam., bears N. 89 1/2° E., 32 lks. dist., mkd. C 40 BT.

The corner is located 50 lks. east of Tenmile Creek, 25 lks. wide, course S. 70° E.

From this point, the SW. cor. of Donation Land Claim No. 40, bears S. 89° 39' W., 55.34 chs. dist., perpetuated and recorded by Arthur R. Evans, Registered Mining Engineer No. 2741, in 1951, from original evidence no longer in existence, further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of a bearing tree mkd. by Evans

A root hole, bears N. 30° E., 54 lks. dist., with down cedar alongside, size indeterminate, with scribe marks SW CL 40 BT visible on decayed blaze.

and bearing trees mkd. by Powell

A fir, 17 ins. diam., bears N. 5 1/4° E., 77 lks. dist., with healed blaze.

A fir, 13 ins. diam., bears N. 37 1/2° W., 64 lks. dist., with healed blaze.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., with magnetic plastic breakaway base, 24 ins. in the ground, with brass cap mkd.

T 28 S
R 8 W

C 40

S 22

1984

Subdivision of Section 21,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.