

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Boundaries 18409
of Donation Land Claim No. 41,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| 22.36 | Intersect the N. and S. center line of the NE $\frac{1}{4}$ of sec. 15. Point for the crossing closing corner, hereinafter described. Descend over SE. slope. |
| 22.85 | Power transmission lines, bears N. 50° E. and S. 50° W. |
| 25.65 | Coos Bay Wagon Road, paved surface, 30 lks. wide, bears N. 40° E. and S. 30° W. |
| 58.30 | County Road No. 5A, paved surface, 30 lks. wide, bears N. and S. |
| 63.10 | Creek, 10 lks. wide, course S. 20° W.; asc. over broken SW. slope. |
| 97.60 | Ridge, bears N. 55° E. and S. 35° W.; desc. over broken NE. slope. |
| 122.10 | Creek, 5 lks. wide, course S. 45° W. from N. 35° E.; asc. over gentle W. slope. |
| 123.36 | Point for the NE. cor. of Donation Land Claim No. 41, at proportionate position, determined by the Grant boundary method; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 28 S R 8 W C 41 S 13 1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears S. 5° W., 89 lks. dist., mkd. C41 BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 49° W., 131 lks. dist., mkd. X BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> |
| 25.30 | S. 0° 25' W., on the E. bdy. of Claim No. 41. Descend along broken SW. slope, through scattering timber and dense undergrowth. The SE. cor. of Donation Land Claim No. 41, perpetuated and recorded by J. W. Cole, County Surveyor, in 1915, from original evidence no longer in existence, and further perpetuated and recorded by Arthur R. Evans, Registered Professional Engineer, No. 2741, in 1951, and by John M. Powell, Deputy County Surveyor, in 1970, monumented with an iron pipe, 1 $\frac{1}{2}$ ins. diam., (with an axle, 1 in. diam., alongside), firmly set, projecting 10 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE T 28 S R 8 W DLC NO. 41 S.E. CORNER 1970</p> </div> <p>from which the remains of the bearing tree mkd. by Cole</p> <p style="margin-left: 40px;">A sawed fir stump, 34 ins. diam., bears N. 43° W., 137 lks. dist., no marks visible on open blaze.</p> <p>and the remains of a bearing tree mkd. by Evans</p> |