

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Mer., Oregon

16902

CHAINS	<p style="text-align: center;">A fir, 9 ins. diam., bears S. 89 1/2° W., 25 lks. dist., mkd. 1/4 S6 BT.</p> <p>Descend 10 ft. over NE. slope.</p>				
40.85	<p>Dirt road, 15 lks. wide, bears N. 65° W. and S. 75° E., in curve.</p>				
41.10	<p>Beaver pond, 80 lks. wide, drains S. 35° E.; asc. 500 ft. over SW. slope.</p>				
65.49	<p>The cor. of secs. 5 and 6 only, on the N. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rocky clay. Timber, yew, maple, fir, cedar, oak, hamlock, pine, madrone, ash, and alder; undergrowth, hazel, arrowwood, poison oak, fern, vine maple, manzanita, ceanothus, huckleberry, blackberry, salmonberry, and young timber.</p>				
<p>Dependent Resurvey of a Portion of Donation Land Claim No. 37, Tps. 29 S., Rs. 3 and 4 W., Willamette Meridian, Oregon</p>					
<p>(Restoring the survey by Dennis Hathorn, U.S. Deputy Surveyor, in 1857, and resurvey by James E. Jelley and Lynn M. Roseberry, Cadastral Surveyors, in 1967-77)</p>					
<p>From the NE. cor. of Donation Land Claim No. 37 (located in sec. 20, T. 29 S., R. 3 W.), monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 29 S</td> <td style="padding: 0 10px;">R 3 W</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">C 37</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 20</td> </tr> </table> <p>1977</p> </div> <p>from which reference monuments set and mkd. by Jelley and Roseberry</p> <p style="margin-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears S. 28 1/2° W., 268 1/2 lks. dist., with brass cap mkd. C37 RM 1977, with an arrow pointing to the cor.</p> <p style="margin-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears N. 58 1/2° W., 300 lks. dist., with brass cap mkd. T29S R3W S20 RM 1977, with an arrow pointing to the cor.</p> <p style="margin-left: 40px;">N. 89° 54' W., on the N. bdy. of Claim No. 37.</p> <p>Ascend 325 ft. over broken SE. slope, through scattering timber and dense undergrowth.</p>		T 29 S	R 3 W	C 37	S 20
T 29 S	R 3 W				
C 37	S 20				
29.065	<p>The crossing closing corner of secs. 19 and 20, at intersection with the N. bdy. of Donation Land Claim No. 37, hereinbefore described.</p> <p>From this point, the 1/4 sec. cor. of secs. 19 and 20, bears S. 0° 13' E., 6.48 chs. dist.</p>				