

CHAINS

DUPLICATE

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
SUBDIVISIONAL LINES, AND DONATION LAND CLAIM BOUNDARIES,

AND

THE SUBDIVISION OF SECTIONS 7 AND 9,

TOWNSHIP 29 SOUTH, RANGE 6 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Robert J. Chappel, Cadastral Surveyor

Under Special Instructions dated June 20, 1991, approved June 21, 1991,
which provided for the surveys included under Group No. 1616,
and Assignment Instructions dated June 21, 1991.

*Survey commenced June 24, 1991**Survey completed September 16, 1991*

T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the west boundary, subdivisional lines, and donation land claim boundaries, and the subdivision of sections 7 and 9, township 29 south, range 6 west, Willamette Meridian, Oregon.</p> <p>The history of prior surveys pertaining to this resurvey, is as follows:</p> <p>In 1854, Nathaniel Ford, U.S. Deputy Surveyor, surveyed the boundaries and a portion of the subdivisional lines.</p> <p>In 1855 and 1856, Elliott N. Bowman, and in 1858, Josiah A. Burnett, U.S. Deputy Surveyors, surveyed donation land claims in the township.</p> <p>In 1957 and 1959, Hans W. Thielsen, Cadastral Surveyor, resurveyed a portion of the west boundary.</p> <p>In 1958 and 1959, Hans W. Thielsen and C. Albert White, Cadastral Surveyors, resurveyed portions of the subdivisional lines.</p> <p>In 1971, Peter A. Peterson and Daniel L. Berry, Cadastral Surveyors, resurveyed portions of the subdivisional lines and donation land claim boundaries.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and Special Instructions dated June 20, 1991, for Group No. 1616, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.</p> <p>The geographic position (NAD 1927) of the ¼ section corner of sections 7 and 12 on the west boundary of the township, as</p>
--------	--

T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

determined by a tie to the National Geodetic Survey triangulation station "TWO OAKS," is as follows:

Latitude 43° 03' 47.74" N. Longitude 123° 27' 48.49" W.

The geographic position (NAD 1927) of the corner of sections 8, 9, 16 and 17, as determined by a tie to the National Geodetic Survey triangulation station "TWO OAKS," is as follows:

Latitude 43° 03' 21.71" N. Longitude 123° 25' 20.75" W.

The mean magnetic declination is 19° East.

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

(Restoring the 1854 survey by Nathaniel Ford and
the 1957 and 1959 resurvey by Hans W. Thielsen)

Beginning at the cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd.

T29S
R7W R6W
S 12 S 7

S 13 S 18
1957

from which the remaining bearing trees mkd. by Thielsen

A maple, 14 ins. diam., bears N. 80° E., 109 lks. dist., with scribe marks R6W S visible on partially healed blaze.

A maple, 16 ins. diam., bears S. 42½° E., 135 lks. dist., with illegible scribe marks visible on opened blaze.
(Record, S. 43½° E.)

and new bearing trees

A fir, 8 ins. diam., bears S. 36½° W., 20½ lks. dist., mkd. T29S R7W S13 BT.

A madrone, 6 ins. diam., bears N. 10° W., 35 lks. dist., mkd. X BT.

The corner is located in small draw, drains N. 50° W.

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>N. 1° 59' 30" W., bet. secs. 7 and 12.</p> <p>Descend over broken NW. slope.</p>
19.185	<p>The S 1/16 sec. cor. of secs. 7 and 12, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 12 * S 7 R7W R6W T29S 1958</p> <p>from which bearing trees mkd. by Thielsen</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 40½° E., 268 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 9° W., 218½ lks. dist., with healed blaze. (Record, 221 lks.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 56' 30" W., beginning new measurement.</p> <p>Over nearly level land.</p>
2.10	<p>Kent Creek, 10 lks. wide, course N. 60° E.; asc. over SE. slope.</p>
3.40	<p>Asphalt surfaced road, 30 lks. wide, bears N. 60° E. and S. 60° W.; asc. over broken SE. slope.</p>
19.080	<p>The ¼ sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S ¼ S12 * 7 R7 R6 1957</p> <p>from which the remains of the bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1957</p> <p style="padding-left: 40px;">A fir snag, 12 ins. diam., bears N. 61° W., 154 lks. dist., with healed blaze. (Record, 155 lks.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A madrone, 11 ins. diam., bears S. 19 3/4° E., 52 lks. dist.,</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>mkd. ¼ S7 BT.</p> <p>A madrone, 13 ins. diam., bears N. 46 ¾° W., 12 lks. dist., mkd. ¼ S12 BT.</p> <p>From this point, the National Geodetic Survey triangulation station, "TWO OAKS," bears N. 31° 41' 55" W., 89.185 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with a brass cap mkd. TWO OAKS 1942.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 29 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p>(Restoring the survey by Nathaniel Ford in 1854, the resurvey by Hans W. Thielsen and C. Albert White in 1957 and 1958, and the resurvey by Peter A. Peterson and Daniel L. Berry in 1971)</p> <hr style="width: 20%; margin: auto;"/> <p>From the ¼ sec. cor. of secs. 9 and 16, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S R6W S 9 ¼ ----- S 16 1962</p> <p>from which the only remaining original bearing tree</p> <p style="padding-left: 40px;">An oak, 32 ins. diam., bears S. 21° W., 279 lks. dist., with scribe marks BT visible on open blaze. (Record, 284 lks.)</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962</p> <p style="padding-left: 40px;">An oak, 16 ins. diam., bears N. 43° W., 87 lks. dist., with healed blaze.</p> <p>N. 88° 45' 30" W., bet. secs. 9 and 16.</p> <p>Ascend over broken S. slope.</p> <p>34.70 Dirt road, 15 lks. wide, on ridge, bears N. and S.; desc. over NW. slope.</p> <p>38.730 The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, (alongside is an iron bolt, ¾" diam, firmly set, projecting 3</p>
--------	---

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>ins. above the ground, also alongside is an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T29S R6W 8 9 16 17 1954), with brass cap mkd.</p> <p style="text-align: center;">T29S R6W S 8 * S 9</p> <p style="text-align: center;">S 17 * S 16 1958</p> <p>from which the remains of the bearing trees mkd. by L. G. Hicks, Private Engineer, in 1917</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 50° E., 19 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A rotted fir stump, 24 ins. diam., bears S. 22° E., 26 lks. dist., with illegible scribe marks on opened blaze.</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 72° E., 50 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A badly rotted fir stump, 12 ins. diam., bears S. 1½° W., 48 lks. dist., with axe marks visible.</p> <p style="padding-left: 40px;">A rotted fir stump, 9 ins. diam., bears S. 21° W., 76½ lks. dist., alongside is a fir lying on the ground, with scribe marks T29S R6W S17 visible on open blaze. (Record, S. 22° W., 77 lks.)</p> <p>and bearing trees mkd. by Thielsen and White</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 85° E., 88 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 67½° W., 66½ lks. dist., with a healed blaze. (Record, 68 lks.)</p> <p>From this point, the National Geodetic Survey triangulation station "TWO OAKS," bears N. 61° 28' 20" W., 242.487 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with a brass cap, mkd. TWO OAKS 1942.</p> <hr style="width: 80%; margin-left: 0;"/> <p>N. 1° 56' 00" E., bet. secs. 8 and 9.</p> <p>Descend over NW. slope, through timber.</p> <p>25.010 The crossing closing cor. of secs. 8 and 9 on the S. bdy. of</p>
--------	---

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>Donation Land Claim No. 47, established by persons unknown, monumented with an iron pipe, 1 in. diam., loosely set flush with the ground, and is accepted as the corner, from which a bearing tree mkd. by persons unknown:</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 62° E., 66 lks. dist., with illegible scribe marks visible on opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W CCC <u>DLC 47</u> S8 S9 1991</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 39° E., 35½ lks. dist., mkd. T29S R6W S9 CCC BT.</p> <p>The iron pipe was removed from the area.</p> <p>From this point, a point established by persons unknown, monumented with an iron rod, 7/8 in. diam., bears S. 80° 01' 30" E., 0.555 chs. dist., this point is not properly positioned and is not utilized in this survey.</p> <p>From this same point, the SW. cor. of Donation Land Claim No. 47, bears N. 89° 01' 00" W., 26.350 chs. dist., hereinafter described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 56' 00" E., beginning new measurement.</p> <p>Descend NW. slope, through timber.</p> <p>2.50 Leave timber; enter pasture, edge bears N. 20° E. and S. 20° W.</p> <p>14.145 Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, the top 6 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W ¼ S 8 * S 9 1991</p>
--------	---

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A power pole, No. B17944, bears N. 32° E., 219½ lks. dist.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. The corner is located in a pasture.</p> <p>From this point, a point reestablished as the ¼ sec. cor. of secs. 8 and 9 by James W. Byron, Deputy County Surveyor, in 1954, recorded in Douglas County Surveyor's Office, corner renewal record No. 134, T. 29 S., R. 6 W., bears N. 89° 45' 40" E., 0.700 chs. dist.; monumented with an iron post, 1 in. diam., firmly set flush with the ground, with brass cap mkd. DOUGLAS COUNTY OFFICE T29S R6W ¼S 8 9 1954. This point was established using erroneous control and is not utilized in this survey. From which a bearing tree mkd. by Byron:</p> <p style="padding-left: 40px;">An oak, 47 ins. diam., bears S. 55° E., 178 lks. dist., with scribe marks S9 CS visible on opened blaze.</p>
22.55	Rice creek, 15 lks. wide, course N. 35° E.; asc. over nearly level land.
27.430	<p>From this point, the interior corner on the W. bdy. of Donation Land Claim No. 47, bears West, 0.215 chs. dist., perpetuated by L. G. Hicks, Private Engineer, in 1917, recorded in Douglas County Surveyor's Office, map file No. M13-71, and further perpetuated by James W. Byron, Deputy County Surveyor, in 1954, recorded in the Douglas County Surveyor's Office, corner renewal record No. 137, T. 29 S., R. 6 W., determined at record distance from bearing trees recorded by Hicks:</p> <p style="padding-left: 40px;">An oak, 22 ins. diam., bears N. 11° E., 122 lks. dist., with scribe marks visible on sawed open blaze.</p> <p style="padding-left: 40px;">An oak, 28 ins. diam., bears N. 65° W., 121 lks. dist., with scribe marks visible on sawed open blaze.</p> <p>No permanent monument established.</p>
27.75	Asphalt road, 40 lks. wide, bears N. 40° E. and S. 60° W.; asc. SE. slope.
40.15	Spur, slopes N. 70° E.; desc. over NE. slope.
53.300	The cor. of 4, 5, 8, and 9, perpetuated by L. G. Hicks, Private Engineer, in 1917, recorded in Douglas County Surveyor's Office, map file No. M13-71, and remonumented by James W. Byron, Deputy County Surveyor, in 1954, recorded in the Douglas County Surveyor's Office, corner renewal record No. 141, T. 29 S., R. 6 W., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">COUNTY SURVEYORS T29S R6W <u>5 * 4</u> 8 * 9 1954 OFFICE</p> <p>from which the remaining bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">An oak, 16 ins. diam., bears N. 22° E., 48½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 25 ins. diam., bears S. 19° W., 175 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 25 ins. diam., bears N. 85½° W., 42½ lks. dist., with healed blaze.</p> <p>The corner is located 3 lks. W. of a fence corner, woven wire fence bears N. 85° E, S. 60° W., and N. 10° W.</p> <p>From this point, the ¼ sec. cor. of secs. 4 and 9, perpetuated by James W. Byron, Deputy County Surveyor, in 1954, recorded in Douglas County Surveyor's Office, corner renewal record No. 108, T. 29 S., R. 6 W., and remonumented by Gary L. Langlitz, Deputy County Surveyor, in 1977, as recorded in the Douglas County Surveyor's Office, corner renewal record No. 234, T. 29 S., R. 6 W., bears S. 89° 07' 30" E., 39.130 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, (alongside is a stone, 7 x 12 x 6 ins. above the ground, no marks visible, also alongside is an iron rod, 7/8 in. diam., firmly set, projecting 2 ins. above the ground), with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T29S R6W S 4 ¼ ----- S 9 1977</p> <p>from which the only remaining original bearing tree</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears S. 11° W., 100 lks. dist., with axe marks visible on rotted blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A oak, 12 ins. diam., bears S. 22° W., 34½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 16 ins. diam., bears N. 54° W., 56 lks. dist., with healed, double blaze.</p>
--------	---

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>and a bearing tree mkd. by Langlitz</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 82½° W., 39½ lks. dist., with healed blaze.</p> <p>The corner is located 4½ lks. S. of a fence corner, fence bears E., W., and S.</p> <hr/> <p>From the ¼ sec. cor. of secs. 7 and 18, determined at record bearing and distance from the remaining bearing tree mkd. by Thielsen and White in 1958:</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 27° W., 161 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T29S R6W S 7 ¼ ---- S 18 1991 </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 85½° E., 87 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>N. 89° 43' 00" W., bet. secs. 7 and 18.</p> <p>Ascend over broken E. slope, through timber and undergrowth.</p> <p>17.90 Spur, slopes N. 30° E.; desc. along N. slope.</p> <p>21.310 The W 1/16 sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> S 7 W 1/16 ---- S 18 T29S R6W 1958 </div> <p>from which the remains of the bearing trees mkd. by Thielsen and White</p>
--------	--

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>A fir, 29 ins. diam., bears N. 79° E., 86 lks. dist., with a healed blaze. (Record, 87 lks.)</p> <p>A fir stump, 20 ins. diam., bears S. 23° W., 74 lks. dist., no marks visible. (Record, S. 25° W., 75 lks.)</p> <p>and a new bearing tree</p> <p>A fir, 20 ins. diam., bears S. 72½° W., 106 lks. dist., mkd. W 1/16 S18 BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89° 47' 00" W., beginning new measurement.</p> <p>Descend along broken N. slope.</p>
23.780	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the ¼ sec. cor. of secs. 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\frac{1}{4}$ S 7 * S 8 T29S R6W 1958 </div> <p>from which a bearing tree mkd. by Gene E. Johnson, Registered Engineer No. 3561, in 1953</p> <p>A fir, 19 ins. diam., bears S. 75 ¾° W., 37 lks. dist., with healed blaze. (Record, S. 72½° W., 38 lks.)</p> <p>and a bearing tree mkd. by Thielsen and White</p> <p>A fir, 18 ins. diam., bears N. 7° E., 103½ lks. dist., with healed blaze. (Record, 101 lks.)</p> <p>Alongside the iron post is an iron pipe, 1 in. diam., firmly set flush with the ground.</p> <p>N. 1° 29' 00" E., bet. secs. 7 and 8.</p> <p>Descend along broken E. slope.</p>
19.320	<p>The N 1/16 sec. cor. of secs. 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">N 1/16 S 7 * S 8 T29S R6W 1958</p> <p>from which the remaining bearing tree mkd. by Thielsen and White</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 51° E., 5 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A madrone, 10 ins. diam., bears N. 7½° W., 37 lks. dist., mkd. N 1/16 S7 BT on bark.</p> <p>The corner is located at the end of an old fence line, extending N., and 25 lks. E. of a dry wash, 25 lks. wide, drains S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 30' 00" E., beginning new measurement.</p> <p>Ascend over SE. slope.</p> <p>9.65 Jeep trail on ridge, bears E. and W.; desc. over NW. slope.</p> <p>19.440 The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 6 * S 5 S 7 * S 8 T29S R6W 1958</p> <p>from which the remains of the bearing trees mkd. by G. G. Stewart, Deputy County Surveyor, in 1921</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 54½° E., 50 lks. dist., with healed blaze. (Record, 52 lks.)</p> <p style="padding-left: 40px;">A sawed fir stump, size indeterminate, bears S. 34° W., 43 lks. dist., no marks visible. (Record, S. 38° W.)</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 75° W., 23 lks. dist., with healed blaze. (Record, N. 72° W.)</p> <p>and the remains of the bearing trees mkd. by Thielsen and White</p> <p style="padding-left: 40px;">A sawed fir stump, 23 ins. diam., bears S. 48½° E., 24 lks. dist., with healed blaze. (Record, 25 lks.)</p>
--------	--

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>A rotted fir stump, size indeterminate, bears S. 28° W., 95 lks. dist., no marks visible.</p> <p>A fir, 17 ins. diam., bears N. 33½° W., 28 lks. dist., with healed blaze.</p> <p>The corner is located alongside a woven wire fence, bears N. 80° E. and S. 80° W., and remains of fence bears N.</p> <hr/> <p>S. 89° 32' 30" W., bet. secs. 6 and 7.</p> <p>Descend along broken N. slope.</p>
22.320	<p>The E 1/16 sec. cor. of secs. 6 and 7, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 6 E 1/16 ----- S 7 T29S R6W 1958</p> <p>from which bearing trees mkd. by Thielsen and White</p> <p>A cedar, 9 ins. diam., bears S. 36° E., 4 lks. dist., with healed blaze. (Record, S. 22° E.)</p> <p>A fir, 10 ins. diam., bears N. 6° W., 23 lks. dist., with healed blaze.</p> <p>The corner is located at a fence corner, fence bears N., E., and W.</p> <hr/> <p>S. 89° 37' 00" W., beginning new measurement.</p> <p>Descend along broken N. slope.</p>
22.20	<p>Kent Creek, 5 lks. wide, course N. 20° E.; asc. over SE. slope.</p>
22.340	<p>The ¼ sec. cor. of secs. 6 and 7, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 6 ¼ ----- S 7 T29S R6W 1958</p> <p>from which bearing trees mkd. by Thielsen and White</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>A chinquapin, 8 ins. diam., bears S. 28° W., 26 lks. dist., with healed blaze.</p> <p>A fir, 16 ins. diam., bears N. 6° W., 40 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of A Portion of the Boundaries of Donation Land Claim No. 41, T. 29 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the survey by Josiah A. Burnett in 1860, and the resurvey by Peter A. Peterson and Daniel L. Berry in 1971)</p> <hr/> <p>From the interior corner on the N. bdy. of Donation Land Claim No. 41, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W S 9 * C 41 1971</p> <p>from which the bearing trees mkd. by Peterson and Berry</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears S. 21° W., 186 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 27 ins. diam., bears N. 58° W., 121 lks. dist., with healed blaze. (Record, 125 lks.)</p> <p>N. 0° 05' 00" W., on the N. bdy. of Claim No. 41.</p> <p>Ascend over broken SE. slope.</p> <p>1.10 Woven wire fence, bears N. 70° W. and S. 70° E.</p> <p>1.800 Point for the crossing closing corner, at intersection with the E. and W. center line of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W DLC 41 C ----- C S 9 CCC 1991</p> <p>from which</p>
--------	--

**Dependent Resurvey of A Portion of
the Boundaries of Donation Land Claim No. 41,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>The top of a marble tomb stone, 1 x 2 x 2 ft. above ground, bears N. 61¼° E., 118 lks. dist., with chisel marks FRITZ FATHER LA AL 1887-1956 MOTHER IDA JANE 1889-1956 on E. face.</p> <p>A fence corner, 8 ins. diam, bears S. 19½° W., 64½ lks. dist., woven wire fence bears N. 10° W. and S. 70° E.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located within the fence boundaries of a cemetery.</p> <p>From this point the ¼ sec. cor. of secs. 9 and 10, bears N. 89° 54' 00" E., 7.510 chs. dist., hereinafter described.</p> <p>Ascend over SE. slope.</p>
2.40	Woven wire fence, bears N. 10° E. and S. 10° W.; leave cemetery.
15.080	<p>The exterior corner on the N. bdy. of Donation Land Claim No. 41, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground with brass cap mkd.</p> <p style="text-align: center;">T29S <u>R6W</u> S 9 * C41 1971</p> <p>from which the remains of bearing trees mkd. by Peterson and Berry</p> <p>A fir stump, 30 ins. diam., bears S. 26° E., 116 lks. dist., no marks visible on bottom of healed blaze. (Record, 120 lks.)</p> <p>A fir, 30 ins. diam., bears S. 58° W., 63½ lks. dist., with healed blaze. (Record, 67 lks.)</p> <p>No other suitable accessories available.</p> <hr/> <p>From the NE. cor. of Donation Land Claim No. 47, perpetuated by L. G. Hicks, Private Engineer, in 1917, recorded in the Douglas County Surveyor's Office, map file No. M13-71, and remonumented by James W. Byron, Deputy County Surveyor, in 1954, recorded in the Douglas County Surveyor's Office, corner renewal records No. 139, T. 29 S., R. 6 W., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS <u>T29S R6W</u> NE COR * DLC 47 * 1954 OFFICE</p>

**Dependent Resurvey of A Portion of
the Boundaries of Donation Land Claim No. 47,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A oak, 46 ins. diam., bears N. 40° E., 6 lks. dist., with rotted blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">An oak, 32 ins. diam., bears N. 88½° E., 36½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 33 ins. diam., bears N. 71° W., 40 lks. dist., with healed blaze.</p> <p>The corner is located in a woven wire fence, bears E. and W. S. 2° 29' 00" E., on the E. bdy. of Claim No. 47.</p> <p>Ascend over broken NW. slope.</p>
77.670	<p>Point for the crossing closing corner, at intersection with the E. and W. center line of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W CCC DLC 47 * C -----C S 9 1991</p> <p>from which</p> <p style="padding-left: 40px;">A madrone, 16 ins. diam., bears S. 34½° E., 166 lks. dist., mkd. T29S R6W S9 CCC BT on bark.</p> <p>No other suitable trees available.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 8 and 9, bears S. 89° 54' 00" W., 26.825 chs. dist., hereinbefore described.</p> <p>Ascend over NW. slope.</p>
92.360	<p>Point for the SE. cor. of Donation Land Claim No. 47, at proportionate distance by the Grant Boundary method, based on the resurvey by L. G. Hicks, Private Engineer, in 1917, recorded in the Douglas County Surveyor's Office, map file No. M13-71; there is no remaining evidence of the original corner.</p>

**Dependent Resurvey of A Portion of
the Boundaries of Donation Land Claim No. 47,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W <u>DLC 47</u> S 9 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 75½° E., 203 lks. dist., mkd. T29S R6W C47 BT.</p> <p style="padding-left: 40px;">A maple, 21 ins. diam., bears S. 29¼° W., 225½ lks. dist., mkd. T29S R6W C47 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located in an open field.</p> <p style="text-align: center;">_____</p> <p>N. 89° 01' 00" W., on the S. bdy. of Claim No. 47.</p> <p>Descend over broken SW. slope.</p> <p>18.00 Enter timber, edge bears N. 50° W. and S. 40° E.</p> <p>27.945 The crossing closing cor. of secs. 8 and 9, hereinbefore described.</p> <p>Descend over NW. slope.</p> <p>54.295 The SW. cor. of Donation Land Claim No. 47, perpetuated by L. G. Hicks, Private Engineer, in 1917, recorded in Douglas County Surveyor's Office, map file No. M13-71, further perpetuated by J. W. Cole, Deputy County Surveyor, in 1921, recorded in Douglas County Surveyor's Office, corner renewal record No. 111, T. 29 S., R. 6 W., and remonumented by James W. Byron, Deputy County Surveyor, in 1954, recorded in the Douglas County Surveyor's Office, corner renewal record No. 136, T. 29 S., R. 6 W., monumented with an iron post, 1 in. diam., firmly set 10 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS SW COR * DLC T29S <u>47</u> R6W 1954 OFFICE</p> <p>from which the remaining original bearing tree</p>
--------	--

**Dependent Resurvey of A Portion of
the Boundaries of Donation Land Claim No. 47,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>An oak, 37 ins. diam., bears S. $0\ 3/4^{\circ}$ E., 108 lks. dist., with healed blaze. (Record, S. 5° E.)</p> <p>and a bearing tree mkd. by Cole</p> <p>An oak, 48 ins. diam., bears S. $79\ 1/4^{\circ}$ E., 266 lks. dist., with healed double blaze.</p> <p>and bearing trees mkd. by Byron</p> <p>An oak, 27 ins. diam., bears S. $84\ 1/2^{\circ}$ W., 204 lks. dist., with healed double blaze.</p> <p>An oak, 37 ins. diam., bears N. $5\ 1/2^{\circ}$ W., $50\ 1/2$ lks. dist., with healed blaze.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 29 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p>From the $1/4$ sec. cor. of secs. 7 and 18.</p> <p>N. $0^{\circ}\ 06'\ 30''$ E., on the N. and S. center line of sec. 7.</p> <p>Ascend over broken SE. slope.</p> <p>19.280 Point for the center S $1/16$ sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S $1/16$ * S 7 C 1991</p> <p>from which</p> <p>A maple, 23 ins. diam., bears N. 25° E., 10 lks. dist., mkd. CS$1/16$ S7 BT.</p> <p>A fir, 15 ins. diam., bears S. $51\ 1/2^{\circ}$ E., 94 lks. dist., mkd. CS$1/16$ S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base and set aluminum fence post alongside the stainless steel post.</p> <p>The corner is located on the N. edge of ridgetop dirt road, 15 lks. wide, bears N. 60° E. and S. 80° W.</p> <p>Descend along broken W. slope.</p>
--------	---

Subdivision of Section 7,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

<p>CHAINS 38.560</p>	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W C$\frac{1}{4}$ S 7 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. $73\frac{1}{4}^{\circ}$ E., 24 lks. dist., mkd. X BT on double blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. $83\frac{3}{4}^{\circ}$ W., 23 lks. dist., mkd. C$\frac{1}{4}$ S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base and set steel fence post alongside the stainless steel post.</p> <p>From this point, a point unofficially established as the C$\frac{1}{4}$ sec. cor. by the Bureau of Land Management during an administrative survey in 1960, bears S. $50^{\circ} 11' 30''$ E., 0.120 chs. dist.; monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground.</p> <p>Descend along broken W. slope.</p>
<p>57.910</p>	<p>Point for the center N $\frac{1}{16}$ sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N $\frac{1}{16}$ * S 7 C 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. $48\frac{3}{4}^{\circ}$ W., $38\frac{1}{2}$ lks. dist., mkd. CN$\frac{1}{16}$ S7 BT.</p> <p>No other suitable trees available.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NW. slope, along edge of pasture, bears N. and S.</p>
<p>77.260</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p>

Subdivision of Section 7,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p> <p>S. $89^{\circ} 37' 30''$ W., on the E. and W. center line of sec. 7.</p> <p>Ascend over NE. slope.</p>
2.60	Ridge, bears N. 40° W. and S. 40° E.; desc. over SW. slope.
21.860	<p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E $\frac{1}{16}$ C ----- C S 7 1991</p> <p>from which</p> <p style="padding-left: 40px;">A maple, 19 ins. diam., bears N. 57° E., 55 lks. dist., mkd. CE$\frac{1}{16}$ S7 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 3° E., $43\frac{1}{2}$ lks. dist., mkd. X BT on double blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on N. edge of abandoned skid road, 15 lks. wide, bears E. and W.</p> <p>Ascend over broken SE. slope.</p>
35.10	Ridgetop dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.; desc. over broken NW. slope.
43.720	The center $\frac{1}{4}$ sec. cor. of sec. 7.
62.60	Kent Creek, 10 lks. wide, course N. 40° E.; asc. over SE. slope.
64.55	Asphalt road, 35 lks. wide, bears N. 40° E. and S. 40° W.
65.820	<p>Point for the center W $\frac{1}{16}$ sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W $\frac{1}{16}$ C ----- C S 7 1991</p>

Subdivision of Section 7,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A maple, 11 ins. diam., bears S. 26½° E., 101½ lks. dist., mkd. CW1/16 S7 BT.</p> <p>No other suitable trees available.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SE. slope.</p>
90.190	<p>The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p style="padding-left: 40px;">From the center E 1/16 sec. cor. of sec. 7.</p> <p>N. 0° 51' 00" E., on the N. and S. center line of the NE¼ of sec. 7.</p> <p>Ascend over broken SE. slope.</p>
19.340	<p>Point for the NE 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NE¼.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S7 1991</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears N. 73° E., 266 lks. dist., mkd. NE 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 40½° E., 129½ lks. dist., mkd. NE 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located at the edge of timber, bears E. and S.</p>
22.10	<p>Ridgetop dirt road, 15 lks. wide, bears N. 55° E. and S. 55° W.; desc. over broken N. slope.</p>
38.715	<p>The E 1/16 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 7 and 8.</p>

Subdivision of Section 7,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	S. 89° 40' 00" W., on the E. and W. center line of the NE¼ of sec. 7.
	Ascend over broken SE. slope.
22.090	The NE 1/16 sec. cor. of sec. 7.
23.35	Ridge, bears N. 45° E. and S. 45° W.; desc. over broken W. slope.
24.25	Dirt road, 12 lks. wide, bears N. 65° E. and S. 65° W.
44.190	The center N 1/16 sec. cor. of sec. 7.
	<hr/>
	From the W 1/16 sec. cor. of secs. 7 and 18.
	N. 1° 05' 00" W., on the N. and S. center line of the SW¼ of sec. 7.
	Descend over NE. slope.
19.135	Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SW¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	SW 1/16 S7 1991
	from which
	A fir, 11 ins. diam., bears N. 80° E., 11 lks. dist., mkd. SW 1/16 S7 BT.
	A fir, 8 ins. diam., bears S. 29½° W., 23 lks. dist., mkd. SW 1/16 S7 BT.
	Deposit a white "DEEP-1" magnetic marker at base and set steel fence post alongside the stainless steel post.
	Descend over NE. slope.
32.80	Kent Creek, 10 lks. wide, course N. 75° E.; asc. over SE. slope.
37.25	Asphalt road, 35 lks. wide, bears N. 40° E. and S. 40° W.
38.310	The center W 1/16 sec. cor. of sec. 7.
	<hr/>
	From the center S 1/16 sec. cor. of sec. 7.

**Subdivision of Section 7,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>S. 89° 54' 00" W., on the E. and W. center line of the SW¼ of sec. 7.</p> <p>Descend Along broken N. slope.</p>
21.710	The SW 1/16 sec. cor. of sec. 7.
45.780	The S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
<hr/> <p>Subdivision of Section 9, T. 29 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/>	
	<p>From the ¼ sec. cor. of secs. 9 and 16.</p> <p>N. 2° 14' 30" E., on the N. and S. center line of sec. 9.</p> <p>Ascend over broken S. slope.</p>
18.25	Ridgetop dirt road, 15 lks. wide, bears N. 50° W. and S. 30° E.; desc. over NE. slope.
28.00	Woven wire fence on ridgetop, bears N. 75° E. and S. 75° W.; desc. over broken NW. slope.
40.090	<p>Point for the center ¼ sec. cor. of sec. 9, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R6W C¼ S 9 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 47½° E., 61½ lks. dist., mkd. C¼ S9 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 17° W., 118 lks. dist., mkd. C¼ S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NW. slope.</p>
78.570	The ¼ sec. cor. of secs. 4 and 9.

**Subdivision of Section 9,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set with top 2 ins. below the ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 9 * S 10 T29S R6W 1971</p> <p>from which the bearing object described by Peterson and Berry</p> <p style="text-align: center;">A power pole, #B7900, bears S. 28° E, 495 lks. dist. (Record, S. 29° E., 504 lks.)</p> <p>No other suitable accessories available.</p> <p>Corner is located in a grape vineyard.</p> <p>S. $89^{\circ} 54' 00''$ W., on the E. and W. center line of sec. 9.</p> <p>Ascend over E. slope, through vineyard.</p>
2.00	Leave vineyard.
2.30	Asphalt road, 35 lks. wide, bears N. 20° E. and S. 20° W.; asc. broken SE. slope.
7.510	<p>The crossing closing corner at intersection with the N. bdy. of Donation Land Claim No. 41, hereinbefore described.</p> <p>From this point, the interior corner on the N. bdy. of Claim No. 41, bears S. $0^{\circ} 05' 00''$ E., 1.800 chs. dist., hereinbefore described.</p>
37.50	Ridge, bears N. 20° E. and S. 20° W.; desc. over NW. slope.
40.495	The center $\frac{1}{4}$ sec. cor. of sec. 9.
52.620	<p>The crossing closing corner at intersection with the E. bdy. of Donation Land Claim No. 47, hereinbefore described.</p> <p>From this point, the SE. cor. of Claim No. 47, bears S. $2^{\circ} 29' 00''$ E., 14.690 chs. dist., hereinbefore described.</p>
79.445	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	<hr/> <p>GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located in Douglas</p>

**Subdivision of Section 9,
T. 29 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

County approximately five miles south of the community of Winston, Oregon. Access is by way of county roads and numerous secondary roads. The elevations range from 650 feet above sea level near the quarter section corner of sections 9 and 10, to 1300 feet above sea level near the center south sixteenth section corner of section 7.

The land surveyed is mostly timbered, with a few open pastures. The timber consists of fir, maple, cedar, madrone, alder and hemlock. The undergrowth consists mostly of poison oak, with a smattering of vine maple, salmonberry and assorted ferns.

The area surveyed is drained mainly by Kent Creek, Rice Creek, and Willis Creek which flow northerly into the South Umpqua River.

There were no mineral deposits or mining activity noted along the lines surveyed.

The mean magnetic declination as shown on the United States Geological Survey quadrangle map "WINSTON, OREG." provisional edition, 1987, is 19° East.