

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 29 S., R. 8 W.

CHAINS 40.19	<p>The cor. of secs. 29, 30, 31, and 32, perpetuated and recorded by J. W. Cole, County Surveyor, in 1923, from the remaining original bearing trees, subsequently re-monumented by James W. Byron, Deputy County Surveyor, in 1958, with an iron rod, 3/4 in. diam., firmly set, extending 8 ins. above ground, from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">An oak, 20 ins. diam., bears S. 75<math>\frac{1}{4}</math>° E., 104 lks. dist., with no marks remaining on rotted open blaze. (Record, S. 46° E., 106 lks.)</p> <p style="margin-left: 40px;">A sawed fir stump, 48 ins. diam., bears S. 10° W., 177 lks. dist., 175 lks. to face, with no marks remaining. (Record distance 175 lks.)</p> <p>and a bearing tree marked by Cole</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears S. 46° E., 43 lks. dist., with a healed blaze.</p> <p>and a bearing tree marked by Byron</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 59° E., 20<math>\frac{1}{2}</math> lks. dist., mkd. with a partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: right; margin-right: 20px;"> <p>FOOK PER LAWEY DEC 1989 M109-20</p> </div> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T 29 S R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1965</td> </tr> </table> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 5<math>\frac{1}{2}</math>° W., 141 lks. dist., mkd. T29S R8W S31 BT.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears N. 65° W., 128 lks. dist., mkd. T29S R8W S30 BT.</p> <p style="margin-left: 40px;">Reset iron rod alongside the iron post.</p> <p>Land, rolling hills. Soil, rocky clay. Timber, fir, cedar, pine, madrone, maple, dogwood, oak, yew, chinquapin and alder; undergrowth, salal, poison oak, arrowwood, Oregon grape, huckleberry, blackberry, willow, vine maple, hazel, manzanita, vines and ferns.</p>	T 29 S R 8 W		S 30	S 29	S 31	S 32	1965	
T 29 S R 8 W									
S 30	S 29								
S 31	S 32								
1965									
0.60	Gravelled road, 25 lks. wide, bears N. 25° E. and S. 25° W.								
8.95	Creek, 3 lks. wide, course N. 10° W.; asc. 35 ft. over East slope.								
13.15	<p>S. 89° 33' W., bet. secs. 30 and 31.</p> <p>Descend 40 ft. over W. slope, through scattering timber and light undergrowth.</p> <p>Top of ascent slopes N., and barbed wire fence bears N. and S.; continue over nearly level land.</p>								