

County Surveyor's Record, Douglas County, Oregon

T. 30 S., R. 4 W.

695

CHAINS	
	CLAIM NO. 39 cont.
0.75	Left bank of S. Umpqua river. Set flagg N. on line on right bank, also a flagg on left bank, cross over, run base East 1.50 chns. flagg bears S 23° 55' W., making 3.38 lks across
4.13	To flagg on right bank of S. Umpqua, course S 80° W.
5.00	To cor. and NW cor. of Claim No. 42. The post, set for this cor. is gone, the remains of a maple, corresponding insize, bearing and distance with the diescription in the field notes of original survey are still here; I futher verify this location by running from witness corner of NW cor. of Claim No. 41, an offset North 4.00 chns. thence East 20.00 chns to line bet. secs. 7 and 8, which I intersected 2225 lks South of 1/4 sec. post. I restore this corner by setting a basalt stone 10 x 8 x 7 ins., 7 ins in the ground marked 39 on NW. face, and raised a mound of stone along-side, from which A balm 16 ins. in diam., bears S.11° W 147 lks dist, marked T 30 S. R 4 W C 39. BT Thence East bet. Claims 39 and 42. Va. 19° E.
3.25	Right bank of river, course S 70° W, set flagg, also set flagg on left bank, cross over, run base South 2.50 chns. flagg bears N 18 3/4° W, making 7.37 lks acrosss.
10.00	Corners comes in the river.
10.62	Left bank of river; cor. and bearing tree are washed away; set as witness corner 62 lks. E. of true cor. a basalt stone 10 x 8 x 8 ins. 7 ins. in the ground, marked 39. W C on NW. face, and raised a mound of stone along side. Thence North, on an offset of 62 lks E. of true line.
1.80	Left bank of river.
2.88	Cor. is in the river; Set as witness corner 108 lks South and 68 lks E. of true cor. a basalt stone marked 39. W C on NW. face, 9 x 8 x 7 ins. 6 ins in the ground, raised a mound of stone alongside. Thence East, from true cor.
0.62	Offset South 288 lks from true cor.
10.00	Offset North 288 lks. regained true line at cor. of Claim 39 and NE cor. of No. 42. The post, set for this cor. is gone, but the bearing tree stands. I restore this cor. by setting a basalt stone 20 x 10 x 7 ins. 15 ins. in the ground, marked 39 on N.W. face, from which A bl. oak 45 ins. in diam. bears N 60° W 100 lks dist., marked T 30 S. R 4 W. C 39 BT. This is the old bearing tree, whose marks being dim, I renew. Thence North, bet. Claims No. 39 and 43. Va. 18° 45' E.
0.12	Set flagg N. on line on right bank of river; also flagg here; lay off base East 90 lks. flagg bears N 11° 10' W. making 4.56 chns between flaggs.