

# County Surveyor's Record, Douglas County, Oregon

T 30 S., R 4 W

699

**CHAINS**

CLAIM NO. 41

Resurvey of John T. Boyle's Land Claim No. 41 in secs. 7 and 18, T 30 S R 4 West, Notification No. 127.

Begin at a point 12.10 chns North and 20 chns West of the SE corner of sect. 7 and the NW cor. of Claim 41, the post of which is gone, but the bearing tree is standing. At 1.00 chn North of true cor., I set a basalt rock 12 x 8 x 6 ins 8 ins. in the ground, for witness corner to NW cor. of Claim, marked C. 41, W.C. on SE face, From which

A bl. oak, 36 ins. in diam. bears S 65°E 31 lks. dist. marked T 30 S. R 4 W. C. 41. WC. BT. This is the old bearing tree which I remark.

East bet. Claims 41 and 39.

Va. 18° 30' E

Offsett South from true corner 205 lks thence by traverse N 78° E 9.86 chns making Northing 205 lks. regained true line.

9.64 Left bank of S. Umpqua river, course S 80° W.

20.01 To NE corner. The post for this cor. is gone. I restore the same by setting a basalt rock 10 x 8 x 8 ins. 7 ins. in the ground, marked 41 on SW. face, raised a mound of stone alongside thence

South, bet. Claims 41 and 42, and bet. secs. 18 and 17 as far as 1/4 sec. cor.

Var. 18°30' E.

Through grainfield.

12.10 The cor. to secs. 7, 8, 17, and 18.

51.75 The 1/4 sec. cor. bet. secs. 17 and 18.

59.40 Leave grainfield, enter oak timber.

66.25 A branch, course W. 1 lk. wide, begin ascent.

73.05 SW. cor. of Claim No. 42.

80.00 The SE cor. of Claim No. 41. The post set for this corner is gone, but the bearing tree is standing. I restore this cor. by setting a basalt rock 12 x 12 x 6 ins. 8 ins. in the ground, marked 41 on the NW face from which

A Wh. oak, 33 ins. in diam., bears N. 25° W 472 lks. dist. marked T 30 S. R 4 W C. 41 BT. This is the old bearing tree, whose marks I renew, Thence

West on South boundary.

Va. 19° E.

Descend hill with scattering oaks.

3.00 Ascent S. slope of hill.

11.50 Top of rise, begin descent.

20.02 The SW. corner. The post set for this cor. is gone, but the bearing tree is standing. I restore this cor. by setting a fir post 4 1/2 ft. long, 4 ins. square, 24 ins. in the ground, marked T. 30 S. R. 4 W. C. 41. on NE face, from which