

CHAINS

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
TOWNSHIP 29 SOUTH, RANGE 4 WEST,
AND A PORTION OF THE SUBDIVISIONAL LINES AND
BOUNDARIES OF DONATION LAND CLAIM NOS. 41, 42, 43 AND 44,
AND
THE SUBDIVISION OF SECTIONS 4, 5, 17 AND 21,
TOWNSHIP 30 SOUTH, RANGE 4 WEST,
OF THE
WILLAMETTE MERIDIAN
IN THE STATE OF OREGON.

EXECUTED BY

Bryan S. Seibold, Cadastral Surveyor
Robert H. Browning, Surveying Technician

Under Special Instructions dated May 6, 1993, approved May 7, 1993,
and Supplemental Special Instructions dated August 24, 1993,
approved August 24, 1993,
which provided for the surveys included under Group No. 1686,
and Assignment Instructions dated May 20, 1993, and September 3, 1993.

Survey commenced May 24, 1993

Survey completed April 7, 1995

T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, township 29 south, range 4 west, a portion of the subdivisional lines and boundaries of Donation Land Claims Nos. 41, 42, 43 and 44, and the subdivision of sections 4, 5, 17 and 21, township 30 south, range 4 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The west boundary was surveyed by James E. Freeman, U.S. Deputy Surveyor, in 1851.

The south boundary of T. 29 S., R. 4 W., the east boundary and a portion of the subdivisional lines was surveyed by Nathaniel Ford, U.S. Deputy Surveyor, in 1854.

The boundaries of Donation Land Claim Nos. 41, 42, 43, and 44 were surveyed by Elliott N. Bowman and Josiah A. Burnett, U.S. Deputy Surveyors, in 1860.

The south boundary of T. 29 S., R. 4 W., the east boundary, a portion of the subdivisional lines, and a portion of Donation Land Claim boundaries of T. 30 S., R. 4 W. were resurveyed by William Thiel, U.S. Deputy Surveyor, in 1889.

The east boundary and a portion of the subdivisional lines were resurveyed by William F. Briggs, U.S. Deputy Surveyor, in 1891.

The remaining subdivisional lines were surveyed by William M. Bushey, U.S. Deputy Surveyor, in 1893.

A portion of the subdivisional lines were resurveyed and section 23 subdivided by James E. Jelley, Cadastral Surveyor, in 1981-82.

Portions of the south boundary and subdivisional lines were resurveyed, and section 31, T. 29 S., R. 4 W., was subdivided by Wayne L. Rogers, Dale T. Bedell, and Bryan S. Seibold, Cadastral Surveyors, and Robert H. Browning, Surveying Technician, in 1991-93.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 6, 1993, and Supplemental Special Instructions dated August 24, 1993, for Group No. 1686, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. An analysis of the unadjusted field data assured a closure exceeding 1:4000 in error. Measured distance and direction have been adjusted by Cadastral Measurement Management (CMM), a computer program that incorporates least squares analysis. The adjusted bearings and distances are reported to the nearest second and 0.001 of a chain.

T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the corner of sections 4, 5, 8 and 9, as determined from a tie to U. S. Geological Survey triangulation station "BLAND MTN. 1953," is as follows:

Latitude: 42° 59' 01.35" N. Longitude: 123° 11' 11.20" W.

The geographic position (NAD 1927) of the corner of sections 8, 9, 16 and 17, as determined from a tie to U. S. Geological Survey triangulation station "BLAND MTN. 1953," is as follows:

Latitude: 42° 58' 09.86" N. Longitude: 123° 11' 12.65" W.

The mean magnetic declination is 18½° East.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the survey by Nathaniel Ford in 1854
and the resurvey by William Thiel in 1889)

Beginning at the 1/4 sec. cor. of sec. 34 only, at proportionate distance determined by the Irregular Boundary Method; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T29S R4W
1/4 S 34

T30S R4W
1994

from which

A fir, 8 ins. diam., bears N. 67½° W., 36½ lks. dist., mkd.
1/4 S34 BT.

A cedar, 7 ins. diam., bears N. 20½° W., 26½ lks. dist., mkd.
1/4 S34 BT.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established during the course of an administrative survey as the 1/4 sec. cor. of sec. 3 only by Alex Tupyti, Roseburg District, Bureau of Land Management, in 1978, bears S. 86° 39' 57" E., 34.901 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above ground.</p> <p>From this same point, a point established as the 1/4 sec. cor. of sec. 3 only by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 91, bears S. 86° 49' 00" E., 35.065 chs. dist.; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, from which bearing trees mkd. by Markham:</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears S. 47 3/4° E., 20 lks. dist., with scribe mark S visible on opened blaze.</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears S. 12° E., 16 lks. dist., with scribe marks 1/4 S3 visible on opened blaze.</p> <p>From this same point, the cor. of secs. 34 and 35 perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 4 W., No. 71, further perpetuated by James W. Byron, Deputy County Surveyor, in 1956, recorded in the Douglas County Surveyors Office map file RM 1-8, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 4 W., No. 219, bears S. 86° 40' 10" E., 40.174 chs. dist.; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 8 ins. above ground, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A root hole, bears N. 86° E., 52 lks. dist., with oak trunk, 23 ins. diam, laying alongside, no marks visible. (Record, N. 80° E., 60 lks.)</p> <p style="padding-left: 40px;">A root hole, bears S. 47½° E., 40 lks. dist., with oak stump alongside, no marks visible. (Record, S. 57° E., 32 lks.)</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears S. 43 3/4° W., 26 lks. dist., no marks visible on decayed blaze. (Record, S. 40° W., 28 lks.)</p> <p>and the remains of a bearing tree mkd. by Markham</p> <p style="padding-left: 40px;">A pine snag, 22 ins. diam., bears N. 49 3/4° E., 35½ lks. dist., with healed double blazes.</p> <p>and a bearing tree mkd. by Byron in 1956</p> <p style="padding-left: 40px;">A root hole, bears N. 54 3/4° W., 48 lks. dist., with fir trunk, 12 ins. diam., laying alongside, no marks visible.</p> <p>and a bearing tree mkd. by Byron in 1963</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A madrone, 13 ins. diam., bears N. $32\ 3/4^\circ$ W., 94 lks. dist., with scribe marks S34 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W S 34 * S 35 S 3 T30S R4W 1994</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 80° E., $35\ 1/2$ lks. dist., mkd. T29S R4W S35 BT.</p> <p>N. $88^\circ 52' 15''$ W., on the S. bdy. of sec. 34.</p> <p>Ascend over gentle E. slope, through moderate timber and dense undergrowth.</p>
5.742	True point for the closing cor. of secs. 3 and 4, hereinafter described.
25.474	<p>Point for the E 1/16 sec. cor. of sec. 4 only.</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"><u> E1/16 S 4</u> 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 29° E., 39 lks. dist., mkd. E1/16 S4 BT.</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears S. 57° W., 54 lks. dist., mkd. E1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the E 1/16 sec. cor. of sec. 4 only by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office file CS 51/19, bears N. $79^\circ 02' 17''$ E., 0.176 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of bearing trees mkd. by Ramsey:</p> <p style="padding-left: 40px;">A fir snag, 5 ins. diam., bears S. 61° E., 51 lks. dist., with scribe marks 16 S4 RS404 BT visible on open blaze.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A cedar, 24 ins. diam., bears S. 10° W., 16 lks. dist., with healed blaze.</p> <p>This point was rejected due to improper control and not utilized in this survey.</p> <p>Ascend over gentle E. slope.</p>
25.70	Dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E., and top of ridge bearing same; desc. over broken SW. slope.
35.90	Ridge, bears N. 20° E. and S. 20° W.; desc. over broken NW. slope.
37.55	Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.
38.10	Gravelled road, 20 lks. wide, bears N. 15° E. and S. 15° W.
40.302	<p>The cor. of secs. 33 and 34 perpetuated by Fredrick E. Warner, Registered Professional Land Surveyor No. 298, in 1957, recorded in the Douglas County Surveyors Office file CS 42/257, further perpetuated by George J. Wenderoth, Registered Professional Land Surveyor No. 5, in 1957, recorded in the Douglas County Surveyors Office map file M5-30, further perpetuated by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office file CS 51/19, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 4 W., No. 223; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A fir, 39 ins. diam., bears N. 30½° E., 37 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 63½° W., 11 lks. dist., with healed blaze.</p> <p>and a remaining bearing tree mkd. by Wenderoth</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 70½° W., 56 lks. dist., with healed blaze.</p> <p>and the remains of a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A madrone snag, 11 ins. diam., bears N. 48 3/4° E., 62 lks. dist., with scribe marks 29S R4W S34 CS BT visible on open double blazes.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T29S R4W <u>S 33 * S 34</u> S 4 T30S R4W 1994</p> </div>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
4.914	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr/> <p>N. 86° 21' 24" W., on the S. bdy. of sec. 33.</p> <p>Descend over broken NW. slope, through moderate timber and dense undergrowth.</p> <p>Point for the 1/4 sec. cor. of sec. 4 only, at proportionate position of the N. bdy. of the section.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W !!!!!-- 1/4 S 4 T30S R4W 1994</p> <p>from which</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S. 32° E., 42 lks. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 74½° W., 18½ lks. dist., mkd. 1/4 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the 1/4 sec. cor. of sec. 4 only by Fredrick E. Warner, Registered Professional Land Surveyor No. 298, in 1957, recorded in the Douglas County Surveyors Office CS file 42/257, perpetuated by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office CS file 51/19, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 184, bears S. 87° 11' 38' E., 0.395 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above ground, from which bearing trees mkd. by Warner:</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S. 0½° E., 26 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 28½° W., 34½ lks. dist., with healed blaze.</p> <p>Warner established this corner at midpoint instead of at proportionate position based on the lotting, therefore, it is not utilized in this survey.</p> <p>Descend over broken W. slope.</p>
18.336	<p>Point for the E 1/16 sec. cor. of sec. 33 only, T. 29 S., R. 4 W.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E1/16 S 33 ----- 1994</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 76 3/4° E., 76 lks. dist., mkd. E1/16 S33 BT.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 62° W., 2½ lks. dist., mkd. E1/16 S33 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the E 1/16 sec. cor. of sec. 33 only, T. 29 S., R. 4 W. by L. E. Ager, Registered Professional Land Surveyor No. 21, determined at recorded bearings and distances from the bearing trees, recorded in the Douglas County Surveyors Office file CS 42/383, bears S. 84° 55' 33" E., 0.815 chs. dist., from which bearing trees mkd. by Ager:</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 70° E., 30 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 23° W., 17 lks. dist., with healed blaze.</p> <p>This point was rejected due to erroneous position and not used in this survey.</p> <p>Descend over broken W. slope.</p>
21.05	Creek (Stinger Gulch), 5 lks. wide, course S. 30° W.; asc. over E. slope.
34.85	Spur, slopes S. 20° E.; desc. over SW. slope.
36.672	<p>The 1/4 sec. cor. of sec. 33 only, restored by person(s) unknown, this position was used and perpetuated by Fredrick E. Warner, Registered Professional Land Surveyor No. 298, in 1957, recorded in the Douglas County Surveyors Office CS file 42/257, and is accepted as a careful and faithful determination of the original corner; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 10 ins. above ground, from which bearing trees mkd. by Warner:</p> <p style="padding-left: 40px;">A madrone, 14 ins. diam., bears N. 79½° E., 31½ lks. dist., with faint scribe marks BT visible on the bark.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears N. 22¼° W., 22½ lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	T29S R4W 1/4 S 33 !!!!!----- T30S R4W 1994
	from which a new bearing tree
	A cedar, 10 ins. diam., bears N. 64° E., 45 lks. dist., mkd. 1/4 S33 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

	S. 87° 43' 25" W., beginning new measurement.
	Descend over SW. slope, through timber and moderate undergrowth.
4.95	Ravine, drains S. 60° E.; asc. over SE. slope.
6.953	True point for the closing cor. of secs. 4 and 5, hereinafter described.
15.65	Ridge, bears N. and S.; desc. over SW. slope.
25.60	Ravine, drains S. 20° W.; asc. over SE. slope.
27.280	Point for the E 1/16 sec. cor. of sec. 5 only.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	_____ E1/16 S 5 1994
	from which
	A fir, 8 ins. diam., bears S. 75° E., 73 lks. dist., mkd. E1/16 S5 BT.
	A fir, 32 ins. diam., bears S. 1° E., 26 lks. dist., mkd. E1/16 S5 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SE. slope.
30.55	Spur, slopes S. 20° W.; desc. over SW. slope.
34.75	Ravine, drains S. 10° W.; asc. over SE. slope.
40.068	The cor. of secs. 32 and 33, perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 4 W., No. 28, further perpetuated by Jack L. Sheppard, Registered Professional Land Surveyor No. 180, in 1955, recorded in the Douglas County Surveyors Record of Government

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Corners Renewed, T. 29 S., R. 4 W., No. 92; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, from which the original bearing trees:</p> <p style="padding-left: 40px;">A madrone, 21 ins. diam., bears N. 31½° E., 89 lks. dist., with fragmentary scribe marks visible on open partially decayed blaze. (Record, N. 30° E.)</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears N. 9 ¾° W., 49 lks. dist., with healed blaze. (Record, N. 72° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R4W S 32 * S 33 ----- ----- S 5 T30S R4W 1994</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 12° E., 48 lks. dist., mkd. T29S R4W S33 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr/> <p>N. 88° 59' 04" W., on the S. bdy. of sec. 32.</p> <p>Ascend over SE. slope, through timber and moderate undergrowth.</p> <p>3.45 Spur, slopes S.; desc. over broken SW. slope.</p> <p>7.534 Point for the 1/4 sec. cor. of sec. 5 only, at midpoint of the N. bdy. of the section.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R4W !!!!!! 1/4 S 5 T30S R4W 1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 19 ¾° E., 14½ lks. dist., mkd. 1/4 S5 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 77° W., 40½ lks. dist., mkd. 1/4 S5 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, a point established as the 1/4 sec. cor. of sec. 5 only by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 84, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 183, bears South, 0.152 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of bearing trees mkd. by Markham:</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 20° E., 166 lks. dist., with no marks visible.</p> <p style="padding-left: 40px;">A madrone, 24 ins. diam., bears S. 55 3/4° W., 109 lks. dist., with no marks visible.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 64 3/4° E., 133 lks. dist., with healed blaze.</p> <p>It was determined that Markham used proper control in an east and west position and improper control in a north and south position, therefore, this point was rejected.</p> <p>Descend over broken SW. slope.</p>
9.20	Ravine, drains S. 15° W.; asc. over SE. slope.
11.90	Spur, slopes S.; desc. over broken SW. slope.
14.55	Ravine, drains S. 15° E.; asc. over SE. slope.
19.261	Point for the E 1/16 sec. cor. of sec. 32 only.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E1/16 S 32</p> <p style="text-align: center;">-----</p> <p style="text-align: center;">1994</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 36 3/4° E., 19 lks. dist., mkd. E1/16 S32 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 15½° W., 16½ lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p>
23.25	Ravine, drains S. 70° E.; asc. over E. slope.
27.80	Dirt road, 20 lks. wide, bears N. 30° E. and S. 20° W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
27.938	<p>Point for the W 1/16 sec. cor. of sec. 5 only.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">----- W1/16 S 5 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 42° E., 61 lks. dist., mkd. W1/16 S5 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 60½° W., 28½ lks. dist., mkd. W1/16 S5 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on the W. edge of an abandoned dirt road.</p> <p>Ascend over E. slope.</p>
35.90	<p>Spur, slopes S.; desc. over SW. slope.</p>
38.522	<p>The 1/4 sec. cor. of sec. 32 only, perpetuated by George A. Barnhart, Registered Professional Land Surveyor No. 120, in 1947, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 4 W., No. 66, further perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1949, recorded in the Douglas County Surveyors Office file, CS 40-238, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 4 W., No. 214; monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A sawed madrone stump, 48 ins. diam., bears N. 70° E., 63 lks. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 88 3/4° E., 4 lks. dist., with healed double blazes.</p> <p style="padding-left: 40px;">A fir snag, 11 ins. diam., bears N. 57½° W., 12 lks. dist., with scribe marks 1/4 S32 CS BT visible on open double blazes.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	T29S R4W 1/4 S 32 !!!!!!!! T30S R4W 1994
	from which a new bearing tree
	A fir, 17 ins. diam., bears N. $36\frac{1}{2}^{\circ}$ W., 25 $\frac{1}{2}$ lks. dist., mkd. 1/4 S32 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

	N. $88^{\circ} 54' 27''$ W., beginning new measurement.
	Descend over broken SW. slope, through timber and moderate undergrowth.
4.80	Dirt road, 20 lks. wide, bears N. 25° E. and S. 25° W.
9.820	True point for the closing cor. of secs. 5 and 6, hereinafter described.
	Descend over broken SW. slope.
16.05	Three wire high tensile power transmission line, bears N. 10° E. and S. 10° W.
17.35	County Road No. 42 (Days Creek Cut-Off Road), gravelled, 30 lks. wide, bears N. and S. 40° E.
17.75	Three wire high tensile power transmission line, bears N. 10° E. and S. 10° W.
19.10	Three wire high tensile power transmission line, bears N. 10° E. and S. 10° W.
20.90	Ravine, drains S.; asc. over SE. slope.
28.10	Spur, slopes S. 10° W.; desc. over S. slope.
39.780	The cor. of secs. 31 and 32, monumented with an iron post, 1 $\frac{1}{4}$ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T29S R4W <u>S 31 * S 32</u> S 6 1961
	from which the remains of the bearing trees mkd by George A. Barnhart, Registered Professional Land Surveyor No. 120, in 1947
	A fir snag, 10 ins. diam., bears S. $52\frac{1}{2}^{\circ}$ E., 50 lks. dist., no marks visible.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

A decayed fir stump, size indeterminate, bears N. 22° W., 50 lks. dist., with scribe marks T29S R W visible on open blaze.

and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1961

A madrone snag, 23 ins. diam., bears S. 59° W., 196 lks. dist., with healed upper blaze and scribe marks BT visible on partially healed lower blaze.

and bearing trees mkd. by Rogers, Bedell, Seibold and Browning

A fir, 4 ins. diam., bears S. 51° E., 44 lks. dist., with scribe marks T30S R4W S6 BT visible on open blaze.

A fir, 5 ins. diam., bears S. 15½° W., 25½ lks. dist., with scribe marks X BT visible on open double blazes.

A fir, 10 ins. diam., bears N. 44½° W., 40 lks. dist., with scribe marks T29S R4W S31 BT visible on open blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the survey by Nathaniel Ford, in 1854,
and the resurvey by William Thiel, in 1889)

From the cor. of secs. 21, 22, 27 and 28, perpetuated by Arthur Boyer, Deputy County Surveyor, in 1937, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 48, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 203; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 9 ins. above ground, from which the remaining original bearing trees:

A madrone snag, 11 ins. diam., bears S. 49 3/4° E., 64 lks. dist., with fragmentary scribe mark S visible on partially healed blaze. (Record, S. 42° E., 67 lks.)

A cedar, 29 ins. diam., bears S. 75° W., 44 lks. dist., with scribe marks 30S R4W visible on opened blaze.

and a bearing tree mkd. by Boyer

A cedar, 27 ins. diam., bears N. 5½° E., 33½ lks. dist., with healed blaze.

and bearing trees mkd. by Byron

A fir, 19 ins. diam., bears S. 45 3/4° E., 60 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 8° W., 54 lks. dist., with healed double blazes.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W S 21 * S 22 S 28 * S 27 1995</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the 1/4 sec. cor. of secs. 21 and 28, bears N. 89° 09' 16" W., 38.292 chs. dist., hereinafter described.</p> <p>N. 1° 45' 24" E., bet. secs. 21 and 22.</p> <p>Descend over broken NW. slope, through second growth timber and dense undergrowth.</p>
1.50	Ravine, drains N. 60° W.; asc. over SW. slope.
4.60	Spur, slopes N. 40° W.; desc. over NW. slope.
27.75	County Road No. 94 (Shively Creek Road), asphalt-surfaced, 40 lks. wide, bears N. 80° W. and S. 80° E.
38.285	<p>The witness corner for the 1/4 sec. cor. of secs. 21 and 22, established by Romanso E. Ware, Registered Professional Land Surveyor No. 1005, in 1981, recorded in the Douglas County Surveyors Office map file, M89-17, and is accepted; monumented with an iron rod, 5/8 in. diam., firmly set 4 ins. below ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T30S R4W 1/4 S 21 * S 22 1993</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 38 ins. diam., bears South, 127 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A maple, 7 ins. diam., bears S. 59° W., 231 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of and iron rod alongside of stainless steel post.</p> <p>Continue over river bottom.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
38.85	Left bank of the South Umpqua River, bears N. 80° W. and S. 80° E., course N. 80° W.; across river.
39.407	True point for the 1/4 sec. cor. of secs. 21 and 22, reestablished by Romanso E. Ware, Registered Professional Land Surveyor No. 1005, in 1981, recorded in the Douglas County Surveyors Office map file, M89-17, and is accepted as the corner, not monumented, point falls in the South Umpqua River.

	N. 1° 23' 50" E., beginning new measurement.
	Across river.
2.75	Right bank of the South Umpqua River, bears N. 55° W. and S. 70° E.; over nearly level ground.
19.574	Point for the N 1/16 sec. cor. of secs. 21 and 22, not monumented due to landowners request.
	Over nearly level ground.
23.95	County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 45 lks. wide, bears N. 65° W. and S. 65° E.; asc. over broken SE. slope.
36.05	Spur, slopes S. 50° W.; desc. over broken W. slope.
39.148	The cor. of secs. 15, 16, 21 and 22, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1940, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 64, further perpetuated by James W. Byron, Deputy County Surveyor, in 1959, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 140; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T30S R4W S 16 * S 15 S 21 * S 22 1959
	from which the remains of bearing trees mkd. by Irving
	A sawed fir stump, 44 ins. diam., bears N. 51° E., 333 lks. dist., with scribe marks BT visible on the bark.
	A sawed fir stump, 30 ins. diam., bears S. 68° E., 212 lks. dist., with part of a healed blaze.
	An oak, 20 ins. diam., bears N. 17° W., 345 lks. dist., with healed double blazes.
	and the remains of a bearing tree mkd. by Byron
	A burned oak snag, 34 ins. diam., bears N. 72° E., 302 lks. dist., with healed double blazes.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

and new bearing trees

A fir, 16 ins. diam., bears N. 33° E., 20½ lks. dist., mkd.
T30S R4W S15 BT.

A fir, 18 ins. diam., bears S. 59¼° E., 31 lks. dist., mkd.
T30S R4W S22 BT.

A fir, 21 ins. diam., bears S. 82¼° W., 25½ lks. dist., mkd.
T30S R4W S21 BT.

A fir, 11 ins. diam., bears N. 71 3/4° W., 32½ lks. dist.,
mkd. T30S R4W S16 BT.

From the cor. of secs. 3, 4, 9 and 10, monumented with an aluminum post, 2½ ins. diam, firmly set, projecting 6 ins. above ground, with aluminum cap mkd.

T30S R4W
S 4 * S 3
S 9 * S 10
1981

from which the remaining original bearing trees

An oak, 21 ins. diam., bears N. 32½° E., 19 lks. dist., with
healed double blazes.

An oak, 37 ins. diam., bears N. 83° W., 59 lks. dist., with
healed blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor,
in 1963

A madrone, 13 ins. diam., bears S. 32° E., 21 lks. dist.,
with healed double blazes.

A madrone, 11 ins. diam., bears S. 82° W., 26 lks. dist.,
with healed double blazes.

and bearing trees mkd. by Jelley

A fir, 9 ins. diam., bears S. 55¼° W., 71½ lks. dist., with
healed blaze. (Record, S. 52½° W.)

A fir, 11 ins. diam., bears N. 57° W., 57 lks. dist., with
healed blaze.

N. 0° 16' 08" E., bet. secs. 3 and 4.

Ascend over S. slope, through scattered timber and dense
undergrowth.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
19.259	<p>The S 1/16 sec. cor. of secs. 3 and 4, established by Larry D. Bishop, Registered Professional Land Surveyor No. 895, in 1970, recorded in the Douglas County Surveyors Office map file, M42-1, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of bearing trees mkd. by Bishop:</p> <p style="padding-left: 40px;">The most southerly trunk of a double trunk cedar, 34 ins. diam., bears N. 45¼° E., 35 lks. dist., with scribe marks S1/16 S3 BT visible on open blaze.</p> <p style="padding-left: 40px;">A root hole, bears N. 13° W., 14 lks. dist., with decayed remains of a pine scattered about.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">S1/16 S 4 * S 3 1994</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 28½° W., 67 lks. dist., mkd. S1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established during the course of an administrative survey as the S 1/16 sec. cor. of secs. 3 and 4 by Alex Tupy, Roseburg District, Bureau of Land Management, in 1978, bears N. 1° 22' 56" E., 0.068 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground. This point was not utilized during the course of this survey, the iron pipe was removed and buried inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 18' 41" E., beginning new measurement.</p> <p>Ascend over SE. slope, through timber and light undergrowth.</p>
19.394	<p>The 1/4 sec. cor. of secs. 3 and 4, perpetuated by G. G. Stewart, Deputy County Surveyor, in 1922, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 25, further perpetuated by Fredrick E. Warner, Registered Professional Land Surveyor No. 298, in 1957, recorded in the Douglas County Surveyors Office file, CS 42/257, further perpetuated by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office file, CS 51/19; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above ground, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A root hole, bears S. 35½° W., 26 lks. dist., with decayed oak trunk, 24 ins. diam., alongside, with no marks visible on decayed face. (Record, S. 45° W.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>and the remains of bearing trees mkd. by Warner</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 77¼° E., 33 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A sawed cedar stump, 28 ins. diam., bears N. 76° W., 55 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W 1/4 S 4 * S 3 1994</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears S. 16½° W., 72 lks. dist., mkd. 1/4 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 19' 57" W., beginning new measurement.</p> <p>Ascend over SE slope, through timber and scattered undergrowth.</p>
10.80	<p>Gravelled road, 20 lks. wide, bears N. 80° E. and S. 80° W., and top of ridge bearing same, desc. over broken N. slope.</p>
19.394	<p>Point for the N 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N1/16 S 4 * S 3 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 71° E., 64 lks. dist., mkd. N1/16 S3 BT.</p> <p style="padding-left: 40px;">A maple, 13 ins. diam., bears N. 66¼° W., 41½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 15¼° W., 45½ lks. dist., mkd. N1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established during the course of an administrative survey as the N 1/16 sec. cor. of secs. 3 and 4 by Alex Tupy, Roseburg District, Bureau of Land Management, in 1978,</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS													
	<p>bears S. 82° 02' 43" W., 0.011 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Tupyí:</p> <p style="padding-left: 40px;">A sawed fir stump, 24 ins. diam., bears S. 46 3/4° E., 21½ lks. dist., with no marks visible on open blaze. A railroad spike has been driven into the center of blaze.</p> <p style="padding-left: 40px;">A maple, 13 ins. diam., bears N. 65½° W., 41½ lks. dist., with healed blaze.</p> <p>This point was not utilized during the course of this survey, the iron pipe was removed and buried inside the stainless steel post and a new bearing and distance was taken to the maple bearing tree.</p> <p>Descend over broken W. slope.</p>												
42.45	<p>Spur, slopes E.; desc. over broken NE. slope.</p>												
53.238	<p>Intersect the S. bdy. of T. 29 S., R. 4 W.</p> <p>True point for the closing cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T29S</td><td>R4W</td></tr> <tr><td style="border-top: 1px solid black;">S 34</td><td></td></tr> <tr><td>S 4</td><td>* S 3</td></tr> <tr><td></td><td>C C</td></tr> <tr><td>T30S</td><td>R4W</td></tr> <tr><td></td><td>1994</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 42¼° E., 53 lks. dist., mkd. T30S R4W S3 CC BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 84½° W., 80 lks. dist., mkd. T30S R4W S4 CC BT.</p> <p>From this point, the original closing cor. of secs. 3 and 4, perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 93, further perpetuated by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office file, CS 51/19, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 189, bears N. 0° 19' 57" W., 0.038 chs. dist.; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 1 in. above ground, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A sawed fir stump, 36 ins. diam., bears S. 8° W., 27 lks. dist., with no marks visible. (Record, 24 lks.)</p>	T29S	R4W	S 34		S 4	* S 3		C C	T30S	R4W		1994
T29S	R4W												
S 34													
S 4	* S 3												
	C C												
T30S	R4W												
	1994												

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

and the remains of a bearing tree mkd. by Markham

A cedar, 27 ins. diam., bears S. 5° E., 48 lks. dist., with
healed double blazes.

and a bearing tree mkd. by Byron

A fir, 17 ins. diam., bears S. 55 3/4° W., 78 lks. dist.,
with healed double blazes.

From this same point, the 1/4 sec. cor. of sec. 34 only, T. 29 S.,
R. 4 W., bears S. 88° 52' 15" E., 5.742 chs. dist., hereinbefore
described.

From the 1/4 sec. cor. of secs. 20 and 21, perpetuated by John H.
Markham, Jr., Registered Professional Engineer No. 2880, in 1953,
recorded in the Douglas County Surveyors Record of Government
Corners Renewed, T. 30 S., R. 4 W., No. 100, further perpetuated
by William J. Ruppert, Registered Professional Land Surveyor No.
866, in 1980, recorded in the Douglas County Surveyors Office map
file, M79-65; monumented with an iron post, 1 in. diam., laying
horizontal underground, with brass cap mkd., T30S R4W 1/4 S20 S21
PLS 866 1980, the iron pipe has been disturbed, therefore the
corner position was determined at record bearing and dist. from a
remaining original bearing tree:

An oak, 46 ins. diam., bears S. 70° E., 260 lks. dist., with
healed double blazes.

and a bearing tree mkd. by Markham

An oak, 29 ins. diam., bears N. 69½° E., 48 lks. dist., with
healed double blazes.

and the remains of a bearing tree mkd. by Ruppert

An oak snag, 16 ins. diam., bears N. 11 3/4° W., 41½ lks.
dist., with scribe marks 1/4 S20 BT visible on open blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins.
in the ground, with brass cap mkd.

T30S R4W
 1/4
 S 20 * S 21
 1994

Deposit a white "DEEP-1" magnetic marker at base of and iron pipe
alongside of stainless steel post.

The corner is located S. 52° E., 0.18 chs. dist. of a fence
corner, with woven wire fences extending N. and W.

N. 1° 42' 59" E., bet. secs. 20 and 21.

Ascend over broken S. slope, through open hillside pasture.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
9.10	Ridge, bears N. 65° E. and S. 65° W.; desc. over broken NW. slope, enter second growth timber and dense undergrowth.
20.154	<p>Point for the N 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N1/16 S 20 * S 21 1994</p> <p>from which</p> <p style="padding-left: 40px;">A madrone, 5 ins. diam., bears N. 27° E., 60 lks. dist., mkd. N1/16 S21 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 46½° W., 31½ lks. dist., mkd. N1/16 S20 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NW. slope.</p>
40.308	<p>The cor. of secs. 16, 17, 20 and 21, perpetuated by Willis M. Ausland, Registered Professional Engineer No. 2037, in 1942, recorded in 1958 in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 138-A, further perpetuated by James W. Byron, Deputy County Surveyor, in 1955 and 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., Nos. 133 and 224; monumented with a gun barrel, firmly set, projecting 6 ins. above ground, from which the remaining original bearing trees:</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 20° E., 15½ lks. dist., with partially healed blaze. (Record, 10 lks.)</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears S. 64¼° E., 17 lks. dist., with healed double blazes. (Record, S. 47½° E., 19 lks.)</p> <p>and the remains of a bearing tree mkd. by Byron in 1955</p> <p style="padding-left: 40px;">A root hole, bears N. 10¼° W., 54 lks. dist., with decayed fir trunk, size indeterminate, laying alongside.</p> <p>and a bearing tree mkd. by Byron in 1963</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears N. 87 3/4° W., 111 lks. dist., with healed double blazes.</p> <p>At the corner point.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the gun barrel, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	T30S R4W <u>S 17 * S 16</u> S 20 * S 21 1994
	from which new bearing trees A fir, 11 ins. diam., bears S. 83° W., 85 lks. dist., mkd. T30S R4W S20 BT. A fir, 6 ins. diam., bears N. 5° W., 76 lks. dist., mkd. T30S R4W S17 BT. Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	<hr/> From the cor. of secs. 15, 16, 21 and 22. N. 85° 33' 06" W., bet. secs. 16 and 21. Descend over broken W. slope, through second growth timber and dense undergrowth.
7.95	Gravelled road, 20 lks. wide, bears N. 30° W. and S. 80° W.
9.55	County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 45 lks. wide, bears N. 20° E. and S. 20° W.
19.933	The E 1/16 sec. cor. of secs. 16 and 21, established by Willis M. Ausland, Registered Professional Engineer No. 2037, in 1942, recorded in the Douglas County Surveyors Office, CS File 36/17, perpetuated by James W. Byron, Deputy County Surveyor, in 1959, recorded in the Douglas County Surveyors Office map file, RM 1-28, and is accepted as the corner; monumented with a gun barrel, firmly set, projecting 3 ins. above ground, from which bearing trees mkd. by Byron: A fir, 21 ins. diam., bears N. 8½° E., 47½ lks. dist., with healed blaze. A fir, 23 ins. diam., bears S. 82° W., 79 lks. dist., with healed double blazes. At the corner point. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the gun barrel, with brass cap mkd.
	S 16 E1/16 !!!!! S 21 1993
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. The corner is located W., 0.13 chs. dist. of a woven wire fence, extending N. 5° E. and S. 5° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	

	N. 85° 32' 15" W., beginning new measurement.
	Descend over gentle W. slope, through scattered trees and undergrowth.
5.45	Right bank of the South Umpqua River, bears N. 15° E. and S. 15° W., course N. 15° E.; across river.
6.50	Left bank of the South Umpqua River, bears N. 15° E. and S. 15° W.; asc. over NE. slope.
8.10	County Highway No. 94 (Shively Creek Road), asphalt-surfaced, 40 lks. wide, bears N. 10° W. and S. 10° E.
16.65	Spur, slopes N. 10° W.; desc. over NW. slope.
17.90	Ravine, drains N. 30° E.; asc. over NE. slope.
20.046	<p>The 1/4 sec. cor. of secs. 16 and 21, perpetuated by Willis M. Ausland, Registered Professional Engineer No. 2037, in 1942, recorded in 1958 in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 138, further perpetuated by James W. Byron, Deputy County Surveyor, in 1959 and 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., Nos. 143 and 204; monumented with a gun barrel, firmly set, projecting 12 ins. above ground (alongside of which is an iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground), from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A root hole, bears N. 12° E., 19 lks. dist., no trace of the tree.</p> <p style="padding-left: 40px;">A sawed fir stump, 18 ins. diam., bears S. 66° W., 16 lks. dist., with no marks visible on opened blaze.</p> <p>and a bearing tree mkd. by Byron in 1963</p> <p style="padding-left: 40px;">A fir snag, 27 ins. diam., bears N. 86½° W., 49½ lks. dist., with healed double blazes.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W S 16 1/4 !!!!! S 21 1994</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 4½° E., 25½ lks. dist., mkd. 1/4 S21 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 4 ins. diam., bears N. 84° W., 26 lks. dist., mkd. 1/4 S16 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the iron rod inside and gun barrel alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">N. 89° 01' 56" W., beginning new measurement.</p> <p>Ascend over broken NE. slope, through second growth timber and dense undergrowth.</p>
19.932	<p>The W 1/16 sec. cor. of secs. 16 and 21, established by Willis M. Ausland, Registered Professional Engineer No. 2037, in 1942, recorded in the Douglas County Surveyors Office, CS File 36/17, and is accepted as the corner; monumented with a gun barrel, firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Ausland:</p> <p style="text-align: center;">A fir snag, 28 ins. diam., bears S. 0¼° W., 69 lks. dist., with no marks visible.</p> <p style="text-align: center;">A sawed fir stump, 40 ins. diam., bears N. 4° W., 11½ lks. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the gun barrel, with brass cap mkd.</p> <p style="text-align: center;">S 16 W1/16 !!!!! S 21 1994</p> <p>from which new bearing trees</p> <p style="text-align: center;">A fir, 11 ins. diam., bears N. 82° E., 34½ lks. dist., mkd. W1/16 S16 BT.</p> <p style="text-align: center;">A fir, 5 ins. diam., bears S. 46° E., 36½ lks. dist., mkd. W1/16 S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">N. 89° 02' 16" W., beginning new measurement.</p> <p>Ascend over broken NE. slope, through second growth timber and dense undergrowth.</p>
1.80	Spur, slopes N. 30° W.; desc. over NW. slope.
12.05	Ravine, drains N.; asc. over NE. slope.
16.15	Spur, slopes N. 30° W.; desc. over SW. slope.
19.972	The cor. of secs. 16, 17, 20 and 21.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 88° 13' 56" W., bet. secs. 4 and 9.</p> <p>Descend over broken S. slope, through scattered timber and undergrowth.</p>
20.063	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 4 E1/16 !!!!! S 9 1994</p> <p>from which</p> <p style="padding-left: 40px;">A prune, 10 ins. diam., bears S. 43 3/4° E., 24 lks. dist., mkd. E1/16 S9 BT.</p> <p style="padding-left: 40px;">A prune, 9 ins. diam., bears N. 74° W., 47½ lks. dist., mkd. E1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Corner is located in a large blackberry patch.</p> <p>Descend over gentle S. slope.</p>
23.65	<p>Woven wire fence, 7 ft. high, extends N. and S., enter prune orchard.</p>
40.126	<p>The 1/4 sec. cor. of secs. 4 and 9, perpetuated by H. L. Eppstein, Douglas County Surveyor, in 1928, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 45, further perpetuated by Fredrick E. Warner, Registered Professional Land Surveyor No. 298, in 1957, recorded in the Douglas County Surveyors Office file, CS 42/257, further perpetuated by James W. Byron, Deputy County Surveyor, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 166; monumented with an iron pipe, 1½ ins. diam., firmly set 8 ins. below ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 38 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W S 4 1/4 !!!!! S 9 1993</p> <p>from which</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

A prune, 10 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ E., 32 $\frac{1}{2}$ lks. dist., not mkd. due to land owners request.

A prune, 9 ins. diam., bears S. 51° E., 25 $\frac{1}{2}$ lks. dist., not mkd. due to land owners request.

A prune, 11 ins. diam., bears S. 58° W., 19 lks. dist., not mkd. due to land owners request.

A prune, 9 ins. diam., bears N. $21\frac{1}{4}^{\circ}$ W., 27 lks. dist., not mkd. due to land owners request.

Buried iron pipe alongside stainless steel post.

From this point, a witness cor. to the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, established by James W. Byron, Deputy County Surveyor, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 166, bears N. $1^{\circ} 28' 22''$ W., 7.725 chs. dist.; monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T30S R4W

WC 510' S TO

S 4

1/4 !!!!!

S 9

1962

from which

An oak, 34 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ E., 441 lks. dist., with healed double blazes.

An oak, 46 ins. diam., bears N. 19° W., 212 lks. dist., with healed double blazes.

The witness cor. is located in a woven wire fence, 7 ft. high, extending N. 80° W. and S. 80° E.

From this same point, a point established by person(s) unknown, bears N. $15^{\circ} 48' 01''$ W., 0.188 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set 4 ins. below ground.

From this same point, the cor. of secs. 4, 5, 8 and 9, bears S. $89^{\circ} 31' 56''$ W., 39.314 chs. dist., hereinafter described.

From the cor. of secs. 4, 5, 8 and 9, perpetuated by George J. Wenderoth, Deputy County Surveyor, in 1949, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 76; monumented with an iron pipe, $2\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, from which the remaining bearing trees mkd. by Wenderoth:

An oak, 22 ins. diam., bears N. 54° E., 121 lks. dist., with healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>An oak, 20 ins. diam., bears N. 82 3/4° E., 172 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W S 5 * S 4 S 8 * S 9 1994</p> <p>from which a new bearing tree</p> <p style="text-align: center;">A pine, 18 ins. diam., bears S. 54° E., 227 lks. dist., mkd. T30S R4W S9 BT.</p> <p>No suitable accessories available in the SW and NW quadrants</p> <p>Deposit a white "DEEP-1" magnetic marker at base of and iron pipe alongside of stainless steel post.</p> <p>From this point, U. S. Geological Survey triangulation station BLAND MTN, bears S. 73° 57' 39" E., 288.739 chs. dist. (mean bearing and sea level distance); monumented with a bronze disk, cemented flush in solid rock, with top mkd. "BLAND MTN 1953" and a triangle.</p> <p>N. 0° 43' 27" E., bet. secs. 4 and 5.</p> <p>Ascend over SE. slope, over open grassland.</p> <p>6.95 Ridge, bears N. 30° E. and S. 30° W.; desc. over broken W. slope.</p> <p>32.10 Ravine, drains N. 70° W.; asc. over SW. slope.</p> <p>37.45 Spur, slopes S. 80° W.; desc. over NW. slope.</p> <p>39.766 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W 1/4 S 5 * S 4 1994</p> <p>from which</p> <p style="text-align: center;">A fir, 15 ins. diam., bears N. 76 3/4° E., 19½ lks. dist., mkd. 1/4 S4 BT.</p> <p style="text-align: center;">A fir, 19 ins. diam., bears S. 39¼° W., 16 lks. dist., mkd. 1/4 S5 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the 1/4 sec. cor. of secs. 4 and 5 by Fredrick E. Warner, Registered Professional Land Surveyor No. 298, in 1957, recorded in the Douglas County Surveyors Office file, CS 42/257, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 236, bears S. 87° 42' 26" E., 0.285 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of bearing trees mkd. by Warner:</p> <p style="padding-left: 40px;">A fir snag, 10 ins. diam., bears S. 77° E., 35½ lks. dist., with scribe marks 1/4 S4 RS298 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir snag, 12 ins. diam., bears S. 14° W., 45½ lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A root hole, bears S. 38° E., 39 lks. dist., with decayed trunk, size indeterminate, alongside, with no marks visible.</p> <p style="padding-left: 40px;">A madrone, 14 ins. diam., bears S. 23 3/4° W., 12½ lks. dist., with healed double blazes.</p> <p>This point was rejected due to erroneous position and not used in this survey.</p> <p>Descend over NW. slope.</p>
47.75	Dirt road, 20 lks. wide, bears N. 60° E. and S. 60° W.
50.10	Creek (Stinger Gulch), 5 lks. wide, course S. 40° W.; asc. over broken SE. slope.
59.649	<p>Point for the N 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N1/16 S 5 * S 4 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 85½° E., 6 lks. dist., mkd. N1/16 S4 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 42 3/4° W., 28 lks. dist., mkd. N1/16 S5 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SE. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS 93.715	<p>Intersect the S. bdy. of T. 29 S., R. 4 W.</p> <p>True point for the closing cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R4W</p> <p style="margin-left: 40px;">S 32</p> <hr style="width: 50px; margin: 0 auto;"/> <p style="margin-left: 40px;">S 5 * S 4</p> <p style="margin-left: 40px;">C C</p> <p>T30S R4W</p> <p style="margin-left: 40px;">1994</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 19 3/4° E., 77 lks. dist., mkd. T30S R4W S4 CC BT.</p> <p style="margin-left: 40px;">A cedar, 22 ins. diam., bears S. 42° W., 46 lks. dist., mkd. T30S R4W S5 CC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the original closing cor. of secs. 4 and 5, perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 85, further perpetuated by Fredrick E. Warner, Registered Professional Land Surveyor No. 298. in 1957, recorded in the Douglas County Surveyors Office file, CS 42/257, bears N. 0° 43' 27" E., 0.262 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears S. 44 3/4° E., 11 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A root hole, bears S. 27½° W., 30 lks. dist., with down fir trunk, 24 ins. diam., alongside, with scribe marks S5 visible on the bark and scribe marks OS R W BT visible on opened blaze.</p> <p>From this same point, the 1/4 sec. cor. of sec. 33 only, T. 29 S., R. 4 W., bears N. 87° 43' 25" E., 6.953 chs. dist., hereinbefore described.</p> <hr style="width: 80%; margin-left: 0;"/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p style="margin-left: 40px;">S. 89° 08' 08" W., bet. secs. 17 and 20.</p> <p>Descend over broken NW. slope, through scattered timber and dense undergrowth.</p>
7.50	Gravelled road, 20 lks. wide, bears N. 20° E. and S. 25° W.
11.15	Ravine, drains N. 10° W.; desc. over broken N. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
12.00	Ravine, drains N. 45° E.; asc. over broken E. slope.
19.264	<p>The E 1/16 sec. cor. of secs. 17 and 20, established by Ronald A. Quimby, Registered Professional Land Surveyor No. 1654, in 1979, recorded in the Douglas County Surveyors Office map file, M80-63, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Quimby:</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 3 3/4° E., 80 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 38¼° W., 70 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 17 E1/16 !!!!! S 20 1994</p> <hr style="width: 20%; margin: auto;"/> </div> <p>S. 89° 09' 07" W., beginning new measurement.</p> <p>Ascend over broken E. slope, through moderate timber and dense undergrowth.</p>
13.60	Spur, slopes N. 55° E.; desc. over NW. slope.
19.269	<p>The 1/4 sec. cor. of secs. 17 and 20, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 225, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE T30S S 17 R 1/4 !!!!! 4 S 20 W 1963</p> </div> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 40° E., 29 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A maple, 12 ins. diam., bears S. 28° W., 31 lks. dist., with healed double blaze.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: auto;"/> </div> <p>S. 84° 32' 33" W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	Descend over NW. slope, through moderate timber and dense undergrowth.
1.60	Ravine, drains N. 20° W.; asc. over NE. slope.
8.80	Spur, slopes N. 45° W.; desc. over broken NW. slope.
16.692	A point established by Ronald A. Quimby, Registered Professional Land Surveyor No. 1654, in 1979, recorded in the Douglas County Surveyors Office map file, M80-63, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, from which bearing trees mkd. by Quimby: <p style="margin-left: 40px;">A fir, 30 ins. diam., bears S. 32 3/4° E., 44½ lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears N. 11 3/4° W., 46 lks. dist., with healed blaze.</p>
18.351	From this point, a point established by Romanso E. Ware, Registered Professional Land Surveyor No. 1005, in 1979, recorded in the Douglas County Surveyors Office map file, M80-35, bears South, 2.390 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground.
20.270	Point for the W 1/16 sec. cor. of secs. 17 and 20. <p style="margin-left: 40px;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="margin-left: 80px;">S 17 W1/16 !!!!! S 20 1994</p> <p style="margin-left: 40px;">from which</p> <p style="margin-left: 80px;">A fir, 18 ins. diam., bears N. 24¼° E., 7 lks. dist., mkd. W1/16 S17 BT.</p> <p style="margin-left: 80px;">A fir, 12 ins. diam., bears S. 17¼° E., 52 lks. dist., mkd. W1/16 S20 BT.</p> <p style="margin-left: 40px;">Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p style="margin-left: 40px;">Descend over broken NW. slope.</p>
40.540	The cor. of secs. 17, 18, 19 and 20, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 214, further perpetuated by Karen Reed, Deputy County Surveyor, in 1978, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 271, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">DOUGLAS CO. SURVEYOR T30S <u>S 18 * S 17</u> S 19 * S 20 R4W 1978</p> <p>from which bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 80¼° E., 158 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 27 ins. diam., bears N. 29½° W., 287 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Reed</p> <p style="padding-left: 40px;">The middle trunk of a triple trunk madrone, 8 ins. diam., bears S. 82 3/4° E., 183 lks. dist., with fragmentary scribe marks visible on partially healed double blazes.</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears S. 47¼° W., 263 lks. dist., with healed double blazes.</p> <hr/> <p>N. 0° 23' 27" E., bet. secs. 17 and 18.</p> <p>Descend over broken N. slope, through mostly open meadows with scattered trees.</p> <p>5.65 Ravine, drains N. 80° W.; continue descent over broken N. slope.</p> <p>40.105 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., determined by the irregular boundary method between the original cor. of secs. 17, 18, 19 and 20 and the reestablished NW cor. of Donation Land Claim No. 42, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W 1/4 S 18 * S 17 1994</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located in the center of a gravelled road, 20 lks. wide, bears N. and S.</p> <hr/> <p>N. 0° 05' 12" W., beginning new measurement.</p> <p>Descend over gradual N. slope, along a gravelled road.</p>
--------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
40.136	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist., determined by the irregular boundary method between the original cor. of secs. 17, 18, 19 and 20 and the reestablished NW. cor. of Donation Land Claim No. 42, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 46 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W <u> S 7 * S 8 </u> S 18 * S 17 1994</p> <p>No suitable accessories available</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the reestablished NE. cor. of Donation Land Claim No. 41, bears N. 0° 00' 41" E., 12.454 chs. dist., hereinafter described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 7 and 8, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 237, bears N. 0° 38' 16" E., 40.643 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T30S R4W 1/4 S7 S8 1963, from which the remains of bearing trees mkd. by Byron:</p> <p style="padding-left: 40px;">A fir snag, 17 ins. diam., bears S. 14° E., 29 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">An oak snag, 15 ins. diam., bears S. 33¼° W., 36½ lks. dist., with healed double blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 75½° E., 57 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 59½° W., 61 lks. dist., mkd. 1/4 S7 BT.</p> <p>From this same point, the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., perpetuated by Arthur R. Evans, Deputy County Surveyor, in 1951, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 115, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 244, bears N. 89° 52' 02" W., 80.590 chs. dist.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A decayed oak, 18 ins. diam., bears N. 74° E., 18 lks. dist., no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

An oak, 21 ins. diam., bears S. $76\frac{1}{2}^{\circ}$ W., 14 lks. dist., with healed triple blaze.

and the remains of bearing trees mkd. by Evans

A sawed fir stump, 31 ins. diam., bears N. $28\frac{1}{2}^{\circ}$ E., 41 lks. dist., with scribe marks BT visible on the bark.

A sawed pine stump, 25 ins. diam., bears S. $9\frac{1}{2}^{\circ}$ W., 50 lks. dist., with healed blaze.

A pine, 13 ins. diam., bears N. $17\frac{1}{4}^{\circ}$ W., 27 lks. dist., with scribe marks T S R5W S visible on the bark.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T30S	
R5W	R4W
S 12 * S 7	

S 13 * S 18	
1994	

from which new bearing trees

A madrone, 11 ins. diam., bears N. $10\frac{1}{2}^{\circ}$ E., 166 lks. dist., mkd. T30S R4W S7 BT.

A madrone, 14 ins. diam., bears S. $50\frac{1}{4}^{\circ}$ E., $12\frac{1}{2}$ lks. dist., mkd. T30S R4W S18 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From the cor. of secs. 8, 9, 16 and 17, perpetuated by Floyd C. Frear, Deputy County Surveyor, in 1919, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 16, further perpetuated by Ben B. Irving, Douglas County Surveyor, in 1948, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 70; monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set flush with the ground, with brass cap mkd. (brass cap is oriented to the east):

T30S	
9	16
8	17
R4W	

from which a bearing tree mkd. by Irving

An oak, 20 ins. diam., bears S. $14\frac{3}{4}^{\circ}$ E., 263 lks. dist., with healed double blaze.

No other suitable accessories available

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>The corner is located at a fence corner, with woven wire fences extending N., S., and W.</p> <p>From this point, the cor. of secs. 4, 5, 8 and 9, bears N. 1° 10' 24" E., 79.000 chs. dist., hereinbefore described.</p> <p>From this same point, U. S. Geological Survey triangulation station BLAND MTN bears S. 89° 50' 05" E., 279.157 chs. dist. (mean bearing and sea level dist.), hereinbefore described.</p> <p>S. 89° 37' 18" W., bet. secs. 8 and 17.</p> <p>Over nearly level ground, through open pastures.</p>
20.15	Gravelled road, 20 lks. wide, bears N. and S.
40.437	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 52 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W S 8 1/4 !!!!! S 17 1995</p> <p>No suitable accessories available</p> <p>Deposit white "DEEP-1" magnetic markers at base of and on top of stainless steel post.</p> <p>The corner is located in a pasture. A small drainage ditch bears S., 0.58 chs. dist., ditch drains N. 10° E.; same ditch also bears E., 0.18 chs. dist., ditch drains N. 40° E.</p> <p>Continue over nearly level ground, through open pastures.</p>
80.75	Gravelled road, 20 lks. wide, bears N. 10° E. and S. 25° W.
80.874	The cor. of secs. 7, 8, 17 and 18.
	<hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 233; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 8 ins. above ground, from which an original bearing tree:</p> <p style="padding-left: 40px;">A madrone, 45 ins. diam., bears N. 65° W., 24 lks. dist., with scribe marks S6 CS B visible on partially decayed, open blaze. (Record, N. 75° W.)</p> <p>and the remains of a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir snag, 12 ins. diam., bears N. 17¼° E., 43 lks. dist., with healed double blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.
	T30S R4W 1/4 S 6 * S 5 1994
	from which a new bearing tree
	A fir, 11 ins. diam., bears N. 39 3/4° E., 61 lks. dist., mkd. 1/4 S5 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	The corner is located at a fence corner, with woven wire fences extending S. and E.
	N. 0° 17' 45" W., bet. secs. 5 and 6.
	Descend over broken NW. slope, through moderate timber and undergrowth.
9.00	Ravine, drains S. 75° W.; asc. over S. slope.
18.15	Spur, slopes N. 70° W.; desc. over N. slope.
20.297	Point for the N 1/16 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	N1/16 S 6 * S 5 1994
	from which
	A fir, 6 ins. diam., bears S. 60¼° E., 44 lks. dist., mkd. N1/16 S5 BT.
	A cedar, 19 ins. diam., bears S. 35° W., 41½ lks. dist., mkd. N1/16 S6 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over N. slope.
29.65	Ravine, drains W.; asc. over S. slope.
47.40	Spur, slopes S. 30° W.; desc. over NW. slope.
54.754	Intersect the S. bdy. of T. 29 S., R. 4 W.
	True point for the closing cor. of secs. 5 and 6.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T29S	R4W
S 32	
S 6 *	S 5
C C	
T30S	R4W
1994	

from which

A fir, 23 ins. diam., bears S. 13 3/4° E., 55 lks. dist., mkd. T30S R4W S5 CC BT.

A fir 20 ins. diam., bears S. 58¼° W., 55 lks. dist., mkd. T30S R4W S6 CC BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point reestablished as the closing cor. of secs. 5 and 6 by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1949, recorded in the Douglas County Surveyors Office file, CS 40/239, bears North, 0.049 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of bearing trees mkd. by Markham:

A fir, 38 ins. diam., bears N. 12½° E., 31 lks. dist., with fragmentary scribe marks visible on the bark.

A madrone snag, 5 ins. diam., bears S. 55 3/4° E., 50 lks. dist., no marks visible on double decayed blaze.

A madrone, 9 ins. diam., bears S. 26¼° W., 60 lks. dist., with healed blaze.

It was determined that Markham used proper control in an east and west direction and improper control in a north and south position, therefore this point was accepted longitudinally but rejected latitudinally.

From this same point, the 1/4 sec. cor. of sec. 32 only, T. 29 S., R. 4 W., bears S. 88° 54' 27" E., 9.820 chs. dist., hereinbefore described.

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43 and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the survey by Josiah A. Burnett and
Elliott N. Bowman, U.S. Deputy Surveyors, in 1860)

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	<p>From the SE. cor. of Donation Land Claim No. 41, perpetuated by Floyd C. Frear, Deputy County Surveyor, in 1919, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 20, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 216; monumented with an iron pipe, 1 in. diam., firmly set 6 ins. below ground, from which a bearing tree mkd. by Frear:</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears N. 80° E., 31½ lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">The most northerly trunk of a triple trunk oak, 41 ins. diam., bears S. 18½° W., 71 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> T30S R4W <u>C 41</u> * S 17 1994 </div> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located N. 20° E., 0.07 chs. dist. of a fence corner, with woven wire fences extending N. and W.</p> <p>N. 0° 27' 04" W., on a portion of the E. bdy. of Claim No. 41.</p> <p>Descend over NW. slope, through scattered timber and undergrowth.</p>
6.521	<p>Point for the SW. cor. of Donation Land Claim No. 42, on the E. bdy. of Donation Land Claim No. 41, at proportionate dist., determined by the Grant Boundary Method between the original SE. cor. of Donation Land Claim No. 41 and the original SW. cor. of Donation Land Claim No. 44, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> T30S R4W * <u>C 42</u> C 41 * <u>S 17</u> 1994 </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 24 ins. diam., bears N. 78 3/4° E., 134 lks. dist., mkd C42 BT.</p>

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 11 ins. diam., bears N. 19 3/4° W., 139 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on the S. edge of a gravelled road, 20 lks. wide, bears S. 80° E. and S. 70° W.</p> <p>The corner is located E., 0.39 chs. dist. of a gravelled road, 20 lks. wide, bears N. 5° E. and S. 5° W.</p> <p>The corner is located N. 25° E., 0.20 chs. dist. of a fence corner, with woven wire fences extending N., S., and E.</p> <hr/> <p>N. 89° 32' 56" E., on the S. bdy. of Claim No. 42.</p> <p>Descend over NE. slope, through grass field with scattered brush.</p>
4.10	Ravine, drains N. 15° W.; asc. over NW. slope.
18.45	Spur, slopes N. 30° W.; desc. over NE. slope.
19.626	Intersect the N. and S. center line of the SW 1/4 of sec. 17.
	Point for the crossing closing cor. of the N. and S. center line of the SW 1/4 of sec. 17 with the S. bdy. of Donation Land Claim No. 42, hereinafter described.
20.251	Point for the SE. cor. of Donation Land Claim No. 42, at proportionate dist., determined by the Grant Boundary Method between the original SE. cor. of Donation Land Claim No. 41 and the original SW. cor. of Donation Land Claim No. 44, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T30S R4W <u> C 42 </u> * S 17 1994
	from which
	A fir, 6 ins. diam., bears S. 42° E., 63 lks. dist., mkd. S17 BT.
	A fir, 12 ins. diam., bears N. 20 3/4° W., 83 lks. dist., mkd. C42 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	The corner is located N. 25° E., 0.30 chs. dist. of a fence corner, with woven wire fence extending N. and barbed wire fence extending W.

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>N. 0° 27' 04" W., on a portion of the E. bdy. of Claim No. 42.</p> <p>Descend over broken NE. slope, though timber and dense undergrowth.</p>
8.161	<p>Point for the SW. cor. of Donation Land Claim No. 43, on the E. bdy. of Donation Land Claim No. 42, at proportionate dist., determined by the Grant Boundary Method between the original SE. cor. of Donation Land Claim No. 41 and the original SW. cor. of Donation Land Claim No. 44, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W * C 43 C 42 ----- * S 17 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 47½° E., 40½ lks. dist., mkd C43 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 17° E., 54 lks. dist., mkd. S17 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located N. 15° E., 0.38 chs. dist. of a fence corner, with woven wire fences extending N., S., and E.</p> <hr/> <p>N. 89° 32' 56" E., on the S. bdy. of Claim No. 43.</p> <p>Ascend over gradual broken N. slope, through heavy timber and moderate undergrowth.</p>
19.617	<p>Intersect the N. and S. center line of sec. 17.</p> <p>Point for the crossing closing cor. of the N. and S. center line of sec. 17 with the S. bdy. of Donation Land Claim No. 43, hereinafter described.</p>
20.251	<p>Point for the SE. cor. of Donation Land Claim No. 43, at proportionate dist., determined by the Grant Boundary Method between the original SE. cor. of Donation Land Claim No. 41 and the original SW. cor. of Donation Land Claim No. 44, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">T30S R4W <u>C 43</u> * S 17 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 31 3/4° E., 28 lks. dist., mkd. S17 BT.</p> <p style="padding-left: 40px;">A cedar, 4 ins. diam., bears N. 65 3/4° W., 34½ lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located N. 75° E., 0.27 chs. dist. of a fence corner, with woven wire fences extending N., S., and E.</p> <hr/> <p>N. 0° 27' 03" W., on a portion of the E. bdy. of Claim No. 43.</p> <p>Descend over N. slope. through scattered timber and dense undergrowth.</p> <p>10.510 The SW. cor. of Donation Land Claim No. 44, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1927, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 41, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 197, determined at recorded bearing and distance from the remains of a bearing tree mkd. by Byron:</p> <p style="padding-left: 40px;">A sawed double trunk oak stump, 40 ins. diam., bears N. 19° E., 129 lks. dist., with scribe mark T visible on opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W * C 44 C 43 ----- * S 17 1994</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 80½° E., 171 lks. dist., mkd. S17 BT.</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 10½° E., 28½ lks. dist., mkd. X BT.</p>
--------	--

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located S. 80° W., 0.09 chs. dist. of a fence corner, with woven wire fences extending S. and E.</p> <hr/> <p>N. 89° 55' 32" E., on the S. bdy. of Claim No. 44.</p> <p>Across broken N. slope, through scattered timber and dense undergrowth.</p>
19.171	<p>Intersect the N. and S. center line of the SE 1/4 of sec. 17.</p> <p>Point for the crossing closing cor. of the N. and S. center line of the SE 1/4 of sec. 17 with the S. bdy. of Donation Land Claim No. 44, hereinafter described.</p>
20.131	<p>The SE. cor. of Donation Land Claim No. 44, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1927, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 40, further perpetuated by James W. Byron, Deputy County Surveyor, in 1964, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 255; monumented with an iron post, 1½ ins. diam., firmly set, projecting 16 ins. above, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T30S — * S.E. DLC 44 R4W 1964</p> <p>from which a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears S. 22½° E., 29 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 21 ins. diam., bears S. 5 3/4° W., 30 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">An oak, 9 ins. diam., bears N. 7° W., 51 lks. dist., with healed blaze.</p> <p>The corner is N. 10° W., 0.09 chs. dist. of a fence corner, with woven wire fences extending S. and W.</p> <hr/> <p>N. 0° 07' 55" E., on the most southerly E. bdy. of Claim No. 44.</p> <p>Descend over N. slope, through timber and moderate undergrowth.</p>
2.35	<p>Creek, 5 lks. wide, course N. 75° W.; asc. over broken SE. slope.</p>
2.50	<p>Dirt road, 20 lks. wide, bears S. 60° E. and W.</p>

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
6.85	Spur, slopes S. 80° W.; desc. over open NW. slope through grass fields.
63.100	<p>Point for the interior L cor. of Donation Land Claim No. 44, at proportionate dist., determined by the Grant Boundary Method between the original most southerly SE. cor. of Donation Land Claim No. 44 and the original most northerly SE. cor. of Donation Land Claim No. 44, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 46 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30S R4W C 44 YYY * S 8 1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">A walnut, 22 ins. diam., bears N. 40¼° E., 136 lks. dist., mkd. C44 BT on the bark.</p> <p>No suitable tree available in the SE quadrant</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr/> <p>S. 89° 52' 05" E., on the most northerly S. bdy. of Claim No. 44. Over level ground, through trees, brush and open fields.</p>
0.30	Gravelled road, 20 lks. wide, bears N. 5° E. and S. 5° W.
76.25	County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 45 lks. wide, bears N. 60° W. and S. 60° E.
77.122	<p>The most northerly SE. cor. of Donation Land Claim No. 44, identical with the SW. cor. of Donation Land Claim No. 47, perpetuated by G. G. Stewart, Deputy County Surveyor, in 1922, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 26, further perpetuated by R. M. Thompson, Registered Professional Engineer, in 1960, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 157, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 245, further perpetuated by Randall Smith, Deputy County Surveyor, in 1988, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 289; monumented with an iron pipe, 2½ ins. diam., firmly set 12 ins. below ground, from which an original bearing tree:</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears N. 79 3/4° E., 92 lks. dist., with healed double blaze. (Record, N. 80° W.)</p> <p>and a bearing tree mkd. by Thompson</p>

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>An oak, 34 ins. diam., bears S. 87½° E., 139 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p>An oak, 20 ins. diam., bears N. 9½° W., 83 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30S R4W C 44 * C 47 S 9 1994</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at base of and iron pipe alongside of stainless steel post.</p> <hr/> <p>From the SW. cor. of Donation Land Claim No.43, on the E. bdy. of Donation Land Claim No. 42.</p> <p>N. 0° 19' 30" W., on the W. bdy. of Donation Land Claim No. 43, a portion of which is identical with a portion of the E. bdy. of Donation Land Claim No. 42.</p> <p>Descend over gentle NW. slope, across mostly open grass fields, with scattered trees and brush.</p>
73.95	<p>County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 40 lks. wide, bears N. 65° E. and S. 65° W.</p>
74.184	<p>The NE. cor. of Donation Land Claim No. 42, at proportionate dist., determined by the Grant Boundary Method between the reestablished SW. cor. of Donation Land Claim. 43 and the original NE. cor. of Donation Land Claim No. 43, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30S R4W S 8 * C 42 * C 43 1994</p> </div> <p>from which</p> <p>A cedar, 31 ins. diam., bears S. 80° E., 149 lks. dist., mkd. X BT.</p> <p>A cedar, 40 ins. diam., bears S. 25° W., 470 lks. dist., mkd. C42 BT.</p>

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NW. slope.</p>
75.45	Left bank of the South Umpqua River, bears N. 70° E. and S. 70° W., course S. 70° W.; across river.
77.55	Right bank of the South Umpqua River, bears N. 70° E. and S. 70° W.; asc. over SE. slope.
78.25	Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.
80.877	<p>Point for the NW. cor. of Donation Land Claim No. 43, at proportionate dist., determined by the Grant Boundary Method between the reestablished SW. cor. of Donation Land Claim No. 43 and the original NE. cor. of Donation Land Claim No. 43, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 46 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30S R4W S 8 YYYYY * C 43 1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears S. 0½° W., 288 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A maple, 10 ins. diam., bears S. 30° W., 404 lks. dist., mkd. S8 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located in a hay field.</p> <hr/> <p>N. 89° 40' 30" E., on the N. bdy. of Claim No. 43.</p> <p>Over level ground, through a hay field.</p>
7.25	Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.; desc. over SE. slope.
8.05	Right bank of the South Umpqua River, bears N. 80° E. and S. 70° W., course S. 70° W.; across river.
13.10	Left bank of the South Umpqua River, bears N. 80° E. and S. 75° W.; asc. over NW. slope.
18.70	County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 45 lks. wide, bears N. 85° E. and S. 80° W.

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS							
20.219	<p>The NE. cor. of Donation Land Claim No. 43, on the W. bdy. of Donation Land Claim No. 44, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1940, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 60, further perpetuated by James W. Byron, Deputy County Surveyor, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 167, and is accepted as a careful and faithful determination of the original corner based on use; monumented with an iron rod, ½ in. diam., firmly set 4 ins. below ground, from which the remains of bearing trees mkd. by Irving:</p> <p style="padding-left: 40px;">A fir snag, 32 ins. diam., bears N. 54½° E., 192 lks. dist., with fragmentary scribe marks visible on the bark.</p> <p style="padding-left: 40px;">A maple, 81 ins. diam., bears S. 2¼° W., 132 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 33 ins. in the ground directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T30S</td> <td>R4W</td> </tr> <tr> <td style="border-bottom: 1px solid black;">S 8</td> <td style="border-bottom: 1px solid black;">*</td> </tr> <tr> <td>C 43</td> <td>* C 44</td> </tr> </table> <p>1994</p> </div> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A maple, 16 ins. diam., bears N. 54° E., 182 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located South, 0.25 chs. dist. from the center of County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 45 lks. wide, bears N. 85° E. and S. 80° W.</p> <p>From this point, the SW. cor. of Donation Land Claim No. 44 bears S. 0° 19' 43" E., 70.322 chs. dist., hereinbefore described.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the SW. cor. of Donation Land Claim No. 42, on the E. bdy. of Donation Land Claim No. 41.</p> <p>N. 0° 57' 57" W., on the W. bdy. of Claim No. 42, a portion of which is identical with a portion of the E. bdy. of Claim No. 41.</p> <p>Descend over gentle N. slope, through grass fields.</p>	T30S	R4W	S 8	*	C 43	* C 44
T30S	R4W						
S 8	*						
C 43	* C 44						
21.829	<p>The 1/4 sec. cor. of secs. 17 and 18, hereinbefore described.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 05' 12" W., on the W. bdy. of Claim No. 42, a portion of which is identical with a portion of the E. bdy. of Claim No. 41, both of which are identical with the N ½ of the sec. line bet. secs. 17 and 18, beginning new measurement.</p>						

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	Descend over gentle N. slope, through grass fields.
40.136	The cor. of secs. 7, 8, 17 and 18, hereinbefore described. <hr style="width: 20%; margin: 10px auto;"/>
	N. 0° 00' 41" E., on the W. bdy. of Claim No. 42, a portion of which is identical with a portion of the E. bdy. of Claim No. 41, beginning new measurement.
	Over nearly level ground, through grass fields.
12.10	County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 40 lks. wide, bears N. 80° E. and S. 70° W.
12.454	Point for the NE. cor. of Donation Land Claim No. 41, at proportionate dist., determined by the Grant Boundary Method between the reestablished SW. cor. of Donation Land Claim No. 42 and the reestablished NE. cor. of Donation Land Claim No. 42, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.
	T30S R4W <u>S 8</u> * C 41 * C 42 1994
	from which
	A maple, 12 ins. diam., bears N. 15¼° E., 28 lks. dist., mkd. X BT.
	An ash, 14 ins. diam., bears N. 21 3/4° W., 49 lks. dist., mkd. S8 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. <hr style="width: 20%; margin: 10px auto;"/>
	N. 0° 19' 42" W., on a portion of the W. bdy. of Claim No. 42, beginning new measurement.
	Descend over NW. slope, through moderate trees and brush.
0.75	Left bank of the South Umpqua River, bears N. 65° E. and S. 75° W., course S. 75° W.; across river.
2.75	Right bank of the South Umpqua River, bears N. 80° E. and S. 65° W.; asc. over SE. slope.
5.058	Point for the NW. cor. of Donation Land Claim No. 42, at proportionate dist., determined by the Grant Boundary Method between the reestablished SW. cor. of Donation Land Claim No. 42 and the reestablished NE. cor. of Donation Land Claim No. 42, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	T30S R4W S 8 * C 42 1994
	from which A power pole, 10 ins. diam., bears S. 14½° W., 216 lks. dist., PPL# 30-04 080200. A power pole, 10 ins. diam., bears N. 27½° W., 388 lks. dist., PPL# 30-04 079200. Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. The corner is located S., 0.10 chs. dist. of a dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W., and N., 0.03 chs. dist. of a woven wire fence, extending N. 80° E. and S. 80° W.
	<hr/> N. 89° 40' 19" E., on the most southerly N. bdy. of Claim No. 42. Descend over SE. slope, through dense undergrowth.
6.45	Right bank of the South Umpqua River, bears N. 65° E. and S. 65° W., course S. 65° W.; across river.
10.117	True point for the interior L cor. of Donation Land Claim No. 42, at proportionate dist., determined by the Grant Boundary Method between the reestablished SW. cor. of Donation Land Claim No. 42 and the reestablished NE. cor. of Donation Land Claim No. 42, there is no remaining evidence of the original corner, not monumented, point falls in the South Umpqua River. From this point, the point selected for the witness cor. to the interior L corner of Donation Land Claim No. 42, bears S. 0° 19' 41" E., 0.900 chs. dist. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.
	W C T30S R4W S 8 * C42 1994
	from which A maple, 11 ins. diam., bears S. 85½° E., 35½ lks. dist., mkd. X BT. An ash, 19 ins. diam., bears N. 26¼° W., 12 lks. dist., mkd. X BT. Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

**Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim Nos. 41, 42, 43, and 44,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>The corner is located N., 0.80 chs. dist. of the center of County Road No. 1 (Tiller Trail Highway), asphalt-surfaced, 40 lks. wide, bears N. 65° E. and S. 70° W.</p> <hr/> <p>N. 0° 19' 41" W., on the interior N. and S. line of Claim No. 42.</p> <p>Across South Umpqua River, course S. 65° W.</p>
2.00	Right bank of the South Umpqua River, bears N. 65° E. and S. 65° W.; asc. over SE. slope.
2.55	Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.
2.914	<p>Point for the exterior L cor. of Donation Land Claim No. 42, at proportionate dist., determined by the Grant Boundary Method between the reestablished SW. cor. of Donation Land Claim No. 42 and the reestablished NE. cor. of Donation Land Claim No. 42, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 46 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30S R4W S 8 YYY * C 42 1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cottonwood, 20 ins. diam., bears S. 66 3/4° E., 83 lks. dist., mkd. C42 BT.</p> <p style="padding-left: 40px;">A maple, 22 ins. diam., bears S. 8½° W., 77 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located at the S. edge of a hay field.</p> <hr/> <p>N. 89° 40' 19" E., on the most northerly N. bdy. of Claim No. 42.</p> <p>Across hay field.</p>
1.05	Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.; desc. over SE. slope.
1.95	Right bank of the South Umpqua River, bears N. 65° E. and S. 65° W., course S. 65° W.; across river.
6.45	Left bank of the South Umpqua River, bears N. 65° E. and S. 60° W.; asc. over NW. slope.
10.117	The NE. cor. of Donation Land Claim No. 42, on the W. bdy. of Donation Land Claim No. 43.

**Subdivision of Section 4,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0° 19' 40" E., on the N. and S. center line of sec. 4.</p> <p>Ascend over broken S. slope, through prune orchard.</p>
7.75	<p>Woven wire fence, 7 ft. high, extends N. 80° W. and S. 80° E.; leave prune orchard, continue ascending through light undergrowth.</p>
19.221	<p>Point for the center S 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S1/16 * S 4 C 1994</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears N. 74½° E., 194 lks. dist., mkd. CS1/16 S4 BT.</p> <p style="padding-left: 40px;">A madrone, 15 ins. diam., bears S. 51° E., 282 lks. dist., mkd. CS1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on the W. edge of an unimproved dirt road.</p> <p>Ascend over S. slope.</p>
38.442	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R4W C1/4 S 4 1994</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 25 ins. diam., bears S. 30½° E., 65 lks. dist., mkd. C1/4 S4 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 25¼° W., 52 lks. dist., mkd. C1/4 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the center 1/4 sec. cor. of sec. 4 by Fredrick E. Warner, Registered Professional Land Surveyor No. 298, in 1957, recorded in the Douglas County Surveyors Office file, CS 42/257, perpetuated by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded</p>

**Subdivision of Section 4,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>in the Douglas County Surveyors Office file, CS 51/19, bears S. 83° 13' 28" E., 0.230 chs. dist.; monumented with an iron pipe, 1 3/4 ins. diam., firmly set, projecting 10 ins. above ground, from which the remains of bearing trees mkd. by Warner:</p> <p style="padding-left: 40px;">A sawed fir stump, 20 ins. diam., bears N. 85½° E., 6 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 14½° E., 15½ lks. dist., with scribe marks 1/4 S4 RS298 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir snag, 8 ins. diam., bears S. 46° W., 9 lks. dist., with healed blaze visible on trunk alongside.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 24½° W., 14 lks. dist., with scribe marks C1/4 S4 RS298 BT visible on open blaze.</p> <p>This point was rejected due to improper control and not utilized in this survey.</p> <p>Ascend over S. slope.</p>
41.80	Ridge, bears S. 80° E. and S. 80° W.; desc. over broken W. slope.
57.884	<p>Point for the center N 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N1/16 * S 4 C 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 54½° E., 25 lks. dist., mkd. CN1/16 S4 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 49 3/4° E., 24 lks. dist., mkd. CN1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the center N 1/16 sec. cor. of sec. 4 by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office file, CS 51/19, bears S. 70° 57' 03" E., 0.172 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, from which the remains of bearing trees mkd. by Ramsey:</p> <p style="padding-left: 40px;">A decayed snag, bears N. 30¼° E., 39 lks. dist., with down and decayed trunk, 20 ins. diam., alongside, with scribe marks CN1/16 visible on open blaze.</p> <p style="padding-left: 40px;">A sawed cedar stump, 22 ins. diam., bears S. 10° E., 46½ lks. dist., with healed blaze visible on trunk alongside.</p>

**Subdivision of Section 4,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	Descend over NW. slope.
59.60	Ravine, drains W.; asc. over SW. slope.
72.10	Creek, 2 lks. wide, course S. 70° W.; asc. over broken SE. slope.
75.70	Spur, slopes W.; desc. over NW. slope.
77.00	Ravine, drains S. 30° W.; asc. over SE. slope.
85.60	Ridge, bears N. 50° E. and S. 50° W.; desc. over NW. slope.
91.646	The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp.
	<hr/>
	From the 1/4 sec. cor. of secs. 3 and 4.
	N. 88° 31' 54" W., on the E. and W. center line of sec. 4.
	Ascend over E. slope, through moderate timber and undergrowth.
5.80	Spur, slopes S.; desc. over SW. slope.
14.45	Ravine, drains S.; asc. over broken SE. slope.
20.046	Point for the center E 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.
	E1/16 C !!!!! C S 4 1994
	from which
	A fir, 7 ins. diam., bears S. 52° W., 29½ lks. dist., mkd. CE1/16 S4 BT.
	A pine, 5 ins. diam., bears N. 34° W., 46 lks. dist., mkd. X BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	The corner is located N. 12 ° W., 0.39 chs. dist. of a fence corner, with woven wire fence extending S. and barbed wire fence extending W.
	From this point, a point established as the center E 1/16 sec. cor. of sec. 4 by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office file, CS 51/19, bears S. 20° 48' 18" E., 0.320 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Ramsey:
	A sawed cedar stump, 15 ins. diam., bears N. 41° E., 25½ lks. dist., with healed blaze.

**Subdivision of Section 4,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 21 ins. diam., bears S. 33½° E., 27 lks. dist., with healed blaze.</p> <p>This point was rejected due to improper control and was not utilized in this survey.</p> <p>Ascend over broken SE. slope.</p>
29.10	Spur, slopes S.; desc. over broken SW. changing to NW. slope.
40.092	The center 1/4 sec. cor. of sec. 4.
79.131	The 1/4 sec. cor. of secs. 4 and 5.
	<hr/> <p>From the center E 1/16 sec. cor. of sec. 4.</p> <p>N. 0° 00' 07" W., on the N. and S. center line of the NE 1/4 of sec. 4.</p> <p>Ascend over SE. slope, through scattered timber and dense undergrowth.</p>
9.25	Ridge, bears N. 60° E. and S. 60° W.; desc. over NE. slope.
19.418	<p>Point for the NE 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the NE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE1/16 S 4 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 22° E., 6½ lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 69¼° E., 30 lks. dist., mkd. NE1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of and drive a steel fence post in the ground S., 0.03 chs. dist. of stainless steel post.</p> <p>From this point, a point established as the NE 1/16 sec. cor. of sec. 4 by Marvin C. Ramsey, Registered Professional Land Surveyor No. 404, in 1959, recorded in the Douglas County Surveyors Office file, CS 51/19, bears N. 48° 49' 40" E., 0.186 chs. dist.; monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, from which the remains of bearing trees mkd. by Ramsey:</p> <p style="padding-left: 40px;">A sawed cedar stump, 20 ins. diam., bears N. 83½° E., 42 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A sawed cedar stump, 26 ins. diam., bears N. 60 3/4° W., 39½ lks. dist., with healed double blaze.</p>

**Subdivision of Section 4,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	This point was rejected due to improper control and was not utilized in this survey.
	Descend over NE. slope.
20.40	Ravine, drains N. 60° W.; asc. over W. slope.
32.55	Gravelled road, 20 lks. wide, bears N. 85° W. and S. 85° E., and top of spur, slopes N. 85° W.; desc. over NW. slope.
41.90	Ravine, drains S. 65° W.; asc. over S. slope.
48.50	Spur, slopes S. 35° W.; desc. over NW. slope.
53.113	The E 1/16 sec. cor. of sec. 4 only, on the N. bdy. of the Tp.
	<hr/>
	From the N 1/16 sec. cor. of secs. 3 and 4.
	N. 88° 27' 15" W., on the E. and W. center line of the NE 1/4 of sec. 4.
	Ascend over SW. slope, through scattered timber and dense undergrowth.
9.65	Gravelled road, 20 lks. wide, bears N. 20° W. and S. 20° E., and top of ridge bearing same; desc. over broken W. slope.
19.933	The NE 1/16 sec. cor. of sec. 4.
	Descend over broken W. slope.
39.866	The center N 1/16 sec. cor. of sec. 4.
	<hr/>
	From the E 1/16 sec. cor. of secs. 4 and 9.
	N. 0° 18' 32" E., on the N. and S. center line of the SE 1/4 of sec. 4.
	Ascend over S. slope, through scattered timber and undergrowth.
19.240	Point for the SE 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the SE 1/4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	SE1/16 S 4 1994
	from which
	A cedar, 8 ins. diam., bears S. 47° W., 27½ lks. dist., mkd. SE1/16 S4 BT.
	A fir, 7 ins. diam., bears N. 47 3/4° W., 22½ lks. dist., mkd. SE1/16 S4 BT.

**Subdivision of Section 4,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located W., 0.26 chs. dist. of a fence corner, with barbed wire fences extending N. and W.</p> <p>Ascend over SE. slope.</p>
38.548	<p>The center E 1/16 sec. cor. of sec. 4.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 3 and 4.</p> <p>N. 88° 17' 08" W., on the E. and W. center line of the SE 1/4 of sec. 4.</p> <p>Descend over SW. slope, through moderate timber and undergrowth.</p>
4.40	<p>Ravine, drains S. 10° W.; asc. over SE. slope.</p>
8.35	<p>Spur, slopes S. 30° W.; desc. over SW. slope.</p>
17.05	<p>Ravine, drains S.; asc. over SE. slope.</p>
20.048	<p>The SE 1/16 sec. cor. of sec. 4.</p> <p>Ascend over SE. slope.</p>
23.20	<p>Spur, slopes S. 20° W.; desc. over broken SW. slope.</p>
40.103	<p>The center S 1/16 sec. cor. of sec. 4.</p> <hr/> <p style="text-align: center;">Subdivision of Section 5, T. 30 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8, perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1958, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 134, further perpetuated by Harold L. Ball, Registered Professional Engineer No. 6025, in 1975, recorded in the Douglas County Surveyors Office map file, M58-47; monumented with a steel fence post, firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Markham:</p> <p style="padding-left: 40px;">A root hole, bears N. 38° E., 12 lks. dist., with decayed fir trunk, size indeterminate, alongside, no marks visible.</p> <p style="padding-left: 40px;">A sawed madrone stump, 19 ins. diam., bears S. 30° E., 22½ lks. dist., with scribe marks BT visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 5,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	T30S R4W S 5 1/4 !!!!! S 8 1994
	and new bearing trees
	A cedar, 14 ins. diam., bears S. 7° W., 120 lks. dist., mkd. 1/4 S8 BT.
	A cedar, 18 ins. diam., bears N. 72¼° W., 101 lks. dist., mkd. 1/4 S5 BT.
	Deposit a white "DEEP-1" magnetic marker at base of and steel fence post alongside of stainless steel post.
	The corner is located at a fence corner, with woven wire fences extending N. and E.
	From this point, the cor. of secs. 4, 5, 8 and 9, bears N. 88° 45' 18" E., 40.440 chs. dist., hereinbefore described.
	N. 0° 36' 09" E., on the N. and S. center line of sec. 5.
	Descend over broken NE. slope, over grassy slope and scattered brush.
3.75	Ravine, drains N. 40° E.; asc. over broken SE. slope.
32.30	Spur, slopes S. 75° E.; desc. over NE. slope.
40.013	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.
	T30S R4W C1/4 S 5 1994
	from which
	A fir, 9 ins. diam., bears N. 76 3/4 E., 32½ lks. dist., mkd. C1/4 S5 BT.
	A fir, 28 ins. diam., bears N. 34° W., 36½ lks. dist., mkd. C1/4 S5 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	The corner is located N. 20° W., 0.36 chs. dist. of a fence corner, with woven wire fences extending S. and W.
	Descend over NE. slope.
43.40	Creek, 1 lk. wide, course S. 75° E.; asc. over broken S. slope.

**Subdivision of Section 5,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
59.45	Dirt road, 20 lks. wide, bears N. 30° W. and S. 40° E.
59.691	Point for the center N 1/16 sec. cor. of sec. 5. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;">C N1/16 * S 5 C 1994</div> from which <div style="margin-left: 40px;">A cedar, 16 ins. diam., bears S. 7½° E., 60 lks. dist., mkd. CN1/16 S5 BT.</div> <div style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 73½° W., 29 lks. dist., mkd. CN1/16 S5 BT.</div> Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Ascend over S. slope.
60.50	Spur, slopes S. 35° E.; desc. over broken NE. slope.
75.55	Creek, 2 lks. wide, course S. 35° E.; asc. over broken SW. slope.
93.410	The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp. <hr/>
	From the 1/4 sec. cor. of secs. 4 and 5. S. 89° 06' 27" W., on the E. and W. center line of sec. 5. Descend over broken NW. slope, through timber and moderate undergrowth.
9.30	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
10.45	Dirt road, 20 lks. wide, bears N. 15° E. and S. 15° W.
11.45	Creek (Stinger Gulch), 5 lks. wide, course S. 25° W.; over broken S. slope.
16.70	Creek, 5 lks. wide, course S. 25° E.; asc. over E. slope.
20.256	Point for the center E 1/16 sec. cor. of sec. 5. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">E1/16 C !!!!! C S 5 1994</div> from which

**Subdivision of Section 5,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 7 ins. diam., bears N. 74° W., 25 lks. dist., mkd. CE1/16 S5 BT.</p> <p>A fir, 9 ins. diam., bears N. 9¼° W., 9 lks. dist., mkd. CE1/16 S5 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p>
24.00	Spur, slopes S. 10° E.; desc. over SW. slope.
36.45	Creek, 5 lks. wide, course S. 25° E.; asc. over broken NE. slope.
40.512	The center 1/4 sec. cor. of sec. 5.
	Ascend over broken NE. slope.
53.40	Creek, 2 lks. wide, course N. 30° E.; asc. over broken E. slope.
60.496	Point for the center W 1/16 sec. cor. of sec. 5.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	W1/16 C !!!!! C S 5 1994
	from which
	<p>A fir, 13 ins. diam., bears N. 13° E., 11 lks. dist., mkd. CW1/16 S5 BT.</p> <p>A fir, 8 ins. diam., bears S. 48° E., 43 lks. dist., mkd. CW1/16 S5 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located S., 0.05 chs. dist. of a woven wire fence, extending E. and W.</p> <p>Ascend over broken E. slope.</p>
65.90	Dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E., and top of ridge bearing same; desc. over broken SW. slope.
78.60	Ravine, drains S. 40° W.; asc. over SE. slope.
80.480	The 1/4 sec. cor. of secs. 5 and 6.
	<hr/> <p>From the center E 1/16 sec. cor. of sec. 5.</p> <p>N. 0° 39' 59" E., on the N. and S. center line of the NE 1/4 of sec. 5.</p>

**Subdivision of Section 5,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	Descend over NE. slope, through heavy timber and moderate undergrowth.
9.95	Creek, 4 lks. wide, course S. 50° E.; asc. over SW. slope.
19.781	Point for the NE 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the NE 1/4. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. NE1/16 S 5 1994 from which A cedar, 13 ins. diam., bears N. 21° E., 10 lks. dist., mkd. NE1/16 S5 BT. A fir, 19 ins. diam., bears S. 84½° W., 37 lks. dist., mkd. NE1/16 S5 BT. Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Ascend over SW. slope.
50.30	Ravine, drains S. 25° W.; asc. over SW. slope.
53.457	The E 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp. <hr/> From the N 1/16 sec. cor. of secs. 4 and 5. S. 88° 49' 11" W., on the E. and W. center line of the NE 1/4 of sec. 5. Ascend over SE. slope, through heavy timber and moderate undergrowth.
2.20	Spur, slopes S.; desc. over broken SW. slope.
6.10	Ravine, drains S. 30° E.; asc. over broken E. slope.
10.55	Spur, slopes S. 15° E.; desc. over broken SW. slope.
20.278	The NE 1/16 sec. cor. of sec. 5.
25.35	Creek, 4 lks. wide, course S. 35° E.; asc. over broken NE. slope.
40.558	The center N 1/16 sec. cor. of sec. 5. <hr/> From the center W 1/16 sec. cor. of sec. 5. N. 0° 08' 52" E., on the N. and S. center line of the NW 1/4 of sec. 5. Ascend over broken SE. slope, through heavy timber and moderate undergrowth.

**Subdivision of Section 5,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
19.987	<p>Point for the NW 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the NW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW1/16 S 5 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 34° E., 60 lks. dist., mkd. NW1/16 S5 BT.</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears S. 72½° E., 17½ lks. dist., mkd. NW1/16 S5 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SE. slope.</p>
31.35	Ridge, bears NE. and SW.; desc. over broken NE. slope.
54.067	The W 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 5.</p> <p>S. 89° 59' 45" W., on the E. and W. center line of the NW 1/4 of sec. 5.</p> <p>Descend over broken SW. slope, through heavy timber and moderate undergrowth.</p>
5.85	Ravine, drains S. 15° E.; asc. over SE. slope.
12.30	Spur, slopes S.; desc. over broken SW. slope.
18.20	Ravine, drains S. 35° E.; asc. over broken SE. slope.
20.136	The NW 1/16 sec. cor. of sec. 5.
	Ascend over broken SE. slope.
27.40	Dirt road, 20 lks. wide, bears N. 30° E. and S. 25° W.
28.35	Ridge, bears N. 40° E. and S. 10° W.; desc. over broken NW. slope.
40.273	The N 1/16 sec. cor. of secs. 5 and 6.
	<hr/> <p style="text-align: center;">Subdivision of Section 17, T. 30 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N. 0° 13' 30" E., on the N. and S. center line of sec. 17.</p>

**Subdivision of Section 17,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Descend over broken NW. slope, through moderate timber and dense undergrowth.</p>
22.898	<p>Intersect the S. bdy. of Donation Land Claim No. 43, point for the crossing closing cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} C \\ \hline C * 43 \\ CCC * S 17 \\ \hline C \\ 1994 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears S. 19° E., 25½ lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 86° W., 63 lks. dist., mkd. S17 CCC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the SE. cor. of Donation Land Claim No. 43 bears N. 89° 32' 56" E., 0.634 chs. dist., hereinbefore described.</p> <p>Descend over broken NW. slope.</p>
37.217	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} T30S \quad R4W \\ C1/4 \quad S 17 \\ \hline 1994 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A power pole, 15 ins. diam., bears N. 46½° E., 110 lks. dist., PPL# 1 35 30-04 175460.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 75¼° E., 164 lks. dist., mkd. C1/4 S17 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NW. slope.</p>
37.40	Gravelled road, 15 lks. wide, bears N. 80° E. and S. 70° W.
37.55	Barbed wire fence, bears N. 75° E. and S. 75° W.
76.652	The 1/4 sec. cor. of secs. 8 and 17.

**Subdivision of Section 17,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

From the 1/4 sec. cor. of secs. 16 and 17, reestablished by proportionate measurement by James W. Byron, Deputy County Surveyor, in 1955, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 132, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 230, and is accepted as a careful and faithful determination of the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T30S R4W
1/4 S
17 * 16
1955

from which the remains of bearing trees mkd. by Byron in 1955

A root hole, bears N. 65¼° E., 61 lks. dist., with fir trunk, 12 ins. diam. alongside, with scribe marks 1/4 S16 CS BT visible on open double blaze.

A fir snag, 11 ins. diam., bears S. 38° W., 68 lks. dist., with healed double blaze.

and a bearing tree mkd by Byron in 1963

An oak, 11 ins. diam., bears N. 2° E., 70 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 8 ins. diam., bears N. 84° E., 31½ lks. dist., mkd. 1/4 S16 BT.

The corner is located in an abandoned dirt road, 20 lks. wide, bears N. 15° E. and S. 15° W., and E., 0.09 chs. dist. of a woven wire fence, extending N. and S.

From this point, the cor. of secs. 8, 9, 16 and 17, bears N. 1° 39' 40" E., 38.769 chs. dist., hereinbefore described.

From this same point, a point established as the N 1/16 sec. cor. of secs. 16 and 17 by James W. Byron, Deputy County Surveyor, in 1959, recorded in the Douglas County Surveyors Office map file, RM1-28, bears N. 1° 39' 02" E., 19.381 chs. dist.; monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Byron:

A fir, 27 ins. diam., bears S. 3¼° W., 53 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 16° W., 82 lks. dist., with healed blaze.

From this same point, the cor. of secs. 16, 17, 20 and 21, bears S. 1° 39' 59" W., 37.606 chs. dist., hereinbefore described.

**Subdivision of Section 17,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	S. 88° 37' 18" W., on the E. and W. center line of sec. 17.
	Descend over broken W. slope, through scattered timber and moderate undergrowth.
13.90	Dirt road, 20 lks. wide, bears N. 40° W. and S. 40° E.
19.742	Point for the center E 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	E1/16 C !!!!!--- C S 17 1994
	from which
	An alder, 14 ins. diam., bears S. 23° E., 202 lks. dist., mkd. CE1/16 S17 BT.
	An oak, 10 ins. diam., bears N. 88 3/4° W., 345 lks. dist., mkd. CE1/16 S17 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over broken W. slope.
27.15	Dirt road, 20 lks. wide, bears N. 15° W. and S. 35° E.
28.10	Creek, 5 lks. wide, course N. 25° W.; continue descending over gentle broken NW. slope.
39.484	The center 1/4 sec. cor. of sec. 17.
	Descend over gentle broken NW. slope.
39.95	Gravelled road, 15 lks. wide, bears N. 80° E. and S. 70° W.
40.90	Barbed wire fence, bears N. 75° E. and S. 75° W.
59.602	Point for the center W 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 38 ins. in the ground, with brass cap mkd.
	W1/16 C !!!!! C S 17 1994
	from which
	A fir, 13 ins. diam., bears N. 89° E., 182 lks. dist., mkd. CW1/16 S17 BT.
	An oak, 36 ins. diam., bears S. 15° E., 134 lks. dist., mkd. CW1/16 S17 BT.

**Subdivision of Section 17,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on the W. edge of a dirt road, 20 lks. wide, bears N. and S. 30° W., and S. 30° W., 0.79 chs. dist. of a fence corner, with barbed wire fences extending N. and S. and woven wire fence extending S. 70° W.</p> <p>Descend over gentle NW. slope.</p>
79.720	<p>The 1/4 sec. cor. of secs. 17 and 18.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0° 56' 44" E., on the N. and S. center line of the SE 1/4 of sec. 17.</p> <p>Ascend over broken SE. slope, through heavy timber and undergrowth.</p>
3.55	<p>Spur, slopes N. 35° E.; desc. over broken NE. slope.</p>
33.157	<p>Intersect the S. bdy. of Donation Land Claim No. 44, point for the crossing closing cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E C * 44 --- CCC * S 17 E 1994</p> </div> <p>from which</p> <p style="padding-left: 40px;">An apple, 6 ins. diam., bears N. 34° E., 114 lks. dist., mkd. C44 CCC BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 80 3/4° E., 94 lks. dist., mkd. S17 CCC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the SE. cor. of Donation Land Claim No. 44 bears N. 89° 55' 32" E., 0.960 chs. dist., hereinbefore described.</p> <p>The corner is located N., 0.07 chs. dist. of a woven wire fence, extending E. and W.</p> <p>Descend over NE. slope.</p>
35.80	<p>Creek, 5 lks. wide, course N. 75° W.; asc. over SW. slope.</p>
36.15	<p>Dirt road, 20 lks. wide, bears N. 60° W. and S. 60° E.</p>
37.412	<p>The center E 1/16 sec. cor. of sec. 17.</p>

**Subdivision of Section 17,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	<hr/> <p>From the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0° 18' 40" E., on the N. and S. center line of the SW 1/4 of sec. 17.</p> <p>Descend over broken NW. slope, through moderate timber and undergrowth.</p>					
16.505	<p>Intersect the S. bdy. of Donation Land Claim No. 42, point for the crossing closing cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>W</td></tr> <tr><td>C * 42</td></tr> <tr><td>CCC * S 17</td></tr> <tr><td>W</td></tr> <tr><td>1994</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 3 3/4° E., 46 lks. dist., mkd. S17 CCC BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 81 3/4° W., 52 lks. dist., mkd. C42 CCC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the SE. cor. of Donation Land Claim No. 42 bears N. 89° 32' 56" E., 0.625 chs. dist., hereinbefore described.</p> <p>Descend over broken N. slope.</p>	W	C * 42	CCC * S 17	W	1994
W						
C * 42						
CCC * S 17						
W						
1994						
38.661	<p>The center W 1/16 sec. cor. of sec. 17.</p> <hr/> <p style="text-align: center;">Subdivision of Section 21, T. 30 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28, perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1952, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 94, further perpetuated by William J. Ruppert, Registered Professional Land Surveyor No. 866, in 1980, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 4 W., No. 276; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground (alongside of which is a steel fence post, firmly set, projecting 4 ft. above ground), from which a bearing tree mkd. by Markham:</p> <p style="padding-left: 40px;">An oak, 23 ins. diam., bears N. 67¼° W., 164 lks. dist., with healed blaze.</p>					

**Subdivision of Section 21,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	and a reference monument set by Ruppert
	A steel fence post, firmly set, projecting 3½ ft. above ground, bears S. 81¼° E., 23½ lks. dist.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.
	T30S R4W S 21 1/4 !!!!! S 28 1995
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Reset the steel fence post, N. 45° E., 5 lks. dist. from corner.
	N. 0° 24' 45" E., on the N. and S. center line of sec. 21.
	Ascend over broken S. slope, through dense undergrowth.
7.95	Spur, slopes S. 5° E.; asc. over broken E. slope.
17.40	Spur slopes N. 80° E.; desc. over broken E. slope.
34.45	Dirt road, 25 lks. wide, bears N. 50° W. and S. 15° E.
40.111	Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T30S R4W C1/4 S 21 1994
	from which
	A fir, 16 ins. diam., bears S. 18° E., 46 lks. dist., mkd. C1/4 S21 BT.
	A fir, 11 ins. diam., bears S. 85½° W., 57 lks. dist., mkd. C1/4 S21 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over broken E. slope.
40.95	Ravine, drains S. 75° E.; asc. over broken SE. slope.
45.85	Spur, slopes S. 45° E.; continue ascending over E. slope.
59.35	Spur, slopes E.; desc. over NE. slope.

**Subdivision of Section 21,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
60.589	<p>Point for the center N 1/16 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N1/16 * S 21 C 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 30¼° W., 26½ lks. dist., mkd. CN1/16 S21 BT.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 46½° W., 31½ lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NE. slope, through second growth timber and dense undergrowth.</p>
64.10	Ravine, drains N. 60° E.; asc. over SE. slope.
70.00	Spur, slopes N. 55° E.; desc. over N. slope.
81.067	The 1/4 sec. cor. of secs. 16 and 21.
	<hr/> <p>From the true point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>N. 88° 06' 59" W., on the E. and W. center line of sec. 21.</p> <p>Across the South Umpqua River.</p>
2.35	Left bank of the South Umpqua River, bears N. 70° W. and S. 70° E., course N. 70° W.; over nearly level ground.
19.617	<p>The center E 1/16 sec. cor. of sec. 21, established by Romanso E. Ware, Registered Professional Land Surveyor No. 1005, in 1981, recorded in the Douglas County Surveyors Office map file, M89-17, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, from which bearing trees mkd. by Ware:</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears S. 80¼° E., 69½ lks. dist., with scribe marks CE1/16 S21 visible on open double blaze.</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears S. 30 3/4° E., 64½ lks. dist., with scribe marks CE1/16 S21 visible on open double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.</p>

**Subdivision of Section 21,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	E1/16 C !!!!!--- C S 21 1993
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. <hr style="width: 20%; margin: 10px auto;"/>
	N. 88° 07' 22" W., beginning new measurement.
	Over nearly level ground, through dense undergrowth.
3.70	Bears Creek, 10 lks. wide, course N. 10° E.; asc. over E. slope.
5.15	County Road No. 94 (Shively Creek Road), asphalt-surfaced, 40 lks. wide, bears N. 15° E. and S. 10° W.
17.25	Ravine, drains S. 75° E.; continue ascending over E. slope.
19.607	The center 1/4 sec. cor. of sec. 21. Ascend over E. slope.
38.20	Dirt road, 20 lks. wide, bears N. 20° E. and S. 40° W.
39.331	From this point, a point established by person(s) unknown, bears North, 0.012 chs. dist., monumented with a square top axle, 1 in. diam., firmly set, projecting 4 ins. above ground.
40.15	Dirt road, 20 lks. wide, bears N. 30° W. and S. 50° E.
50.70	Spur, slopes S. 20° E.; desc. over broken S. slope.
60.444	The 1/4 sec. cor. of secs. 20 and 21. <hr style="width: 20%; margin: 10px auto;"/>
	From the center E 1/16 sec. cor. of sec. 21.
	N. 0° 58' 53" E., on the N. and S. center line of the NE 1/4 of sec. 21.
	Across nearly level ground, through moderate undergrowth.
3.10	Left bank of the South Umpqua River, bears N. 60° W. and S. 60° E., course N.; across river.
5.10	Left bank of the South Umpqua River, bears N. 50° E. and S. 50° W.; asc. gradually over nearly level ground.
10.10	County Road No. 94 (Shively Creek Road), asphalt-surfaced, 40 lks. wide, bears N. 5° E. and S. 15° W.
15.95	County Road No. 94 (Shively Creek Road), asphalt-surfaced, 40 lks. wide, bears N. 15° E. and S. 20° E.
18.30	Left bank of the South Umpqua River, bears N. 30° W. and S. 30° E., course N. 30° W.; across river.

**Subdivision of Section 21,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
20.023	True point for the NE 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the NE 1/4 of sec. 21, not monumented, falls in the South Umpqua River.
20.95	Right bank of the South Umpqua River, bears N. 30° W. and S. 30° E.; over nearly level ground.
40.044	The E 1/16 sec. cor. of secs. 16 and 21.
	<hr/> <p>From the point for the N 1/16 sec. cor. of secs. 21 and 22.</p> <p>N. 86° 49' 14" W., on the E. and W. center line of the NE 1/4 of sec. 21.</p> <p>Across level ground.</p>
18.970	Point selected for the witness cor. to the NE 1/16 sec. cor. of sec. 21.
	Set a brass tablet, 3½ ins. diam., with a 3½ in. stem cemented in a drill hole in solid rock, with brass cap mkd.
	<p>W C NE1/16 S 21 <----- 52.8 FT. 1993</p>
	from which
	A fir, 28 ins. diam., bears N. 4¼° E., 312 lks. dist., mkd. X BT.
	A rock face, 3 ft. high and 4 ft. wide, bears S. 40½° E., 39 lks. dist., mkd. X BO.
19.20	Right bank of the South Umpqua River, bears N. 20° W. and S. 20° E., course N. 20° W.; across river.
19.770	True point for the NE 1/16 sec. cor. of sec. 21, not monumented, falls in the South Umpqua River.
21.10	Left bank of the South Umpqua River, bears N. 20° W. and S. 30° E.; asc. over E. slope.
22.25	County Road No. 94 (Shively Creek Road), asphalt-surfaced, 40 lks. wide, bears N. 40° W. and S. 40° E.
39.591	The center N 1/16 sec. cor. of sec. 21.
	<hr/> <p>N. 88° 34' 22" W., on the E. and W. centerline of the NW 1/4 of sec. 21.</p> <p>Ascend over broken NE. slope, through second growth timber and dense undergrowth.</p>
32.35	Ridge, bears N. 10° E. and S. 10° W.; desc. over NW. slope.

**Subdivision of Section 21,
T. 30 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
40.369	The N 1/16 sec. cor. of secs. 20 and 21.
	GENERAL DESCRIPTION
	<p>The lands included in the foregoing resurvey are located in Douglas County near the community of Days Creek, Oregon. Access to the area is gained via Interstate 5, County Road Nos. 1, 34, 42, 92 and 94, with other gravelled and dirt roads branching from them into the areas.</p> <p>The elevation ranges from approximately 750 feet above sea level near the South Umpqua River in Donation Land Claim No. 42, to about 2000 feet above sea level in the NW 1/4 of section 21. The terrain varies from level bottom ground to mountainous. The soil consists of a rocky clay in the upper elevations to a sandy loam in the lower elevations.</p> <p>The area is drained by the South Umpqua River, Stinger Gulch, Beals Creek, Wood Creek, Days Creek and numerous other small and seasonal drainages.</p> <p>The timber consists of fir, cedar, hemlock, alder, maple, oak, chinquapin, pine, ash, yew and madrone. The undergrowth is mainly salal, Oregon grape, manzanita, arrowwood, poison oak, vine maple and young timber.</p> <p>There were no mineral deposits noted along the lines surveyed.</p> <p>The mean magnetic declination, as shown on the United States Geological Survey 7½ minute quadrangle map "DAYS CREEK, OREGON," provisional edition, published in 1986, is 18½° East.</p>