

County Surveyor's Record, Douglas County, Oregon

T. 30 S., R. 4 W.

705

CHAINS

CLAIM NO. 44

Resurvey of Joel Thorn's Land Claim No. 44, T. 30 S., R. 4 W., in secs. 8 and 9 and 17, Notification No. 125.

Beginning at the SE cor. of said Claim, the post of which set originally is gone, but replaced by one set by the Co. Surveyor, its witness tree, a Bl. oak, 8 ins. in diam. N 80° E is standing, but the marks have been chopped out. I prove this corner also by running North 30 lks. from exterior or SW. corner of Claim No. 47; I set a basalt stone 16 x 8 x 8 ins. in mound of stone, (impracticable to dig.) marked 44 on NW. face, from which

A Wh. oak, 16 ins. in diam. bears N 73 1/2° W, 104 lks dist. marked T 30 S R 4 W C. 44 B.T. Thence

West on South boundary of Claim No. 44.

Var. 19° E.

Gravelly high land, 15 ft. above river.

2.00 Road to Canyonville, course N 80° W.

2.75 Enter enclosure prairie with scattering oaks and pines.

41.00 Enter grainfield.

56.52 Intersected sec. line betw. secs. 8 and 9 20.50 chns N. of the SW. cor. of sec. 9.

77.00 Cornfield, interior angle corner. The post set for this corner is gone. I restore this cor. by setting a fir post 4 1/2 ft. long 4 ins. square, 24 ins. in the ground, marked T 30 S. R 4 W. C. 44 on NW. face, raised a mound of stone alongside. (I proved this cor. by running W. 20.00 chns to the line bet. Claims No. 44 and 43.)

J. Weaver's house bears S 2 1/2° E.

Champan's house bears S 35° W.

P. Weaver's barn bears S 83° W.

Thence, South along East boundary of Claim No. 44.

Var. 18° 25' E.

Level prairie, cornfield.

20.33 Intersected sec. line between secs. 8 and 17, 20 chns West of sec. cor.

23.00 Leave level, begin ascent.

25.00 Weaver's house bears East, 1.20 chns.

44.00 Leave benchland, begin ascent of hill.

55.00 Top of rise, begin descent, Va. 18° 55' E.

60.90 A branch, course NW. 5 lks. wide, begin ascent.

63.08 The exterior or a SE. corner, The post set for this cor. is gone, but the witness tree is standing. I restore this corner by setting a fir post 4 1/2 ft. long, 4 ins. square, 24 ins. in the ground, marked T 30 S R 4 W C. 44 on NW. face, from which