

# County Surveyor's Record, Douglas County, Oregon

T 30 S, R 4 W

707

**CHAINS**

Claim No. 44 cont.

71.50      Offset South 5.60 chns, regained true line at the right bank of river, enter low bottom.

Var. 19° 5' E.

72.50      Wagon road, course E & W.

75.00      Enter grainfield.

97.33      The NE corner. As the post set for this corner is gone, and cultivation has obliterated any marks on the ground, I went to the NE cor. of Claim No. 46 and run South to the SE. corner of Claim No. 44. I found the distance to be 75.23 chns instead of 77.57 chns. therefore Cl. 44 will lose its proportion of difference (234 lks.) namely 61 lks. At the point 1939 lks. N. from SE cor., I restore this corner by setting a basalt stone 18 x 10 x 8 ins. marked 44 on S. W. face, 12 ins. in the ground, and raised a mound of stone alongside.                      Thence

South bet. Claims No. 44 and No. 47.

Var. 18° 40' E.

Level prairie.

2.00      Begin ascent of West end of hill.

5.00      Top of rise, enter oak openings, begin descent.

13.96      Right bank of S. Umpqua river, course N.W. Set flagg South at SE. corner, run base East 260 lks. flagg bears S 25° 36' W., making 5.43 chns across.

19.39      SE corner and place of beginning, Left bank of S. Umpqua River.

June 12th, 1889