

# County Surveyor's Record, Douglas County, Oregon

T 30 S., R 4 W

711

CHAINS

CLAIM NO. 47

Resurvey of George T. Day's Land Claim No. 47. T. 30 S. R. 4 W. in secs. 3, 4, 9, 10 and 15. Notification No. 139.

Begin at the Exterior angle or SW. corner of said claim. Here I found a post, set probably by the Co. Surveyor, standing, but it is slightly out of true place. As the bearing tree is standing I restore this corner by setting a fir post 4 1/2 ft. long, 4 ins. square, 24 ins. in a mound of stone, marked T 30 S. R 4 W C. 47 on the NE. face, from which

A Wh. oak 9 ins. in diam. bears N 80° E, 92 lks. dist., marked T 30 S. R 4 W C.47 BT. This is the old bearing tree, whose marks being dim, I renew. Thence

East on South boundary of Claim No. 47.

Var. 19° E.

On traverse, as the line falls into and follows up the river.

S 53 1/3° E. 7.00 chns to bridge; N 19 3/4° E, 6.20 chns cross on bridge, making a northing of 168 lks. and easting of 773 lks., offset South 1.68 chns regained true line.

- |       |   |
|-------|---|
| 7.73  | Right bank of S. Umpqua river, course N 60° W., begin ascent, enter oak openings.   |
| 21.97 | Intersected sec. line bet. secs. 9 and 10. 1811 lks. South of 1/4 sec. post.  |
| 24.00 | Interior angle corner. The post set for this corner is gone but the bearing tree is standing; I restore this corner by setting a Wh. oak post 4 1/2 ft. long, 4 ins. square, 24 ins. in the ground, marked T 30 S. R. 4 W. C.47 on NE face, from which<br><br>A Wh. oak, 18 ins. in diam. bears S 21 1/2° E 102 lks. dist., marked T 30 S. R 4 W. C.47 BT. This is the old bearing tree, whose marks being dim, I renew.<br><br>Thence South on west boundary of Claim No. 47.<br><br>Var. 18° 50' E. |
| 2.75  | Days Creek, 35 lks wide, course W.  |
| 7.50  | Enter enclosure.  |
| 11.00 | Leave oak openings, enter a garden.   |
| 14.50 | Leave garden, a low bottom.   |
| 19.50 | Right bank of S. Umpqua River, course N 20° W., make offset East of 3.30 chns.  |
| 21.24 | Intersect secs. line bet. secs. 10 and 15, 294 lks. East of witness corner to secs. 10 and 15. which stands 278 lks. E. of true corner, therefore 278+294-330, gives 242 lks. for intersection of claim and section line.   |
| 28.00 | Exterior or SW. corner. As the true corner is in the river, at a point 3.30 chns East of true corner, I set a basalt stone 24 x 8 x 4 ins. marked 47 W.C. on NE face in a mound of stote, from which  |