

County Surveyor's Record, Douglas County, Oregon

16819

Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claims, No. 48, and No. 49,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Josiah A. Burnett,
U. S. Deputy Surveyor, in 1857
and the resurvey by William Thiel,
U. S. Deputy Surveyor, in 1889)

From the SW. cor. of Donation Land Claim No. 49, on the
E. bdy. of Donation Land Claim No. 48, perpetuated by J.
W. Cole, County Surveyor, in 1924, from original evidence
no longer in existence, and further perpetuated and re-
corded by James W. Byron, Deputy County Surveyor, in 1954,
and still further perpetuated and recorded by Gregory
Quibell, Deputy County Surveyor, in 1981, monumented with
an iron bolt, 1 in. diam., firmly set flush with asphalt
surface of county road, from which the remains of a
bearing tree mkd. by Byron:

A root hole, bears N. 88° E., 37 lks. dist., with
a down oak alongside, 8 ins. diam., no marks
visible.

and bearing trees mkd. by Quibell

A white oak, 42 ins. diam, bears N. 30 3/4° E., 133
lks. dist., with scribe marks SW CL 49 CS BT
visible on open double blaze.

A white oak, 5 ins. diam., bears S. 64° E., 28 1/2
lks. dist., with scribe marks SW CL 49 CS BT
visible on open blaze.

and reference monuments

An iron post, 28 ins. long, 2 1/2 ins. diam.. set 24
ins. in the ground, for a reference monument
bears N. 53 1/4° E., 35 lks. dist., with brass cap
mkd. C 49 RM 1981 and an arrow pointing to the
corner.

An iron post, 28 ins. long, 2 1/2 ins. diam. set 24
ins. in the ground, for a reference monument,
bears S. 44° E., 34 lks. dist., with brass cap
mkd. T30S R4W S10 1981 and an arrow pointing to
the corner.

Corner is located on E. edge of Days Creek Road, 30 lks.
wide, bears N. 5° E. and S. 15° W.

N. 0° 08' W., on the E. bdy. of Claim No. 48, marking
the true line.

Descend 20 ft. over NE. slope, along Days Creek Road.

4.25 Leave Days Creek Road, bears N. 30° E. and S. 5° W.

13.45 Days Creek, 8 lks. wide, course W.; asc. 35 ft. over SE.
slope, through grain field along woven wire fence.

27.02 Intersect the line bet. secs. 3 and 10.

From this point, the E 1/16 sec. cor. of secs. 3 and 10,
bears N. 88° 01' W., 3.57 chs. dist., hereinbefore
described.

27.57 Point for the NE cor. of Donation Land Claim No. 48, at
proportionate distance; there is no remaining evidence
of the original corner.