

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 20 S., R. 12 W.

CHAINS

12°30', distance 8.98.

61.73 Resumed chaining.

63.00 Hill too steep & brushy to be chained, Base W. 140 lks.;
angle opposite 10°30', distance over 7.57.

70.57 To object.

72.70 To bank of Tsiltcoos Lake. Set meander post; from which
A spruce, 40 in. dia., bears N.1°E., 238 lks. dist.
An alder, 12 in. dia., bears N.40°W., 4 lks. dist.
Base S.13°W. 750; thence West 950. Object on S. bank of
lake bears S.27½°E., 28.76 distance over.

80.00 Corner of secs. 1, 6, 7 & 12 is in lake.

South on E. boundary of Sec. 12.

21.46 Set meander post; from which

A spruce, 10 in. dia., bears S.61°W., 42 lks. dist.

An alder, 8 in. dia., bears S.76°E., 88 lks. dist.

27.50 Top of hill.

32.50 Stream, 2 lks. wide, course W.

40.00 Set gr. sec. post; from which

A vine maple, 4 in. dia., bears N.82°E., 10 lks. dist.

A fir, 30 in. dia., bears N.38°W., 65 lks. dist.

It is impracticable to run this line further because of
a high mountain ridge.

Resumed the survey of exterior lines at the corner of
Townships 21 & 22 S., of Ranges 12 & 13 West, on the
Coast Meridian.

October 5th, 1857.

Subdivisions of T. 20 S., R. 12 W.
Survey by Harvey Gordon under Contract No. 69 dated
Feb. 2nd, 1857.

North between secs. 35 & 36.

1.50 Ridge, course E. & W.

4.50 Stream, 2 lks. wide, course W.

15.00 Ridge, course E. & W.

26.00 Stream, 2 lks. wide, course W.