

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 12 W.

CHAINS 55.00	To bank of lake Tahkenitch. An alder, 8 in. dia. is meander corner; from which A fir, 24 in. dia., bears N.58°E., 18 lks. dist. Alder, 12 in. dia., bears S.24°E., 28 lks. dist. Regained line across. Base North 2.00; angle opposite 10°15', dist. 11.03.
66.03	Meander corner. Set post; from which An alder, 15 in. dia., bears S.5°E., 110 lks. dist. An alder, 18 in. dia., bears North, 9 lks. dist.
69.00	Ridge, course South.
78.77	To meander post on lake; from which A spruce, 36 in. dia., bears N.82°E., 25 lks. dist. Alder, 6 in. dia., bears S.80°E., 15 lks. dist.
80.00	To Sec. corner in lake.

December 3rd, 1857.

	North between secs. 25 & 26.
6.05	Leave lake Tahkenitch. A fir, 30 in. dia. is meander corner; from which A willow, 8 in. dia., bears S.57°E., 12 lks. dist. Offset E. 1.20 to avoid swamp.
15.00	Return to line; leave swamp.
17.25	Stream, 6 lks. wide, course W.; foot of hill. Begin to ascend.
28.50	Stream, 4 lks. wide, course SW.
40.00	Set qr. sec. post; from which An alder, 12 in. dia., bears S.59°E., 10 lks. dist. An alder, 9 in. dia., bears N.47°W., 9 lks. dist.
42.50	Ridge, course SW.
51.00	Stream, 3 lks. wide, course W.
63.50	Stream, 2 lks. wide, course W.
80.00	A hemlock, 12 in. dia. is corner of secs. 25, 24, 25 & 26; from which A spruce, 36 in. dia., bears N.55°W., 13 lks. dist. A spruce, 30 in. dia., bears S.30°W., 10 lks. dist.