

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 12 W.

CHAINS

- 42.55 To Lake. Set post; from which
 An alder, 8 in. dia., bears N.57°W., 32 lks. dist.
 An alder, 6 in. dia., bears S.73°E., 34 lks. dist.
- 43.00 Set flag; regained line across: Base S.32½°E., 6.20;
 angle opposite 10½°, distance 31.56.
- 74.56 Set meander post; from which
 An alder, 18 in. dia., bears N.54°W., 33 lks. dist.
 A spruce, 30 in. dia., bears S.18°E., 34 lks. dist.
- 79.02 To sec. corner.
-
- North between secs. 26 & 27.
- 2.40 To lake. Set post; from which
 A spruce, 48 in. dia., bears N.55°W., 17 lks. dist.
 A spruce, 5 in. dia., bears S.37°E., 10 lks. dist.
 Base S.66½°W., 6.00, West 20 lks.; angle opposite 13½°,
 distance over 21.82.
- 24.22 Set meander post; from which
 A spruce, 10 in. dia., bears N.60°W., 22 lks. dist.
 A spruce, 24 in. dia., bears N.80°E., 18 lks. dist.
- 37.00 Ridge, course E. & W.
- 40.00 Set gr. sec. post; from which
 A spruce, 24 in. dia., bears S.21°E., 43 lks. dist.
 A spruce, 48 in. dia., bears N.6½°W., 38 lks. dist.
- 47.60 To lake. Alder, 4 in. dia. is meander corner; from
 which
 An alder, 5 in. dia., bears S.25°W., 14 lks. dist.
 An alder, 10 in. dia., bears N.68°E., 28 lks. dist.
 Base N.65°W., 180; angle opposite 12½°, distance 813.
- 55.73 Set post; from which
 A spruce, 24 in. dia., bears S.60°W., 3 lks. dist.
 A spruce, 10 in. dia., bears S.35°E., 16 lks. dist.
- 69.00 To lake. Set post; from which
 A spruce, 60 in. dia., bears N.45°E., 6 lks. dist.
 A spruce, 8 in. dia., bears S.55°W., 60 lks. dist.