

Subdivisions of T. 20 S., R. 12 W.

CHAINS

A fir, 30 in. dia., bears N.3°W., 78 lks. dist.  
 A fir, 30 in. dia., bears N.4°E., 67 lks. dist.

South between secs. 23 & 24.

Var. 20°E.

16.50 Stream, 2 lks. wide, course W.

21.50 Set witness gr. sec. corner; from which

An alder, 12 in. dia., bears N.10°E., 80 lks. dist.

A spruce, 100 in. dia., bears S.3°W., 27 lks. dist.

Bottom of ravine beyond which it is impracticable to survey.

East, on true line, between secs. 13 & 24.

3.50 High ridge, course SE., beyond which the ravines are impassable.

Set post; from which

Alder, 5 in. dia., bears N.88°E., 12 lks. dist.

Alder, 6 in. dia., bears S.19°W., 10 lks. dist.

North between secs. 13 & 14.

4.00 Ridge, course NW., beyond which it is impracticable to survey.

Set post; from which

An alder, 5 in. dia., bears N.61°E., 26 lks. dist.

An alder, 4 in. dia., bears N.51°W., 13 lks. dist.

December 7th, 1857.

North between secs. 14 & 15.

9.00 Leave lake. A fir, 24 in. dia. is meander corner; from which

A spruce, 40 in. dia., bears West, 5 lks. dist.

12.20 To lake. Set post; from which

A spruce, 24 in. dia., bears S.8°W., 15 lks. dist.

A fir, 24 in. dia., bears N.77°E., 38 lks. dist.

Base E. 40 lks.; angle opposite 5½°, dist. over 438.