

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 12 W.

CHAINS	<p>A hemlock, 5 in. dia., bears S.2°E., 42 lks. dist.  A spruce, 24 in. dia., bears N.53°E., 28 lks. dist.</p>
62.00	Slough, 200 lks. wide, course N.
68.00	Stream, 2 lks. wide, course W.
80.00	Bank of lake. Set post corner of Secs. 1, 2, 11 & 12; from which A spruce, 30 in. dia., bears N.50°W., 12 lks. dist. A spruce, 72 in. dia., bears S.45°E., 29 lks. dist. Alder, 12 in. dia., bears N.60°E., 38 lks. dist. Spruce, 8 in. dia., bears S.83°W., 60 lks. dist. Dec. 9, 1857.
	East, on random, between secs. 1 & 12.
40.00	Set temporary qr. sec. post.
80.00	Thence North 3.40 " East 1.46 to bank of lake. " N.13°E., 7.50 to witness corner on township line; hence
83.15	Intersect South 340 lks. from sec. corner. S.87°39'W., on true line, between secs. 1 & 12.
1.68	Leave lake. Set post; from which A fir, 36 in. dia., bears S.19°W., 21 lks. dist. A fir, 36 in. dia., bears N.13°E., 47 lks. dist.
12.50	Top of mountain, course N. & S.
15.63	To Lake Tsiltcoos. Set post; from which An alder, 4 in. dia., bears N.52°W., 14 lks. dist. A fir, 20 in. dia., bears S.14°E., 27 lks. dist. In line across. Base South 1.90; angle opposite 7°30', distance over 14.35.
29.98	Set meander post; from which An alder, 18 in. dia., bears N.86°W., 32 lks. dist. An alder, 18 in. dia., bears S.38°E., 38 lks. dist.
41.57	Set qr. sec. post; from which A spruce, 36 in. dia., bears N.45°W., 2 lks. dist. A spruce, 24 in. dia., bears S.50°E., 6 lks. dist.
61.50	Enter slough, course North.