

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 12 W.

CHAINS

An alder, 5 in. dia., bears S.15°E., 10 lks. dist.  
 A hemlock, 8 in. dia., bears N.25°W., 5 lks. dist.  
 39.93 Set qr. sec. post; from which  
 A spruce, 15 in. dia., bears N.2½°W., 56 lks. dist.  
 A spruce, 18 in. dia., bears S.38°E., 52 lks. dist.  
 43.50 Ridge, course NW.  
 52.50 Stream, 2 lks. wide, course NW.  
 56.00 Stream, 2 lks. wide, course NW.  
 63.50 Stream, 2 lks. wide, course NW.  
 75.00 Ridge, course N.  
 77.50 Stream, 2 lks. wide, course N.  
 79.85 To sec. corner.

December 14th, 1857.

North between secs. 27 & 28.

14.25 To Lake Tahkenitch. Set post; from which  
 A spruce, 36 in. dia., bears S.28°E., 54 lks.  
 A spruce, 24 in. dia., bears N.24°W., 40 lks. dist.  
 Base E. 11.23; angle opposite 11°, 57.77 distance over.  
 40.00 Qr. sec. corner is in lake.  
 72.02 Leave lake. Alder, 4 in. dia. is corner; from which  
 An alder, 6 in. dia., bears N.67°E., 15 lks. dist.  
 An alder, 10 in. dia., bears S.65°W., 20 lks. dist.  
 80.00 Set post corner of secs. 21, 22, 27 & 28; from which  
 A spruce, 6 in. dia., bears N.35°E., 30 lks. dist.  
 A spruce, 8 in. dia., bears S.20°E., 70 lks. dist.  
 Alder, 6 in. dia., bears S.23°W., 25 lks. dist.  
 V. maple, N.67°W., 44 lks. dist.

East, on random, between secs. 22 & 27.

Var. 20°E.

40.00 Set temporary qr. sec. post.  
 79.00 Intersected N. 47 lks. from meander post and N. 110 from  
 sec. corner in lake.  
 N.89°13'W., on true line, between secs. 22 & 27.