

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 12 W.

CHAINS	North, on random, between secs. 4 & 5.
40.00	Set temporary qr. sec. post.
80.25	Intersect E. 123 lks. from sec. corner. S.0°53'E., on true line, between secs. 4 & 5.
40.25	Set qr. sec. post; from which A pine, 8 in. dia., bears S.17 $\frac{1}{4}$ °E., 734 lks. dist. A pine, 18 in. dia., bears S.2 $\frac{3}{4}$ °W., 813 lks. dist.
43.00	Enter brush.
65.84	Lake. Set post; from which A pine, 10 in. dia., bears S.74°W., 60 lks. dist. A pine, 15 in. dia., bears N.8 $\frac{1}{2}$ °E., 164 lks. dist.
66.84	Flag in line. Across S. of flag. Base N.12 $\frac{1}{2}$ °E., 290; angle opposite 11°, distance 6.07.
72.91	Leave lake. Set post; from which A willow, 3 in. dia., bears S.45°W., 18 lks. dist. An alder, 6 in. dia., bears N.28°E., 29 lks. dist.
80.25	To sec. corner on margin of lake.
	West, on true line, between secs. 5 & 8. Var.20°E.
	In line on W. side of lake. Base N. 100 lks. Sec. corner bears S.77°E., distance 4.33.
4.33	Set meander post; from which A pine, 3 in. dia., bears N.24°W., 60 lks. dist.. A pine, 10 in. dia., bears S.55°W., 105 lks. dist.
9.50	Ridge, course N. & S.
40.00	Set qr. sec. post; from which A pine, 10 in. dia., bears N.15°E., 230 lks. dist. A pine, 10 in. dia., bears S.39 $\frac{3}{4}$ °E., 235 lks. dist.
54.00	Shore of the Pacific Ocean. Witness corner N.7 $\frac{1}{2}$ °E., 440 lks. dist., a natural mound, 6 ft. high.
	West, on true line, between secs. 8 & 17.
40.00	Set qr. sec. post; from which