

Subdivisions of T. 20 S., R. 12 W.  
 Survey by Wm. H. Byars under Contract 745 dated May 1st, 1902.

## CHAINS

From the cor. of secs. 13 and 24, T. 20 S., R. 12 W., on E. bdy. of Tp., where I find witness trees cut down, stumps and cor. standing and agreeing with notes furnished by the surveyor general, I run

N.89°47'W., on random line, bet. secs. 13 and 24.

40.00 Set tem.  $\frac{1}{4}$  sec. cor.

79.75 Intersect N. & S. line at cor. of secs. 13, 14, 23 and 24. Cor. post destroyed, witness trees standing and agree with notes furnished by the surveyor general. I reestablish the corner with a spruce post from witness trees, 4 ft. long, 4 ins. sq., 24 ins. in the ground, marked T 20 S S 13 on NE., R 12 W S 24 on SE., S 23 on SW. and S 14 on NW. faces, with 3 notches on S. and 1 notch on E. edges; from which

A spruce, 36 ins. diam., bears S.52°W., 48 lks. dist.

A vine maple, 6 ins. diam., bears S.21°E., 51 lks. dist.

A fir, 30 ins. diam., bears N.3°W., 78 lks. dist.

A fir, 30 ins. diam., bears N.4°E., 67 lks. dist.

Thence I run

S.89°47'E., on true line, bet. secs. 13 & 24.

Steep ascent about 200 feet.

3.20 Top of spur, course NW.; along steep N. slope.

5.00 Steep descent about 200 ft.

8.00 A creek, 1 lk. wide, course N.; steep ascent along NW. slope.

14.25 Top of spur on line, course N.; descend about 200 ft.

17.25 A creek, 2 lks. wide, course NW. from E. Creek, 1 lk. wide, from SE.

20.25 Leave creek, flows from SE.; steep ascent about 600 ft.

31.75 Top of spur on line, course NW.; across draw, course N.

38.00 Top of ridge, course N. & S.

40.00 Set a spruce post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 13 on the N. and 24 on the S. faces; from which