

## Subdivisions of T. 20 S., R. 12 W.

CHAINS

A spruce, 30 ins. diam., bears S.44°W., 15 lks.dist.,  
marked  $\frac{1}{4}$  S 24 B T.

A spruce, 12 ins. diam., bears N.46 $\frac{1}{2}$ °W., 15 lks.dist.,  
marked  $\frac{1}{4}$  S 13 B T.

Steep descent, about 400 ft.

50.75 A creek, 1 lk. wide, course NE.; steep ascent about 100 ft.

58.25 Top of spur, course N.80°E.; descend along spur.

65.50 Enter slashing, course N. & S.

70.50 Enter creek bottom, course N. & S.

72.25 Creek, 2 lks. wide, course SE.; ascend SW. slope.

75.25 Enter G. W. Slonker's enclosures.

77.85 Enter G. W. Slonker's house.

79.75 The cor. of secs. 13 and 24.

From the cor. of secs. 13, 14, 23 and 24 I run

S.0°21'E., along blazed line bet. secs. 23 and 24.

Steep ascent, about 100 ft.

3.25 Top of spur on line, course W.; steep descent about 300 ft.

11.35 Creek, 1 lk. wide, course W.; over spur, course W.

21.25 Witness cor. bet. secs. 23 and 24. Corner gone, witness trees standing and agree with notes furnished by the surveyor general. I reestablish the witness cor. by setting a sandstone, 20x12x4 ins., 14 ins. in the ground, marked W C on NE. face; from which (old witnesses)

A spruce, 100 ins. diam., bears S.3°W., 27 lks. dist.

An alder, 12 ins. diam., bears N.10°E., 80 lks.dist.

Thence I run S.0°1'E., on random line, bet. secs. 23 and 24.

40.00 Set tem.  $\frac{1}{4}$  sec. cor.

81.00 Intersect E. & W. line, 130 lks. West of cor. of secs. 23, 24, 25 and 26. Post and one witness tree destroyed.

Reestablish cor. by setting a hemlock post, 4 ft. long,

4 ins. sq., 24 ins. in the ground and marked T 20 S S

24 on the NE., R 12 W S 25 on the SE., S 26 on the SW.

and S 23 on the NW. faces, also 2 notches on the S. and

1 notch on the E. edges; from which

A spruce, 36 ins. diam., bears N.66°E., 51 lks.dist.

A spruce, 36 ins. diam., bears S.65°E., 20 lks.dist.