

## Subdivisions of T. 20 S., R. 12 W.

CHAINS

A spruce, 36 ins. diam., bears N.55°W., 13 lks. dist.

A spruce, 48 ins. diam., bears S.76°W., 40 lks. dist.

marked T 20 S R 12 W S 26 B T; this tree is in place of the one destroyed.

At the point of intersection

Set a hemlock post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for closing cor. of secs. 23 and 24, marked C C T 20 S R 12 W on N., S 24 on E. and S 23 on W. faces, with 2 grooves on S. and 1 groove on E. faces; from which

A spruce, 28 ins. diam., bears N.20°E., 40 lks. dist., marked T 20 S R 12 W S 24 B T.

A hemlock, 30 ins. diam., bears N.23½°W., 30 lks. dist., marked T 20 S R 12 W S 23 B T.

Destroyed all markings referring to Secs. 23 and 24 on the old corner and its witnesses.

Thence I run N.0°1'W., on true line, bet. secs. 23 and 24.

Steep descent, about 100 ft.

- 5.00 A creek, 2 lks. wide, course W.; steep ascent about 600 ft.
- 16.00 Top of spur on line, course W.; steep descent about 600 ft.
- 27.50 A creek, 1 lk. wide, course W.; steep ascent about 600 ft.
- 36.75 Top of ridge, course NW. & SE.; dim trail along ridge.  
Steep descent about 100 ft.
- 41.00 Set a larch post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for the ¼ sec. cor., marked ¼ S 23 on W. and 24 on E. faces; from which
- An elder, 4 ins. diam., bears N.7°E., 22 lks. dist., marked ¼ S 24 B T.
- An elder, 5 ins. diam., bears S.35°W., 25 lks. dist., marked ¼ S 23 B T.
- Continue steep descent about 500 ft.
- 59.50 A creek, 2 lks. wide, course N.70°W.
- 59.75 The witness cor., heretofore described.  
Thence N.0°21'W., bet. secs. 23 and 24.
- 81.00 The cor. of secs. 13, 14, 23 and 24.

July 27, 1905.