

Subdivisions of T. 20 S., R. 12 W.

CHAINS

An alder, 18 ins. in diam., bears S.40°E., 34 lks. dist., marked M C T 20 S R 12 W S 12 B T.

An alder, 18 ins. in diam., bears N.20°W., 19 lks. dist., marked M C T 20 S R 12 W S 1 B T.

A house bears N.22°W., 3.00 chs. dist.

Steep ascent about 200 ft.

38.75 Top of spur, course N.

43.77 1/4 sec. cor. Post and trees gone; stumps of trees standing.

Reestablish the 1/4 sec. cor. by setting a fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, and marked S 1 1/4 S on the N. and S 12 1/4 S on the S. faces; from which

A spruce, 14 ins. in diam., bears S.53°W., 30 lks. dist., marked S 12 1/4 S B T.

An alder, 14 ins. in diam., bears N.3°W., 27 lks. dist., marked S 1 1/4 S B T.

The stumps of the old bearing trees as indicated by the field notes furnished by the surveyor general.

48.75 Top of spur on line, c N.; descend.

61.60 Enter willow and alder marsh, course N. & S.

62.75 A creek, 5 lks. wide, course N.

64.50 Leave marsh, course N. & S.

67.75 Brewster's old house 10 lks. S. of line.

68.25 Steep descent about 75 ft.

70.25 Intersect E. margin of arm of lake. I was unable to find the meander post or the witnesses thereto.

Mark an alder, 8 ins. in diam., M C on the E., T 20 S R 12 W on the W., S 1 on the N. and S 12 on the S. sides, for the meander cor. of frac. secs, 1 and 12, E. arm of lake. No other trees convenient for bearing trees.

To determine distance across I set flag on line on W. shore; then measure a base S.2°21'E. 100 lks. to point, whence flag bears N.88°W. and the angle opposite is 4° 21' and the dist. is cotan. 4°21' by base or 13.146 by 100 = 13.15 chs., making