

Subdivisions of T. 20 S., R. 12 W.

CHAINS

83.40

To W. shore. Up bluff.

84.40

The cor. of secs. 1, 2, 11 & 12 is gone and witness trees cut down; stumps standing. Reestablish the cor. from the old stumps by marking a maple, 8 in. in diam., T 20 S S 1 on the NE., R 12 W S 12 on the SE., S 11 on the SW. and S 2 on the NW. faces, also 5 notches on the S. and 1 notch on the E. angle of same; from which

A hemlock, 8 ins. in diam., bears N.86°E., 35 lks. dist., marked T 20 S R 12 W S 1 B T.

A maple, 5 ins. in diam., bears S.43°E., 3 lks. dist., marked T 20 S R 12 W S 12 B T.

A maple, 8 ins. in diam., bears S.45°W., 3 lks. dist., marked T 20 S R 12 W S 11 B T.

A spruce, 7 ins. diam., bears N.9°W., 49 lks. dist., marked T 20 S R 12 W S 2 B T.

August 1, 1905.

From the cor. of secs. 13, 14, 23 and 24, I run N.0°3'E., along blazed line, bet. secs. 13 and 14.

Ascend in dense undergrowth.

4.50 Top of spur, course N.60°W.; steep descent about 400 ft.

15.50 Enter creek bottom, course E. & W.

17.00 Creek, 4 lks. wide, course W.

18.50 Leave bottom, course E. & W.

Over spur, about 50 ft. above creek.

26.25 A creek, 1 lk. wide, course SW.; steep ascent about 600 ft.

40.00 Set a maple post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for the $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 14 on the W. and S 13 on the E. faces; from which

A spruce, 48 ins. in diam., bears East, 40 lks. dist., marked $\frac{1}{4}$ S 13 B T.

A spruce, 30 ins. in diam., bears N.62°W., 32 lks. dist., marked $\frac{1}{4}$ S 14 B T.

47.00 Top of ridge, course E. & W.; across draw, course E.

66.50 Top of spur on line, course SE.; across head of draw, course E.