

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 12 W.

CHAINS

- 74.45 Top of spur on line, course N.80°E.; descend to corner.
- 80.00 Mark a spruce, 8 ins. in diam., T 20 S S 12 on the NE.,  
R 12 W S 13 on the SE., S 14 on the SW. and S 11 on the  
NW. faces, with 4 notches on the S. and 1 notch on the  
E. sides of the same, for cor. of secs. 11, 12, 13 and  
14; from which
- A spruce, 12 ins. in diam., bears N.60°E., 7 lks.  
dist., marked T 20 S R 12 W S 12 B T.
- A spruce, 30 ins. in diam., bears S.45°E., 35 lks.  
dist., marked T 20 S R 12 W S 13 B T.
- A spruce, 14 ins. in diam., bears S.45°W., 25 lks.  
dist., marked T 20 S R 12 W S 14 B T.
- A spruce, 8 ins. in diam., bears N.30°W., 25 lks.  
dist., marked T 20 S R 12 W S 11 B T.

July 29th, 1905.

- S.89°56'E., along blazed line, bet. secs. 12 and 13.
- 2.50 Top of spur on line, course N.; steep descent, about 600  
ft.
- 9.75 Creek, 5 lks. wide, course N.  
Narrow bottom along creek, about 3.00 chs. wide; steep  
ascend, about 600 ft.
- 22.50 Top of ridge, course N.60°W. & S.60°E.; steep descent  
about 600 ft.
- 40.00 Set a maple post, 4 ft. long, 4 ins. sq., 24 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 12 on N. and S 13  
on S. faces; from which
- An alder, 24 ins. in diam., bears N.85°E., 47 lks.  
dist., marked  $\frac{1}{4}$  S 12 B T.
- An elder, 4 ins. diam., bears S.28°W., 14 lks.  
dist., marked  $\frac{1}{4}$  S 13 B T.
- 41.90 A creek, 5 lks. wide, course N.  
A narrow valley, about 3.00 chs. wide, along creek;  
steep ascent, about 600 ft.
- 58.00 Top of spur on line, course NW.; steep descent, about