

Subdivisions of T. 20 S., R. 12 W.

CHAINS

From this old $\frac{1}{2}$ sec. cor. I run
 North along blazed line, on E. bdy. of sec. 13.
 48.00 Top of ridge, course NE. & SW.; steep descent.
 64.00 Enter slashing, course E. & W.
 68.00 Leave slashing. A creek, 1 lk. wide, course NW.
 70.50 Enter slashing, course N.
 House E., 8.00 chs. dist.
 80.09 The corner of secs. 12 and 13, heretofore described.
 The true course of the line of the E. bdy. of sec. 13 is
 North and the length of same is 80.09 chs.

July 30th, 1905.

From the cor. of secs. 3, 4, 9 and 10, the post and witness trees to this cor. are all destroyed, excepting the spruce, 36 ins. in diam., bearing N.60°E., 100 lks. dist., it is down, but yet recognizable. I re-establish this cor. by marking a hemlock, 8 ins. in diam., T 20 S S 3 on the NE., R 12 W S 10 on the SE., S 9 on the SW. and S 4 on the NW. faces and 5 notches on the S. and 3 notches on the E. angles of the same; from which

A hemlock, 8 ins. diam., bears N.45°E., 17 lks. dist., marked T 20 S R 12 W S 3 B T.

A hemlock, 24 ins. diam., bears S.60°E., 18 lks. dist., marked T-20 S R 12 W S 10 B T.

A hemlock, 16 ins. diam., bears S.40°W., 26 lks. dist., marked T 20 S R 12 W S 9 B T.

A chitterwood, 5 ins. diam., bears N.65°W., 48 lks. dist., marked T 20 S R 12 W S 4 B T.

In place of the old witness tree- A spruce, 36 ins. diam., bears N.60°E., 100 lks. dist.

August 31, 1902.

N.89°56'W., on a random line, bet. secs. 4 and 9.

40.00 Set tem. $\frac{1}{2}$ sec. cor.

79.03 Intersect sec. line, 40 lks. S. of the cor. of secs. 4, 5, 8 and 9. Corner and witnesses agree with notes fur-