

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 12 W.

CHAINS

nished by the surveyor general.

Thence I run

S.89°39'E., on true line, bet. secs. 4 & 9.

3.00 Gradual ascent. Dense undergrowth.

34.00 Top of ridge, c NW. & SE., about 200 ft. above corner.

40.00 Set a spruce post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, marked S 4 1/4 S on the N. and S 9 1/4 S on the S. faces, for 1/4 sec. cor. and from which

A spruce, 60 ins. diam., bears N.80°W., 35 lks. dist., marked S 4 1/4 S B T.

A spruce, 60 ins. diam., bears S.80°E., 30 lks. dist., marked S 9 1/4 S B T.

Over rolling hills.

79.03 The cor. of secs. 3, 4, 9 and 10.

Sept. 1st, 1902.

North, on random line, bet. secs. 3 and 4.

40.00 Set temp. 1/4 sec. cor.

80.00 Being unable to find the established corner of secs. 3, 4, 33 and 34 I set temp. cor. and go to the meander cor. on the W. border of Lake Tsiltcoos on the N. bdy. of the Tp. on line bet. secs. 3 and 34, which is given me as being 31.39 chs. W. of the sec. cor. I find the post gone and one witness tree down. Re-establish the cor. by setting a fir post, 4 ft. long, 4 ins. square, 24 ins. in the ground and marked T 19 S S 34 on the N., M C on the E., T 20 S S 3 on the S. and R 12 W on the W. faces; from which

(Old B.T.), a spruce, 7 (now 16) ins. diam., bears N.13°W., 11 lks. dist., marked T 19 S R 12 W S 34 B T.

A fir, 16 ins. diam., bears S.75°W., 47 lks. dist., marked T 20 S R 12 W S 3 B T.

Thence I run

West, on blank line, bet. secs. 3 and 34.