

## Subdivisions of T. 20 S., R. 12 W.

CHAINS

notches on the W. faces.

Sept. 3, 1902.

North, on random line, bet. secs. 3 and 4.

40.00 Set tem.  $\frac{1}{4}$  sec. cor.

80.00 Being unable to find the cor. of secs. 3, 4, 33 and 34,

I proceed to resurvey the N. bdy. of secs. 3 and 4  
(notes heretofore given).

Sept. 2, 1902.

The cor. of secs. 33 and 34, T. 19 S., R. 12 W. is 1.14  
chs. N. and 0.80 chs. E. of the tem. cor. set on the  
random line bet. secs. 3 and 4.At the point of intersection, I set a spruce post, 4 ft.  
long, 4 ins. sq., 24 ins. in the ground, for the closing  
cor. of secs. 3 and 4, marked S 3 on the E., C C T 20  
S R 12 W on the S. and S 4 on the W. faces and 3  
grooves on E. & W. faces; from whichA spruce, 30 ins. diam., bears S.36°E., 25 lks.  
dist., marked T 20 S R 12 W S 3 C C B T.A spruce, 60 ins. diam., bears S.54°W., 59 lks.  
dist., marked T 20 S R 12 W S 4 C C B T.

From the cor. of secs. 3, 4, 9 and 10,

North, on blazed line, bet. secs. 3 &amp; 4,

4.00 Top of spur on line, course NE.; steep descent about 100  
feet.

15.75 Enter creek bottom, course SE. &amp; NW.

16.75 A creek, 5 lks. wide, course SE.

19.75 Begin ascent.

40.00 Set a hemlock post, 4 ft. long, 4 ins. sq., 24 ins. in  
the ground, marked S 3  $\frac{1}{4}$  S on the E. and S 4  $\frac{1}{4}$  S on  
the W. faces, for the  $\frac{1}{4}$  sec. cor.; from whichA hemlock, 10 ins. diam., bears S.10°E., 14 lks.  
dist., marked S 3  $\frac{1}{4}$  S B T.

A hemlock, 12 ins. diam., bears S.82°W., 28 lks.