

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 21 S., R. 11 W.
Survey by John W. Meldrum under Contract 116 dated Dec. 16, 1866.

CHAINS

North between secs. 3 & 4.

* * * * *

80.00 Set post for corner to secs. 3, 4, 33 & 34.

A fir, 30 in. diam., bears N.55°W., 47 lks. dist.

A hemlock, 8 in. diam., bears N.48°E., 33 lks. dist.

A fir, 24 in. diam., bears S.25°E., 18 lks. dist.

A fir, 33 in. diam., bears S.55°W., 30 lks. dist.

East on North boundary of Sec. 3.

Var.19°East.

30.78 Creek, 40 lks. wide, runs SW.

40.00 Set 1/4 sec. post; from which

A maple, 20 in. diam., bears N.60°E., 21 lks. dist.

An alder, 12 in. diam., bears S.20°W., 22 lks. dist.

65.80 Right bank of Smiths River and set meander post; from

which

A spruce, 18 in. diam., bears S.50°W., 85 lks. dist.

A maple, 20 in. diam., bears S.19°E., 26 lks. dist.

I cause flag to be set on left bank on line; I then run

N.20°E. 250 lks. for base. Flag bears S.58 1/2°E., distance

across the river 4.69 chs.

70.49 Set meander post on left bank; from which

An alder, 30 in. diam., bears S.46°E., 80 lks. dist.

A spruce, 40 in. diam., bears N.25°E., 27 lks. dist.

80.00 Set post for corner to secs. 2, 3, 34 & 35; from which

An alder, 10 in. diam., bears S.8°W., 70 lks. dist.

A willow, 4 in. diam., bears N.15°W., 89 lks. dist.

An alder, 7 in. diam., bears N.70°E., 30 lks. dist.

An alder, 12 in. diam., bears S.4°E., 73 lks. dist.

Jan. 18th, 1869.

East on North boundary of Sec. 2.

Var.19°East.

21.70 Smiths River and set meander post on left bank; from

which