

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS	in accordance with your field notes, I run North, on line, between secs. 34 & 35. Var. 20° East.	
42.00	Ravine, c SE.; begin ascent.	-10
49.67	Top of burnt spur; as the line north passes over 4 ravines filled with burnt timber, fallen logs, and wild gooseberry brush, I set here a back flag and go to the third spur on line; thence lay off base N. 60° 40' W., 5.00 chs.; back flag bears S. 6° 15' E., making northing 37.41 chs.; thence South 7.08, making northing 30.33 chs.	+300
80.00	Set post on a small spur, close to rocky cliff, for corner to secs. 26, 27, 34 & 35; from which A chittewood, 6 in. in dia., bears N. 6½° W., 80 lks. dist. There is no other living tree in sight, no chance for any pits, as the rock is too close to the surface. November 26, 1879.	
<hr/>		
	West, on random line, bet. secs. 27 & 34. Var. 20° East.	
80.60	Intersect 93 lks. North of post to corner of secs. 34, 33, 28 & 27. N. 89° 20' East, on true line, bet. secs. 27 & 34. Ascend.	
2.50	Top of ridge; thence along South slope of a timber flat.	+40
25.25	Gulch, c South; begin to ascend.	-80
32.50	Top of ridge, c N. & S.	+120
40.30	Set ¼ sec. post; from which An alder, 5 in. in dia., bears N. 48½° E., 13 lks. dist. A chittewood, 5 in. in dia., bears S. 65½° W., 23 lks. dist.	
42.00	Gulch, c S.; begin ascent.	-80
51.20	Top of spur, c NE. & SW.	+120
62.50	Top of main dividing ridge, c N. & S.	+100