

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 11 W.

CHAINS	A fir, 42 in. in dia., bears N.16°W., 20 lks. A fir, 36 in. in dia., bears N.18°E., 46 lks.	
41.00	Top of ridge, c E. & W.; begin descent. Nov. 29th.	+350
45.90	Fir, 30 in. in dia.	
47.80	Canyon, c E.; begin ascent.	-120
50.00	Top of spur, c E. & W.; begin descent.	+60
52.50	Canyon, c E.	-40
54.80	Alder, 15 in. in dia.	
62.50	Top of main ridge, c E. & W.; begin very steep descent. 25 lks. E. is a canyon with perpendicular sides of bare rock.	+400
69.80	Fir, 56 in. in dia.	
70.70	Canyon, c NW., above mentioned; it has been washed out clean to the bedrock, taking even the timber down. Begin ascent.	-300
76.50	Top of spur, c NW. & SE.	+40
79.00	Canyon, c W.; begin very steep ascent.	-200
80.00	Post for corner to secs. 25, 26, 24 & 23 is a fir, 15 in. in dia.; from which A fir, 12 in. in dia., bears N.55°E., 12 lks. An alder, 8 in. in dia., bears N.64°W., 54 lks. An alder, 4 in. in dia., bears S.2°W., 223 lks. An alder, 9 in. in dia., bears S.2½°E., 193 lks.	+80
	West, on random line, bet. secs. 26 and 23. Var.20°East.	
80.96	Intersect south 40 lks. of corner of sections 26, 27, 23 and 22. November 30. S.89°43'E., on true line, between secs. 26 and 23. Var.20°East.	
0.25	Trail to the Lake country, c North.	
0.50	Branch, c SE., 5 lks. wide.	
2.20	Foot of hill; begin ascent.	