

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 19 S., R. 11 W.

CHAINS

- 24.85 Fiddle Creek, 40 lks. wide, course N.20°W.
- 27.50 Pond. Offset South 50 lks. to avoid same.
- 28.14 Offset again 50 lks. further to avoid same.
- 31.11 Offset North 100 lks. into line and North 150 lks. to avoid swamp.
- 34.08 Swamp; offset North 90 lks. to avoid same.
- 37.00 Offset South 240 lks. into line.
- 40.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which
 A maple, 12 ins. diam., bears N.6 $\frac{1}{2}$ °E., 33 lks.dist., marked $\frac{1}{4}$ S B T.
 A maple, 12 ins. diam., bears S.61°W., 46 lks.dist., marked $\frac{1}{4}$ S B T.
- 41.43 Fiddle Creek, 40 lks. wide, c S.20°W.
- 42.96 Fiddle Creek, 40 lks. wide, c N.40°W.

Nov. 7th, 1889.

- 49.00 Leave bottom; ascend gradually.
- 54.00 Enter bottom again.
- 55.00 On N. edge of Fiddle Creek, c W.
- 59.30 Stream, 5 lks. wide, c South.
- 70.20 Leave bottom.
- 80.00 On low hill sloping South.
 Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 34, 35, 2 & 3, marked T 19 S S 35 on NE., T 20 S S 2 on SE., R 11 W S 3 on SW., S 34 on NW. faces, with 2 notches on East and 4 on West edges; from which
 A cedar, 36 ins. diam., bears N.52°W., 138 lks.dist., marked T 19 S R 11 W S 34 B T.
 A cedar, 36 ins. diam., bears N.33 $\frac{1}{2}$ °E., 140 lks.dist., marked T 19 S R 11 W S 35 B T.
 A cedar, 36 ins. diam., bears S.75 $\frac{1}{2}$ °E., 110 lks. dist., marked T 20 S R 11 W S 2 B T.
 A cedar, 36 ins. diam., bears S.88°W., 246 lks. dist., marked T 20 S R 11 W S 3 B T.