

South Bdy. of T. 19 S., R. 11 W.

CHAINS

1 on SW. and R 11 W S 36 on NW. faces, with 6 notches on each edge; from which

A cherry, 5 ins. diam., bears N.76°W., 18 lks. dist., marked T 19 S R 11 W S 36 B T.

A fir, 50 ins. diam., bears S.46½°W., 45 lks. dist., marked T 20 S R 11 W S 1 B T.

A fir, 36 ins. diam., bears N.77½°E., 29 lks. dist., marked T 19 S R 11 W S 31 B T.

A cherry, 5 ins. diam., bears S.32½°E., 33 lks. dist., marked T 20 S R 10 W S 6 B T.

Exterior and Subdivisional Lines of T. 20 S., R. 11 W. Survey by Wm. Thiel under Contract 567 dated Feb. 16, 1891.

I begin at the cor. to secs. 25, 36, 30 & 31, T. 20 S., Rs. 10 & 11 W., which is a post, 4 ins. sq., much decayed, marked T 20 S S 30 on NE., R 10 W S 31 on SE., R 11 W S 36 on SW., S 25 on NW. faces, with 1 notch on S. and 5 notches on N. edges; from which

A maple, 7 ins. dia., bears N.45°E., 69 lks. dist., marked T 20 S R 10 W S 30 B T.

A maple, 18 in. dia., bears S.35°W., 60 lks. dist., marked T 20 S R 11 W S 36 B T.

A maple, 5 ins. dia., bears N.37°W., 38 lks. dist., marked T 20 S R 11 W S 25 B T.

A hazel, 3 ins. dia., bears S.15°E., 35 lks. dist., marked T 20 S R 10 W S 31 B T.

I replace the old post by setting a sandstone, 14x11x6 ins., 10 ins. in the ground, marked with 1 notch on S. and 5 notches on N. edges.

Thence I run

North on line bet. secs. 30 and 25.

Var. 20°20'E.

Descend.

4.00 A creek, 5 lks. wide, course SE.; begin ascent of E. slope. -40

33.50 Top of ridge, bears E. & W.; descend. +450