

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 20 S., R. 11 W.

CHAINS

- 40.00 Set a post, 3 ft. long, 3 ins. sq., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; and raised a mound of stone, $1\frac{1}{2}$ ft. high and 2 ft. base alongside. Fits impracticable.
The old cor. and its bearing trees have been burned; there is now only a thick growth of thimbleberries on this place.
Descend.
- 41.75 A canyon, course E. -150
- 42.50 Bare bedrock.
- 52.00 Top of ridge, bears NE. & SW.; descend. +200
- 58.50 A canyon, course NE.; ascend. -25
- 60.50 Top of spur, bears E. & W.; descend. +60
- 63.00 A canyon, course E.; ascend. -75
- 68.75 Top of ridge, bears E. & W.; descend E. slope. +200
- 74.50 Top of spur, bears N.20°E. & S.20°W.; begin descent of E. slope.
- 80.00 Set a post, $4\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 30, 19, 24 & 25, marked T 20 S S 19 on NE., R 10 W S 30 on SE., R 11 W S 25 on SW., S 24 on NW. faces, with 2 notches on S. and 4 notches on N. edges; from which
A fir, 40 ins. diam., bears N.76°E., 14 lks. dist., marked T 20 S R 10 W S 19 B T.
A fir, 12 ins. diam., bears S.3°E., 105 lks. dist., marked T 20 S R 10 W S 30 B T.
A fir, 7 ins. diam., bears S.61 $\frac{1}{2}$ °W., 44 lks. dist., marked T 20 S R 11 W S 25 B T.
A fir, 8 ins. diam., bears N.2°W., 107 lks. dist., marked T 20 S R 11 W S 24 B T.

North between secs. 24 and 19.

Var. 20°11'E.

Descend.

- 6.00 A canyon, course E.; begin ascent. -125