

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 11 W.

CHAINS

A fir, 30 ins. dia., bears N.38°W., 65 lks. dist.,
marked $\frac{1}{2}$ S B T, old bearing tree.

A vine maple, 4 ins. dia., bears S.83 $\frac{1}{2}$ °E., 13 lks.
dist., marked $\frac{1}{2}$ S B T, new bearing tree.

June 11th, 1892.

Thence I run

S.0°34'W., on true line, bet. secs. 7 & 12.

Va.20°20'E.

.25	A canyon, course W.; ascend.	
2.40	Top of spur, bears E. & W.; descend.	+30
6.00	A canyon, course W.	-50
11.00	Enter bottom, bears SW. & NE.	-40
13.25	A creek, 6 lks. wide, course W.	
14.00	Leave bottom; ascend W. slope.	
20.00	Top of spur, bears E. & W.; descend.	+75
30.50	A canyon, course NW.; ascend.	-60
35.75	Top of spur, bears NW. & SE.; descend.	+120
40.50	A canyon, course W.	-100
43.50	A canyon, course W.; ascend.	-60
47.60	An alder, 8 ins. dia., which I marked for cor. to secs. 7, 12, 13 & 18, T 20 S S 7 on NE., R 11 W S 18 on SE., R 12 W S 13 on SW., S 12 on NW. faces, with 2 notches on N. and 4 notches on S. sides; from which A fir, 36 ins. dia., bears N.51 $\frac{1}{2}$ °E., 30 lks. dist., marked T 20 S R 11 W S 7 B T. An alder, 9 ins. dia., bears S.66°E., 17 lks. dist., marked T 20 S R 11 W S 18 B T. A fir, 36 ins. dia., bears S.18°W., 9 lks. dist., marked T 20 S R 12 W S 13 B T. An alder, 8 ins. dia., bears N.89°W., 5 lks. dist., marked T 20 S R 12 W S 12 B T.	

S.0°34'W., on true line, bet. secs. 13 and 18.

Va.20°16'E.

Ascend.