

## County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 11 W.

CHAINS

dist., marked T 20 S R 12 W S 24 B T.

A hemlock, 4 ins. dia., bears N.25°W., 9 lks. dist.,  
marked T 20 S R 12 W S 13 B T.

S.0°34'W., on true line, bet. secs. 19 & 24.

Var.20°12'E.

Descend.

3.60 Enter swamp, or marsh, covered by a dense growth of  
willows and by water up to 2 ft. in depth; I, therefore,  
make an offset

North	3.60 chains.
East	3.00 "
N.70½°E.,	1.50 "
N.36° E.,	2.85 "
S.80½°E.,	2.15 "
N.88° E.,	7.30 "
S.34° W.,	7.55 "
S.65½°W.,	2.70 "
S.56° W.,	1.73 "
S.44° W.,	2.78 "
S.30½°W.,	1.83 "
S.39° W.,	2.23 "
S.20° W.,	1.58 "
S.50° W.,	1.75 "
N.52½°W.,	1.72 "

12.50 Intersect witness corner to secs. 18, 19, 13 & 24.

June 13th, 1892.

North Bdy. of T. 21 S., R. 11 W.

Survey by Wm. Thiel under Contract 567 dated Feb.16,1891.

I begin at the cor. of secs. 3, 4, 33 & 34, on the N.  
bdy. of this Tp., which I replace by setting a post,  
4½ ft. long, 4 ins. sq., 24 ins. in the ground, marked  
T 20 S S 34 on NE., R 11 W S 3 on SE., T 21 S S 4 on  
SW., S 33 on NW. faces, with 3 notches on E. & W.  
edges; from which